

The Worldwide Leader in LED Technology. Please Visit Us at Lightfair 2008 Booth # 1380

Dialight	Please Visit Us at Lightfair 2008 Booth # 1380					
Product Navigation	Home About	t Us 🗧 Products 🗧 I	nvestor Relations	News	Contact Us	Secure EAX
Circuit Board Indicators						
Panel Mount Indicators	Circuit Board Indicators - Through Hole Indicators OM# 5530212002E 3 mm Lens					
Solid State Lighting	P/N# 5530212002F	3 mm	Lens			
Traffic Signals	Description Package Options	3 mm Bi-Level CBI 60 Pieces Per Tube				
Vehicle Lighting	Product Type	Through Hole Indicators				
Rail	Sub Product Type Configuration	with Bi-Level Housing 3 mm Lens				
Obstruction Lighting	Viewing	Right Angle				
Hazardous Area Lighting	Viewing Angle Test Current (mA)	60 2mA				
Heliport Lighting	Absolute Maximum Ratings (Ta = 25 °) Distributor Stock Check					
sales contacts	Solder Temp Operating Temp Storage Temp	260° for 5 sec -55 to +100° C -55 to +100° C RoHS /pB Free view PDF			Check stock with now. 5530212002F Check stock ()	our distributors
Product Line Search Please select a Product Line	Operating Characteristics					
to search.	LED Position		Found in position (a), 2			
find ()	LED POSIDON	Found in position(s): 1	Found in position(s): 2			
	Color	Red	Green			
Part # / Text Search	Lamp Type	Single Color	Single Color			
Part No.: Text Search:	LED Type	Low Current	Low Current			
	Intensity Min (mcd)	1.0	1.0			
	Intensity Typ (mcd)	1.6	1.6			
search	Intensity Max (mcd)					
-> quick links	Fwd Voltage Min					
Dialight Corporate Video	Fwd Voltage Typ					
	Fwd Voltage Max					
Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. View PDF File	Dom Wavelength Min (nm)					
	Dom Wavelength Typ (nm)					
	Dom Wavelength Max (nm)					
	Power Dissipation Max (mW)	20	20			
Application Notes FAQs	Backlighting					
	Pitch Between Vertical					
Dialight Ltd (UK) Dialight Garufo Dialight BLP LumiDrives	Pitch Between Horizontal					
	Lum Intensity Min					
	Lum Intensity Typ					
	Lum Intensity Max					



Copyright 2006 Dialight. All rights reserved | Privacy Policy