
# **Spec Sheet**

# SMD Power Inductors (NR series S type)

# NRS4018T1R0NDGJ



#### Features

- Item Summary1.0uH±30%, 3.2A, 4.0x4.0x1.8mm
- Lifecycle Stage
  - Mass Production
- Standard packaging quantity (minimum)
  Taping Embossed 3500pcs


### Products characteristics table

Inductance	1.0 uH ± 30 %
Case Size (mm)	4.0x4.0
Rated Current (max)	3.2 A
Saturation Current (max)	4 A
Saturation Current (typ)	4.59 A
Temperature Rise Current (max)	3.2 A
Temperature Rise Current (typ)	3.72 A
DC Resistance (max)	32.4 mΩ
DC Resistance (typ)	27 mΩ
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	90 MHz
Operating Temp. Range	-25 to +125 ℃ (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 20 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

#### External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 1.8 mm
Dimension e	1.1 ±0.2 mm
Dimension f	2.5 ±0.2 mm

# Recommended Land Patterns



2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the Date at any time without notice. Before making final selection, please check product specification.

# SMD Power Inductors (NR series S type)

### NRS4018T1R0NDGJ

Dimension unit : mm unit: inch Length: 4.0 + / - 0.2(0.157 + / - 0.008)Width: 4.0 +/- 0.2 (0.157 + / - 0.008)max. ) Height: 1.8 max. (0.071



Inductance: 1.0 иΗ (test freq at 0.1MHz) DC Resistance: 0.027 / 0.0324 ohm (typ/max)

Saturation Current: 4,000 mA (max) 3,200 mA ( max ) Temp. rise Current:

> Saturation current typical: 30% reduction from initial L value. Temp rise Current typical: Temperature will rise by 40 deg C

