

# Conductor marker carrier - PATG 4/23 - 0808011

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Conductor marker carrier, transparent, unlabeled, mounting type: slide on, cable diameter range: 6 ... 10 mm, lettering field size: 23 x 4 mm

## Your advantages

- The corresponding UC-WMT ..., US-WMT ..., UCT-WMT ... and EMT ... insert labels are used for marking
- These conductor marking systems consist of marker carriers and insert labels
- The PATG ... collar is a captive marker carrier
- ☑ Can be used to mark conductors with a diameter of 0.6 ... 50 mm

## RoHS

# Key Commercial Data

Packing unit	200 pc
Minimum order quantity	200 pc
GTIN	4 017918 168889
GTIN	4017918168889

## Technical data

#### Dimensions

Length (b)	23 mm
Width (a)	7.5 mm
Cable diameter	6 mm 10 mm

#### Ambient conditions

	Ambient temperature (operation)	-50 °C 80 °C
--	---------------------------------	--------------

#### General

Color	transparent
Туре	Profile
Components	Silicone-free
Flammability rating according to UL 94	V0



# Conductor marker carrier - PATG 4/23 - 0808011

# Technical data

### General

Material	PVC	
RoHS compliant	Yes	
Test for substances that would hinder coating with paint or varnish	VW PV 3.10.7:2005-02	
Result	Test passed	
Marking mounting type	slide on	
Standards and Regulations		
Flammability rating according to UL 94	V0	

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com