Circular laser accurately indicates the target area within the circle

Features:

- Instantly measure the temperature of objects without making contact
- High Infrared temperature measurements to 1832°F (1000°C)
- 0.1 to 1.0 adjustable emissivity
- Audible and Visual High/Low Temperature Alarms with red circular laser
- Min/Max/Avg/Diff
- Backlit LCD display with bargraph and selectable °F or °C readout
- Automatic Data Hold
- Auto power off after 8 seconds
- · Low battery indicator
- Includes Type K bead probe, 9V battery and pouch case

Applications:

Measure the surface temperature of objects that are too hot to touch or hard to reach

Measure the temperature of moving objects

Specifications

	-
IR Temperature Range	-58 to 1832°F (-50 to 1000°C)
Accuracy	$\pm 1.0\% \pm 1.8$ °F/1°C at 68 to 572°F (20 to 300°C)
	$\pm 1.5\% \pm 1.8^{\circ}$ F/1°C at 572 to 1832°F (300 to 1000°C)
Resolution	0.1°F/°C
Distance to Target Ratio	20:1
Response Time	150ms
Emissivity	0.10 to 1.0 adjustable
Laser	Circular
Type K Temperature	-58 to 2498°F (-50 to 1370°C)
Accuracy	±(0.5% + 3°F/1.5°C) 32 to 2498°/0 to 1370°C
Power	9V battery
Dimensions	7.5 x 4.3 x 2.2" (190 x 110 x 55mm)
Weight	9.3oz (263g)
Weight	9.3oz (263g)

Ordering Information:

IRT500

20:1 IR Thermometer with Type K





