Electrical Testing per Tusonix standard test plans and Mil-Std-202 Test Methods.

MARKETING SALES DRAWING **DIMENSIONS IN INCHES - DO NOT SCALE THIS DRAWING DIMENSIONS IN METRIC - [] ORIENTATION** .187 ±.005 [4.75 ±0.13] **CIRCUIT** #18 AWG (.040) [1.02] DIA. COPPER, SEE NOTE 3. .425 [10.80] .093 ±.015 [2.36 ±0.38] .266 ±.015 #8-32 UNC-2A [6.76 ±0.38] BRASS, SILVER PLATED. .575 [14.61] REF.

NOTES:

- 1. SUPPLIED WITH SILVER PLATED HEX NUT AND LOCKWASHER.
- 2. TUSONIX STANDARD PART NUMBER: 4201-003. TUSONIX RoHS COMPLIANT PART NUMBER: 4201-003 LF. CUSTOMER MUST SPECIFY STANDARD OR RoHS PART NUMBER WHEN ORDERING.
- 3. LEAD FINISH: STANDARD PART #: 60/40 SOLDER PLATED. RoHS PART #: SILVER PLATED.
- 4. PART MARKING: TRADEMARK AND VARIATION NUMBER ON HEX FLATS. STANDARD PART: BLACK INK. RoHS PART: GREEN INK.

			2000		85°C 200		125 °(15 A	10 G	400 VDC 2 SEC.		5	100 MHz 38	1 GHz 63	10 GHz 70	-
CORD	0	-S. 8-14-85		MT & ADDED		S.M. 07-27-05	3				Unles	ERANCES So Otherwis Specified AL ± .031 [0.1]	e I	BUSHING S ⁻ EMI FILTE		

WAS SK6733-000 RELEASED. L.E. RDN TO COMP FI METRIC, 01-23-02 20020123-2-0 Original Release 20050726-2-1 ADDED NOTES. -2015 Rev-0

TUCSON, ARIZONA

ANGLES ±

.E

Scale 4 X Drawn S.M. 01-23-02

T.C. 01-23-02

Approved

Α 4201-003