# ACL**Staticide**



## **Directions:**

Test on a non-critical area to ensure material and product compatibility. Wearing gloves, apply liberally to surface coating and allow to soak. Flood rinse and clean. Use lint-free wipes to help remove conformal coating. Repeat application as needed. Some heat-cured coatings may require immersion and soaking of coated board.

For industrial use only. Read SDS carefully prior to use.

#### Material Compatibility:

ABS	Fair
Buna-N	Good
EPDM	Good
Graphite	Good
HDPE	Fair
Kynar™	Fair
LDPE	Good
Lexan™	Poor
Neoprene	Poor
Noryl	Fair
Nylon™ 66	Good
Cross-linked PE	Good
Polypropylene	Fair
Polystyrene	Poor
PVC	Good
Silicone Rubber	Fair
Teflon™	Good
Viton™	Good



11 oz (312g) aerosol / 12 per case

## 8698 Staticide<sup>®</sup> Conformal Coating Remover

## Versatile and High-Performing

ACL's Conformal Coating Remover quickly and efficiently removes many types of conformal coatings, including acrylic, silicone, and urethane conformal coatings from PCBs and other surfaces. It can be used as precision coating remover for specific areas or as a full immersion bath.

With its fast stripping action, it easily prepares surfaces for solder rework and repair. Conformal Coating Remover will not fade, crack, yellow, or discolor plastics under normal use conditions. It is compatible with most materials used in electrical and electronic assemblies and is compliant to REACH and RoHS.

### Ideal for the following applications:

- Medical devices
- Automotive
- Marine
- Aerospace
- Engineering and design equipment
- Process control

## **FEATURES:**

- 🕸 Flammable
- **8** Safe for most plastic and PCB surfaces
- Evaporates guickly; non-corrosive
- 8 No CFCs or HCFCs
- REACH and RoHS compliant
- Made in USA

## ACL Staticide

840 W. 49th Place · Chicago, IL 60609 800.782.8420 · 847.981.9212 · fax 847.981.9278 info@aclstaticide.com · www.aclstaticide.com



ACL Inc. registered to ISO-9001 : 2015 Certificate NO. 10002746

Rev. 05/16/2019 MKB