

RF SAW FILTER page 1 of 3

RSF-1457.000-20000-1411-TR

Electrical Specification

Parameters		Value	Unit
Center Frequency (Fo)		1457.000	MHz
Insertion Loss, tpy/max	@ 1447 ~ 1467 MHz	1.4 / 2.0	dB
Amplitude Ripple	@ 1447 ~ 1467 MHz	0.3 / 1.0	dB
Input / Output VSWR	@ 1447 ~ 1467 MHz	1.3 / 2.0	-
Absolute Attenuation, tpy/min	@ 10 ~ 960 MHz	-33 / -36	dB
	@ 1559 ~ 1606 MHz	-35 / -39	dB
	@ 1710 ~ 2170 MHz	-35 / -39	dB
	@ 2300 ~ 2400 MHz	-40 / -45	dB
	@ 2400 ~ 2500 MHz	-40 / -48	dB
	@ 2570 ~ 3000 MHz	-40 / -48	dB
	Input	50	Ω
Terminating Impedance	Output	50	Ω
ESD voltage	ESD(HBM)	50	VDC
Sensitive discharge device	ESD(MM)	175	
DC. Voltage VDC		5	V
Input Power, max, 2000h		29	dBm
Operating Temperature Range		-30 ~ +85	°C
Storage Temperature Range		-40 ~ +85	°C

Dimension





TOP VIEW

BOTTOM VIEW

PIN #	PIN NAME	DESCRIPTION
1	IN	Input
4	OUT	Output
2,3,5	GND	Ground

0.60



RF SAW FILTER page 2 of 3 RSF-1457.000-20000-1411-TR

Frequency Characteristics





RF SAW FILTER page 3 of 3

RSF-1457.000-20000-1411-TR



Environmental

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	2
REACH – SVHC	Compliant
RoHS	Compliant



Tape Dimension



APPROVAL

DRAWN BY	ZZ, August 12, 2021
APPROVED BY	AR, August 12, 2021
REVISION	A, Initial Release

Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable, or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.

RALTRON ELECTRONICS • 10400 N.W. 33rd STREET • Miami, Florida 33172 • U.S.A. Telephone: +1 305-593-6033 • Fax: +1 305-594-3973 • e-mail: sales@raltron.com • web site: http://www.raltron.com