



Features

- Trays that can stack and nest together for improved use of space
- · Great container for Kanban
- Permanently static dissipative foam laminated to our impreganted corrugated material provides ESD and shock protection

Foam Electrical Properties: 1 x 10⁴ to < 1 x 10¹¹ ohms

Foam Thickness: 1/8" (+/- 1/16" tolerances)

ltem	Size I.D L x W x D (IN)	
37750	18 x 11-3/8 x 1-3/4	
37751	22-7/8 x 17-1/4 x 2-3/4	

Dimensional tolerances are +/- 1/8" unless otherwise specified

Meets the required limits of ANSI/ESD S20.20, Packaging standard ANSI/ESD S541, and worksurface standard ANSI/ESD S4.1

SPECIFICATIONS

Properties	Typical Values	Test Procedures/Method
Surface Resistance	1 x 10 ⁶ to < 1 x 10 ⁹ ohms	ANSI/ESD STM11.11
Sloughing Test	Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test.	ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load
	No conductive particles abrased from surface	Rockwell International Test Report of January 8, 1992
Recyclability	Complete recyclability of package	Rockwell International Test Report of January 8, 1992

