Nylon

Nylon is natural filament with exceptional resilience and strength for all your 3D printing needs.

Features & Benefits

Excellent dimensional stability Highly abrasion resistant Chemical resistance Exceptional tensile strength Very low friction coefficient High flexibility

Users

Intermediate

Available Sizes

1.75 mm 3 mm (Filament diameter measures 2.88 mm)

Individual Packaging Stock

1 kg reels 5 lb reels

On Request

0.5 kg reels10 lb reels (lead time maybe longer)15 lb reels (lead time maybe longer)30 lb reels (lead time maybe longer)Coils in various weights

Full Box Packaging

0.5 kg reels packaged 14 to a box1 kg reels packaged 12 to a box5 lb reels packaged 6 to a box

Each box contains the same material, size and color. All filaments are vacuumed sealed with desiccant.

Standard Colors

Natural Black White

Tolerances

+ 0.003" / -0.003"

Recommended Printer Specifications

Optimal Print Temp: 245°C – 280°C Optimal Bed Temp: 110°C – 120°C (PEI film recommended)

Quality

All Keene Village Plastics 3D printer filaments are manufactured in Barberton, Ohio, USA with top quality raw materials and **3-Axis** laser-controlled precision providing the highest class of products for the 3D printing industry.



P.O. Box 24376 Mayfield Heights, OH 44124 sales@villageplastics.com KeeneVillagePlastics.com

P 330 | 753 | 0100 ^{1/1} F 330 | 753 | 6610 2017/1