

## NOTES:

- I. COMPONENTS MOLDED IN A CLEAR TRANSMISSIVE POLYCARBONATE (UL 94V-0 FLAMMABILITY).
- 2. COMPONENTS DESIGNED TO BE PRESSED INTO PANEL.
- 3. STORAGE AND OPERATING TEMPERATURE: -30°C TO 100°C
- 4. DIALIGHT PART NUMBER: 515-1003F

	THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWIN OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.		
١	SCALE: 10.000	DRAWING NUMBER	REV
ı	ALL DIM'S IN: INCHES (MM)	C-17685	١ , ا
	TOLERANCES: UNLESS OTHERWISE SPECIFIED	C-17003	A
	FRACTIONS: ±1/64 DECIMALS (.XX): ±.01 DECIMALS (.XXX): ±.005	(.XXX): ±.01 (.XXX): ±.005  MATERIAL  SEF NOTES	
	ANGLES: ±3°		
	FINISH:	Dialight 1501 ROUTE 3	4 SOUTH NJ 07727
	FSCM 83330	SHEET I OF I FAMILY TABLE:	