Operating Temperature Range

-25° to 70° C, relative humidity of 85% or less

Materials

Revision:

А

Date:

9/4/2009

- 1. Insulator: POM, black
- 2. Shell: C3604 brass, 2 µm nickel plated
- 3. Spring contact: C5191 phosphor bronze, 2 µm nickel plated
- 4. Spring fork: C3604 brass, 1 µ" gold plated

Electrical Requirements

Dielectric strength: 1 min @ 500 Vac Insulation resistance: 100 MΩ @ 500 Vdc Contact resistance: 50 m Ω or less

Mechanical Requirements

Insertion force: 0.4-4 kgf

Withdrawal force: 0.4-4 kgf

Life cycle: 5000 mating cycles while maintaining 0.4 kgf min. insertion force, 0.4 kgf min. withdrawal force and less than $60 \text{ m}\Omega$ contact resistance.

- Environmental Requirements Heat test: 70 °C, relative humidity 70-85% for 96 hours without deformation
- Humidity test: 40 °C, relative humidity 90-100% for 96 hours without deformation
- Salt spray test: 35±2 °C, relative humidity 90-95%, 5% NaCl mist for 24 hrs. Wash parts after test. Maintain mechanical requirements and a contact resistance of less than 100 m Ω .



2

5

Description:

Initial release

3