

Aranet T/RH IP67 sensor



- 1 Monitors temperature and relative humidity
- 2 IP67 casing
- 3 Up to 3 km / 1.9 mi range
- 4 Designed for dusty and humid locations
- 5 GORE membrane for accurate readings



Aranet T/RH IP67 Sensor measures temperature and relative humidity. The IP67 protection allows this device to operate in harsh environmental conditions. The sensor is wireless, battery-powered and ensures constant and reliable data monitoring. T/RH IP67 sensor is compatible with Aranet Cloud.

Aranet T/RH IP67 sensor

TDSPT802 (EU)


Measures the temperature and relative humidity of the environment

TDSPT8U2 (NA)

TDSPT8R2 (RU)

Sensor performance

	Temperature	Relative Humidity
Range	-40 °C to 60 °C (-40 °F to 140 °F)	0-100 %
Resolution	0.1 °C (0.1 °F)	0.1 %
Accuracy ¹	±0.3 °C (±0.5 °F)	± 2 %
Hysteresis	N/A	± 1 %
Long-term drift	0.03 °C/year (0.05 °F/year)	0.5 %/year
Time constant τ (63 %)²	8 minutes	TBD

**Radio parameters**

Line of sight range	3 km (1.9 mi)
Supported ISM bands	EU868, NA915
Transmitter power	14 dBm
Data transmission interval ³	1, 2, 5 or 10 minutes
Data protection	XXTEA encryption
Compatible base stations	Aranet PRO

General

Ingress Protection code	IP67
Maximum operating temperature range	-40 °C to 60 °C (-40 °F to 140 °F)
Dimensions	Ø 35 x 120 mm (Ø 1.4 x 4.7 in)
Weight ⁴	69 g (2.1 oz)
Enclosure material	ASA plastic
Included in the box	1 AA alkaline battery, polyester string

Power 1 AA battery

	Alkaline ⁵	Lithium ⁶
Type	Alkaline ⁵	Lithium ⁶
Operating temperature	-20 °C to 55 °C (-4 °F to 131 °F)	-40 °C to 60 °C (-40 °F to 140 °F)
TX interval	Battery lifetime at 20 °C (68 °F) ⁷	
1 minute	1.8 years	2.3 years
2 minutes	3.4 years	4.7 years
5 minutes	6.9 years	10 years
10 minutes	10 years	10+ years

Compliance

CE	Conformité Européenne
IC	Innovation, Science and Economic Development Canada
FCC	Federal Communications Commission (USA)

Aranet qualifies its T/RH sensor to work properly within ambient clean air. Qualification for use in harsh environment is the duty of the user of the sensor. Exposure to volatile organic compounds, acids or bases, etching substances such as H₂O₂, NH₃, shall be avoided.

¹ 95 % of the sensors measure within these typical limits in equilibrium state at time of sale. For evaluation of the total measurement error hysteresis and long-term drift has to be taken into account.

² Time constant is determined at 1 m/s airflow.

³ Due to regulatory requirements 1 minute data transmission interval is not available in Russia.

⁴ Weight with alkaline AA Fujitsu LR6G07 Premium battery.

⁵ AA Fujitsu LR6G07 Premium battery used for tests and calculations.

⁶ AA Energizer L91 Ultimate Lithium battery used for tests and calculations.

⁷ Battery lifetime data has been obtained by mathematical extrapolation and is provided for descriptive purposes only and is not intended to make or imply any guarantee or warranty.