

Ha-Vis EtherRail 4xAWG22/7 bl CAT5 50m



	Part number	09 45 600 1410
	Specification	Ha-Vis EtherRail 4xAWG22/7 bl CAT5 50m
	HARTING eCatalogue	https://b2b.harting.com/09456001410

Image is for illustration purposes only. Please refer to product description.

Identification

Category	System cabling
Element	Bulk cables
Specification	Not assembled
Type of cable	Copper cable (round)
Description of the cable	for railway applications
Version	
Cable length	50 m
Number of cores	4
Core structure	4x AWG 22/7
Technical characteristics	
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 +85 °C unmoved -25 +70 °C moved
Cable diameter	6.4 6.8 mm
Minimum bending radius	6x Cable diameter
Test voltage U _{r.m.s.}	1 kV Wire / wire / shielding
Coupling attenuation @ 20 °C / 100 MHz	8 mΩ/m
Conductor resistance @ 20 °C	≤54.4 Ω/km
Insulation resistance @ 20 °C	≥5,000 MΩ x km
Signal run time @ 20 °C	≤4.4 ns/m

Page 1 / 2 | Creation date 2021-07-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com



Technical characteristics

Impedance @ 100 MHz	100 Ω ±5 %			
Material properties				
Material (cable)	Polyolefin copolymer electron beam crosslinked Comp 752			
Colour (cable)	Blue			
RoHS	compliant			
ELV status	compliant			
China RoHS	e			
REACH Annex XVII substances	No			
REACH ANNEX XIV substances	No			
REACH SVHC substances	No			

Specifications and approvals

Specifications	EN 45545-2 (HL 1-3) fire protection in railway vehicles
	EN 50264-1 fire protection in railway vehicles
	EN 50306-1 fire protection in railway vehicles
	NFPA 130 fire protection in railway vehicles
	UN/ECE-R 118 fire protection for rolling stock
	EN 50306-4 Resistance to ozone
	EN 60811-504 High low temperature resistance
	EN 60811-404 High oil resistance
	EN 60811-404 High fuel resistance
	EN 60811-404 Alkali resistance
	EN 60811-404 Acid resistance
	DIN 51900 Low fire load

Commercial data

Packaging size	1
Net weight	3,365 g
Net weight	61 g/m
Country of origin	Switzerland
European customs tariff number	85444991
eCl@ss	27061801 Data and communication cable (copper)

Page 2 / 2 | Creation date 2021-07-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com