





Description: CY3250-286XXQFN POD

56 pin SSOP OCD with Hirose cable connector (P/N: DF12-5.0-20DP-0.5V-81) with retension mechanism included. Compatible with: SF-QFN48A-L-02B, QFN foot, 48 pin, 0.5mm pitch, 5mm body

XT-PSoC-15-20H-10-01

UGA Male pin shroud

	Page:_1_of 2			
EA-8C286XX-Q48-01 Drawing	Status: Released	Scale: <u>~3:1</u>		Rev: A
© 2009 IRONWOOD ELECTRONICS, INC. Tele: (800) 404-0204 www.ironwoodelectronics.com	Drawing: M. Tully		Date: 6/3/09	
	File: EA-8C286XX-Q48-01 Dwg		Modified:	

<u>Tolerances:</u> diameters ±0.03mm [±0.001"], PCB perimeters ±0.13mm [±0.005"], PCB thicknesses ±0.18mm [±0.007"], pitches (from true position) ±0.08mm [±0.003"], all other tolerances ±0.13mm [±0.005"] unless stated otherwise. Materials and specifications are subject to change without notice.



Side view: CY3250-286XXQFN Pod on QFN48 foot

Tolerances: diameters ±0.03mm [±0.001"], PCB perimeters ±0.13mm [±0.005"], PCB thicknesses ±0.18mm [±0.007"], pitches (from true position) ±0.08mm [±0.003"], all other tolerances ±0.13mm [±0.005"] unless stated otherwise. Materials and specifications are subject to change without notice.

				Page: 2_of 2
EA-8C286XX-Q48-01 Drawing	Status: Released	Scale: <u>~4:1</u>		Rev: A
© 2009 IRONWOOD ELECTRONICS, INC. Tele: (800) 404-0204 www.ironwoodelectronics.com	Drawing: M. Tully		Date: 6/3/09	
	File: EA-8C286XX-Q48-01 Dwg		Modified:	