



Data Sheet

RISH Clamp 1000/300A

3 ¾ Digits digital Clamp meter



Measure



Control



Record



Analyze

Application

RISH Clamp 1000A/300A measures important electrical parameters like AC Current, AC Voltage, DC Voltage. It also features Capacitance, Ohm & Continuity, frequency, Dutycycle and temperature measurement.

Product Features

Unique Design

Rish clamp 1000A / 300Ais a highly innovative design for features those increases **safety** and **comfort** of user.

- Rotating clamp jaws facilitate the measurement at physically awkward positions, vertical bus bars, conductors placed at positions difficult to access.
- Clamp jaws can be opened or closed with the trigger placed at bottom side away from the jaws. This allows the user to place his/her hand at safer distance from live conductor. This greatly reduces exposure of human beings to electrical shocks
- Location and design of trigger eliminates fatigues caused by single finger operation. It allows spreading the force required to open the jaws over more than one finger to ensure comfortable operation.
- Comfortable operation of push buttons and function selector switch, in adverse field conditions.

Large Jaw Opening

Rish Clamp 1000A: Jaw opening of 51mm for standard wire diameter of 50mm

Rish Clamp 300A : Jaw opening of 41mm for standard wire diameter of 40mm

Narrow Body

Narrow housing for firm grip and easy to carry.

High Accuracy for low current measurement

The clamp meter can measure accurately at not only the High currents but also Low current ranges.

User selectable Backlit : (Optional)

It is possible to conduct measurement using the clamp meter during night time in darkness with the help of Backlit. The back lit can be switched ON or OFF by pressing a single key.

Temperature measurement

Temperatures from -200 to 800 °C using Pt 100 and Pt 1000 sensors.

AUTO POWER OFF

In order to save the power of the Batteries, the clamp meter will automatically shut OFF if it detects no activity for 10 minutes.

Analog Scale

Analog scale that updates at the rate 20 times/sec to observe fluctuations in input.

CONTINOUS ON MODE

In this mode, AUTO POWER OFF is disabled.

DATA Hold Function

By pressing DATA HOLD button, reading on the display can be latched for Hands free operation.

MIN,MAX Function

By pressing MIN/MAX button, the clamp meter will start recording latest Minimum and Maximum readings

NULLZERO Correction for Resistance

For Low ohm measurement, the lead resistance can be compensated by pressing the shift key (Yellow Key)

NULLZERO Correction for Capacitance

Null zero connection for capacitance. For nF range, stray capacitance can be compensated by shift key (Yellow Key)

AUTO and MANUAL ranging modes

In AUTO ranging mode the instrument automatically selects the range with best resolution depending on the applied input.

In MANUAL ranging mode range is user selectable using MAN key.

Diode Measurement

For testing diodes and transistors, diode measurement function is available.

Protection from dust and water

IP20 for terminals as per IEC60529

Applicable International Safety standards

600 V CAT IV/1000V CAT III as per International Safety standard IEC 61010-1-2001

Double molded Cover for soft touch and firm grip of the Instrument

| Measuring function | Measuring range | Resolution | Input impedance | Intrinsic error of digital display ± (...% of rdg + ...digit) at reference condition | Over load capacity ¹⁾ | | |
|--------------------|------------------------|--------------------|----------------------|---|---|--|--------------|
| | | | | | Over load value | Overload duration | |
| V dc | 30.00 mV | 10 µV | >10 GΩ // <40pF | 0.5 + 3 ²⁾ | 1000 V DC AC eff / rms Sine wave | Continuously | |
| | 300.0 mV | 100 µV | >10 GΩ // <40pF | 0.5 + 3 | | | |
| | 3.000 V | 1 mV | 11 MΩ // <40pF | 0.25 + 1 | | | |
| | 30.00 V | 10 mV | 10 MΩ // <40pF | 0.25 + 1 | | | |
| | 300.0 V | 100 mV | 10 MΩ // <40pF | 0.25 + 1 | | | |
| | 1000 V | 1 V | 10 MΩ // <40pF | 0.35 + 1 | | | |
| V ~ | 3.000 V | 1 mV | 11 MΩ // <40pF | 0.75 + 2 (10....300 Digit) | | | |
| | 30.00 V | 10 mV | 10 MΩ // <40pF | 0.75 + 1 | | | |
| | 300.0 V | 100 mV | 10 MΩ // <40pF | > 300 Digit | | | |
| | 1000 V | 1V | 10 MΩ // <40pF | | | | |
| Ω | No load voltage | | | | | | |
| | 30.00 Ω | 10 mΩ | Max. 3.2 V | 0.5 + 3 ²⁾ | 1000 V DC AC eff / rms Sine wave | 10 min | |
| | 300.0 Ω | 100 mΩ | Max. 3.2 V | 0.5 + 3 | | | |
| | 3.000 KΩ | 1Ω | Max.1.25 V | 0.4 + 1 | | | |
| | 30.00 KΩ | 10 Ω | Max. 1.25 V | 0.4 + 1 | | | |
| | 300.0 KΩ | 100 Ω | Max. 1.25 V | 0.4 + 1 | | | |
| | 3.000 MΩ | 1 KΩ | Max. 1.25 V | 0.6 + 1 | | | |
| | 30.00 MΩ | 10 KΩ | Max. 1.25 V | 2.0 + 1 | | | |
| → | 2.000 V | 1 mV | Max. 3.2 V | 0.25 + 1 | | | |
| A ~ | 300.0 A | 0.01 A | ----- | 1.5 % of range + 5 Digits | 1100* A / 360A | Continuously | |
| | 1000A* | 0.1 A | ----- | 1.5 % of range + 5 Digits | | | |
| Measuring function | Measuring range | Resolution | Discharge resistance | U0 max. | Intrinsic error of digital display ± (...% of rdg + ...digit) at reference condition | Over load capacity ¹⁾ | |
| | | | | | | Over load value | |
| F | 30.00 nF | 10 pF | 250 KΩ | 2.5 V | 1.0 + 3 ²⁾ | 1000 V DC AC eff / rms Sine | 10 min |
| | 300.0 nF | 100 pF | 250 KΩ | 2.5 V | 1.0 + 3 | | |
| | 3.000 µF | 1 nF | 25 KΩ | 2.5 V | 1.0 + 3 | | |
| | 30.00 µF | 10 nF | 25 KΩ | 2.5 V | 3.0 + 3 | | |
| Hz | | | f min V dc | f min V ~ | 0.5 + 1 ³⁾ | ≤ 3 kHz 1000 v 30 kHz; 300 V 100 kHz 30 V | Continuously |
| | 300.0 Hz | 0.1 Hz | 1 Hz | 45 Hz | | | |
| | 3.000 KHz | 1 Hz | 1 Hz | 45 Hz | | | |
| | 30.00 KHz | 10 Hz | 10 Hz | 45 Hz | | | |
| Hz | 100.0 KHz | 100 Hz | 100 Hz | 100 Hz | | | |
| % | 2.0....98.0% | 0.1 % | 2 Hz | -- | 2 Hz... 1kHz ± 5 Digit ⁴⁾ 1 kHz ... 10 kHz; ± 5 Digit / kHz ⁴⁾ | 1000 V DC AC eff / rms Sine | 10 min |
| °C | Pt 100 | -200.0...+200.0 °C | 0.1 °C | -- | 2 Kelvin + 5 Digit ⁵⁾ | | |
| | | +200.0...+850.0 °C | 0.1 °C | | 1.0 + 5 ⁵⁾ | | |
| | Pt 1000 | -100.0...+200.0 °C | 0.1 °C | -- | 2 Kelvin + 2 Digit ⁵⁾ | | |
| | | +200.0...+850.0 °C | 0.1 °C | | 1.0 + 2 ⁵⁾ | | |

1) At 0° +40 °C

2) With zero adjustment, without zero adjustment + 35 digits

3) Range:

3 V ac/dc: Ue = 1.5 V eff/rms ... 100 V eff/rms

30 V ac/dc: Ue = 15 V eff/rms ... 300 V eff/rms

300 V ac/dc: Ue = 150 V eff/rms ... 1000 V eff/rms

4) On the range 3 V dc, square – wave signal positive on one side 5 ... 15 V,

f = const., not 163.84 Hz or integral multiple.

5) Without sensor

*applicable for 1000A

Reference conditions for Accuracy

Reference temperature

23°C ± 2K

Relative Humidity

45%...55% RH

Waveform of measured quantity

Sinusoidal

Input frequency

50 or 60 Hz ±2%

Battery Voltage

8 V ± 0.1 V

Response time

| Influence Quantity | Range of Influence | Measuring Ranges | Attenuation |
|----------------------------------|--|------------------|-------------|
| Common Mode interference voltage | Noise quantity max. 1000 V | V dc | > 120 dB |
| | Noise quantity max. 1000 V ~ 50 Hz, 60 Hz sinusoidal | 3V~ 300 V~ 30 V~ | > 70 dB |
| | | 1000 V~ | > 60 dB |
| Normal Mode interference voltage | Noise quantity V ~ Value of the measuring range at a time Max. 1000V~, 50Hz, 60Hz sinusoidal | V dc | > 50dB |
| | Noise quantity max. 1000 V- | V~ | >110dB |

Environmental

| | | | |
|-----------------------|---|-----------------------|--|
| Operating temperature | -10 to +55°C | Number of digits | 3 ¾ digits. |
| Storage temperature | -20 to +70°C | Maximum count | 3100 counts. |
| Relative humidity | 0... 90% non condensing | Over range indication | "OL" is displayed. |
| Terminal Protection | IP50 for Housing and IP20 for terminals | Polarity indication | "—" sign is displayed for DC functions, if positive pole is at " <u>—</u> ". |

Battery

| | |
|-----------------|---|
| Battery Voltage | 9 V DC |
| Battery type | Manganese Dioxide Cell as per IEC6F22 , alkaline manganese cell as per IEC 6LR 61 |
| Battery Life | Minimum 220 hours on Vdc, Adc, 80 hours on Vac, Aac. |

Display

Influence Quantities and Variations

| Influence Quantity | Range of Influence | Measured Quantity/ Measuring Range | Variation ¹⁾ ± (....% of rdg. +digits) |
|------------------------------------|---|------------------------------------|---|
| Temperature | 0 °C +21 °C and +25 °C...+40°C | 30/300 mV dc | 1.0 + 3 |
| | | 3...300 V dc | 0.15 + 1 |
| | | 1000 V dc | 0.2 + 1 |
| | | V ~ | 0.4 + 1 |
| | | 30 Ω ²⁾ | 0.15 + 2 |
| | | 300 Ω | 0.25 + 2 |
| | | 3 KΩ – 3 MΩ | 0.15 + 1 |
| | | 30 MΩ | 1.0 + 1 |
| | | 30 nF ²⁾ – 3 µF | 0.5 + 2 |
| | | 30 µF | 2.0 + 2 |
| | | Hz | 0.5 + 1 |
| | | % | ± 5 digits |
| | | -200...+200 °C | 0.5 K + 2 |
| | | +200...+850°C | 0.5 + 2 |
| | | A ~ | 0.75% of range + 1 |
| Frequency of the measured quantity | 15 Hz...<30 Hz | 3...300 V ~ | -- |
| | 30 Hz...<45 Hz | | -- |
| | > 65 Hz...400 Hz | | 2.0 + 3 |
| | >400 Hz...1 KHz | | 2.0 + 3 |
| | >1 KHz...20 KHz | | -- |
| | 15 Hz...<30 Hz | 1000 V ~ | -- |
| | 30Hz ...<45 Hz | | -- |
| | >65 Hz ... 1 KHz | | 3.0 + 3 |
| | 15 Hz...<30 Hz | A ~ | -- |
| | 30Hz ...<45 Hz | | -- |
| | >66 Hz... 1 kHz | | 2.0% of range + 1 |

| Influence Quantity | Range of Influence | | Measured Quantity/ Measuring Range | Variation ¹⁾ ± (....% of rdg. +digits) |
|--|---|--------|---------------------------------------|---|
| Wave form of the measured quantity ³⁾ | Crest factor CF | 1....3 | V ~ ⁴⁾ A ~ ⁴⁾ | |
| | | 1....5 | | |
| Battery Voltage |  ⁵⁾ ... < 7.9 V ... > 8.1 V ... 10.0 V | | V DC | 2 Digit |
| | | | V~ | 4 Digit |
| | | | A~ | 6 Digit |
| | | | 30Ω / 300 Ω/C | 4 Digit |
| | | | 3 kΩ – 30 MΩ | 3 Digit |
| | | | nF, μF | 1 Digit |
| | | | Hz | 1 Digit |
| | | | % | 1 Digit |
| Relative humidity | 75% | | V~, VDC | 1 x intrinsic error |
| | 3 Days | | A~ | |
| | Meter off | | Ω | |
| | | | F | |
| HOLD | - | | Hz | ± 1 digits |
| | - | | % | |
| MIN/MAX | - | | °C | ± 2 digits |
| | - | | V ac/dc , A ~ | |

1) With temperature: Error data apply per 10 K change in temperature.

With frequency: Error data apply to a display from 300 digits onwards.

2) With zero adjustment.

3) With unknown waveform (crest factor CF > 2), measure with manual range selection

4) With the exception of sinusoidal waveform.

5) After the “  ” symbol is displayed

Applicable Standards

EMC
Immunity

IEC 61326: Class B
IEC 61000-4-2 8 KV
atmosphere discharge, 4 KV
contact discharge
IEC 61000-4-3 : 3 V/m

Safety

IP for water & dust
Pollution degree
Installation category
High Voltage Test

IEC 61010-1-2001
IEC60529
2
IV
6.7 kV AC, 50Hz for 1 minute
between housing and input.
3.7 kV AC, 50Hz for 1 minute
between housing with jaws and
input.

Weight

0.6 Kg

Warranty

1 years




RISHABH

All specifications are subject to change without notice



Measure



Control



Record



Analyze

RISHABH INSTRUMENTS LIMITED

Domestic (India): +91 253 2202028/99 | marketing@rishabh.co.in

International: +91 253 2202004/06/08/99 | global@rishabh.co.in

www.rishabh.co.in