

Housing - HC-STA-D25-SLWSC-2SSP16-EL-AL - 1424398

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Box mounting bases D25, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PC, cable outlets: 2, lateral, height: 57 mm, cable gland: none, support sleeve: no, 2x Pg16, protective cover: yes, Standard



Key Commercial Data

| Packing unit | 1 pc |
|--------------|-----------------|
| GTIN | 4 055626 371382 |
| GTIN | 4055626371382 |

Technical data

Dimensions

| Height | 57 mm |
|--------|-------|
| Width | 51 mm |
| Length | 80 mm |

Ambient conditions

| Degree of protection (IP) | IP66 (with locked protective cover) |
|---------------------------------|-------------------------------------|
| | IP67 (when plugged in) |
| Ambient temperature (operation) | -40 °C 125 °C |

General

| Size | D25 |
|------------------------------|---------------------------|
| Housing type | Box mounting bases |
| Color | gray aluminum |
| Locking type | with single locking latch |
| No. of cable outlets | 2 |
| Cable outlet | lateral |
| Screw connection | none |
| Type of the screw connection | 2x Pg16 |
| Protective cover | yes |

09/22/2019 Page 1 / 3



Housing - HC-STA-D25-SLWSC-2SSP16-EL-AL - 1424398

Technical data

General

| Housing material | Die-cast aluminum, salt water resistant |
|----------------------------------|---|
| Housing surface material | uncoated |
| Material lock | РА |
| Material, protective cover | PC |
| Assembly instructions | One opening is sealed with a plastic filler plug and can be opened using a screwdriver. |
| Environmental Product Compliance | |

| China RoHS | Environmentally Friendly Use Period = 50 |
|------------|--|
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Drawings





Dimensional drawing

Approvals

Approvals

Approvals

EAC / DNV GL

Ex Approvals

Approval details



Housing - HC-STA-D25-SLWSC-2SSP16-EL-AL - 1424398

Approvals



PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com