Product data sheet Characteristics

NSYCU600UL

ClimaSys standard cooling unit side of enclosure - 640W at 230 V





Overview

Lead time	Usually Ships within 4 Weeks	
-----------	------------------------------	--

Main

IVIAIII		
Range	ClimaSys	
Product name	CU	
Product or Component Type	Cooling unit	
Mounting type	Side	
Type of Installation	Indoor	
Product destination	For enclosure	
Mounting Mode	By screws	
Input voltage	230 V 50/60 Hz	
Phase	1 phase	
Cooling power	2180 Btu/H 50/60 Hz L35-L35 1600 Btu/h 50/60 Hz L35-L50	

Complementary

23.86 in (606 mm)
12.44 in (316 mm)
8.35 in (212 mm)
2.1 A
8.1 A
400 W 50/60 Hz, L35-L35 470 W 50/60 Hz, L35-L50
1.6
Electronic controller
68122 °F (2050 °C)
Maximum 122 °F (50 °C) Inside the enclosure 68115 °F (2046 °C) Outside the enclosure 68122 °F (2050 °C)
65 dB
362.59 psi (25 bar)
Internal circuit 87178.34 Gal/hr(US) (330 m3/h) 50/60 Hz External circuit 150580.77 Gal/hr(US) (570 m3/h) 50/60 Hz
46.30 lb(US) (21 kg)
R134a 0.51 lb(US) (0.23 kg))
Optional external circuit filter
Thermal protection T 6 A Short-circuit protection (magnetic)

1

Material	Steel
Color	Gray RAL 7035)

Environment

Product Certifications	UL
Standards	DIN 3168
IP degree of protection	IP55 IEC 60529 on the internal circuit) IP34 IEC 60529 on the external circuit)

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480653551
Nbr. of units in pkg.	1
Package weight(Lbs)	46.30 lb(US) (21.0 kg)
Returnability	Yes
Country of origin	ES

Packing Units

PCE
8.35 in (21.2 cm)
12.44 in (31.6 cm)
23.86 in (60.6 cm)
P12
6
333.34 lb(US) (151.2 kg)
33.86 in (86.0 cm)
31.50 in (80.0 cm)
47.24 in (120.0 cm)

Offer Sustainability

Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.