NSYS3DM6615T

Spacial S3DM H600xW600xD150.IP66 IK10 RAL7035. top and bottom.





Main

Range	Spacial
Product name	Spacial S3DM
Application	Modular distribution application
Category	Compact enclosure
Enclosure nominal height	23.62 in (600 mm)
Enclosure nominal width	23.62 in (600 mm)
Enclosure nominal depth	5.91 in (150 mm)
Door type	Glass
Mounting plate description	Without mounting plate
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Product destination	For installation of modular chassis DLM
Device composition	2 cable gland plate top and bottom 1 body 1 door 1 lock

Complementary

Body type	Single piece body	
	Gutter-shaped front rail double sheet thickness	
Number of doors	Front face 1	
Door opening side	Reversible 120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges	
	Cable gland plate by screws	
Material	Body steel	
	Door steel and security glass	
Surface finish	Epoxy-polyester powder	
Color	Gray RAL 7035)	
Standards	IEC 62208	
Product Certifications	GL	
	CUL	
	UL	
	LR	
	DNV	
	BV	

Environment

IK degree of protection	IK08 IEC 62262
IP degree of protection	IP66 IEC 60529

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480158537
Nbr. of units in pkg.	1
Package weight(Lbs)	42.99 lb(US) (19.5 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	24.02 in (61.0 cm)	
Package 1 width	24.02 in (61.0 cm)	
Package 1 Length	11.81 in (30.0 cm)	

Offer Sustainability

Green Premium product
REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
₫Yes
☐ China RoHS Declaration
Product Environmental Profile

Contractual warranty

• • • • • • • • • • • • • • • • • • • •	
Warranty	18 months