CATALOG # 1EJH1 SAFETY ORGANIZATIONS RELIABILITY SPECIFICATIONS: ECN # APPRVD. DATE 05MAY03 STORAGE TEMPERATURE: -40°C TO +85°C 0631-0174-03 THIS FILTER HAS BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED HUMIDITY: 21 DAYS @ 40°C 95% RH. BY THE LISTED AGENCY. THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED CURRENT OVERLOAD TEST: 6 TIMES Ir FOR IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS 8 ZECONDS HAVE BEEN MET: TEST SPECIFICATIONS: UL RECOGNIZED: UL 1283 CSA CERTIFIED: CSA 22.2, # 8 INDUCTANCE: 10.0 mH NOMINAL CAPACITANCE: (MEASURED @ 1KHz, 0.250VAC MAX., 25°C±1°C) VDE APPROVED: EN 133 200 LINE TO GROUND: NONE LF OPERATING SPECIFICATIONS LINE TO LINE: 0.10 µF±20% DISCHARGE RESISTOR: 1.5 Ms LINE CURRENT/VOLTAGE: 1 AMP, 120/250 VAC, L/G AND L/L I.R 1 AMP/40°C, 250 VAC NO DISCHARGE RESISTOR: 6000M₁ (MIN.) @ 100VDC, 20°C AND 50% RH LINE FREQUENCY: 50-60Hz RECOMMENDED RECEIVING INSPECTION HIPOT: MAXIMUM LEAKAGE CURRENT, EACH LINE TO GROUND: 2µА @120V 60Hz 1500VAC OR 2250VDC FOR 1 MINUTE LINE TO GROUND: @250V 50Hz 5µА LINE TO LINE: 1450VDC FOR 1 MINUTE OPERATING AMBIENT TEMP. RANGE: -10°C TO +40°C @ RATED CURRENT, Ir. FILTER APPROVAL: IN AN AMBIENT, $T_{\rm O}$, HIGHER THAN 40°C, THE MAXIMUM OPERATING THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR CURRENT, In, IS AS FOLLOWS: $I_0 = I_r$ YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT. - 1.575±.015 -2.15 MAX. -0.250 TERMINALS WITH Ø 0.069 HOLE (2X) 0 0.96 M0.81 MAX. MAX CAN FLANGE EXTENDS BEYOND Ø 0.132±.01 WITH THE PERIMETER OF 2.038 MAX. Ø 0.260 REF X 90° CONNECTOR AS SHOWN COUNTERSUNK HOLE FOR 0.250 TERMINAL WITH #4 FLAT HEAD SCREW (2X) 0.069 X 0.155 SLOT 1.13 MAX. \emptyset 0.140 \emptyset 0.140 R 0.12 (4X) -R = 0.234 (4X) -(2X) (2X) 0.900 0.820 - 1.200 -- 1.200 -- 1.575 -- 1,575 -* RESISTOR LOCATION OPTIONAL PANEL CUTOUT (FRONT MOUNT) PANEL CUTOUT (BACK MOUNT) TOLERANCE ±.005 TOLERANCE ±.005 50 (MINIMUM) INSERTION $\Gamma \square ZZ$ THIRD ANGLE 50_{Ω} TUCO /Electronics #20017COM PROJECTION 844 E. ROCKLAND RD. LIBERTYVILLE IL 60048 FREQUENCY . 15 | . 50 5 01 . 05 . 10 10 30 UNLESS OTHERWISE SPECIFIED. MHz TOLERANCE TO BE ±.025 POWER LINE FILTER CDMMDNMATERIAL & FINISH: AS SUPPLIED 41 13 26 33 36 41 31 26 18 | CAD FILE: | G:\CD\1EJH102 | TYCE: 0-1609008-1 | SCALE: | NTS | DATE: | 10-17-01 | CATALOG NO. dΒ This document is proprietary to CORCOM INC. REV. and is not to be reproduced nor used for . 10-17-01 DIFF 5 8 19 27 45 36 32 manufacturing purposes except on CORCOM'S 2 ORIG: DRW. BY: 1EJH1 dB prior written consent. PJ0