SEIZAIKEN SILVER OXIDE BATTERY


SR920W 370

42 mAh Mercury Free

1. Specifications


2. Dimensions

Model		SR920W
IVIOUEI		31132000
Nominal Voltage		1.55V
Nominal Capacity		42mAh [cov:1.20V]
Standard Discharge Current		80μΑ
Operating Temperature Range		−10°C~+60°C
Weight		0.60g
Dimensions	Diameter	9.50mm
	Height	2.05mm




3. Characteristics

Discharge Characteristics




Measurement conditions: Temp: 23 deg C Load: $15k\Omega$

◆ Shelf Life



Measurement conditions:Temp:23 deg C Storage conditions: 60 deg C Dry Load:15k Ω


◆ Low Temperature Characteristics



Measurement conditions:

Temp:-10 deg C Load:2kΩ 7.8msec pulse

◆ Anti-leakage Performance



Storage conditions:

Temp:45 deg C Humidity:93% R.H.

Seiko Instruments Inc. Micro Energy Division 8, Nakase 1-chome, Mihama-ku, Chiba-shi, Chiba 261-8507 Japan Tel:(+81) 43-211-1735 FAX: (+81)43-211-8034 www.sii-me.com



^{*}Data is for reference only and is not guaranteed.

^{**}Changes may be made at any time to the information here without prior notice.

Precautions for Your Safety

SEIZAIKEN

For using SII Silver Oxide batteries, please follow the following precautions.



- Do not heat, disassemble nor dispose of in fire
 Doing so damages the insulation materials and may cause fire,
 heat generation, leakage or bursting.
- Do not short.

If the (+) and (-) come into contact with metal materials, shortcircuit occurs. As a result, fire, heat generation, leakage or bursting may occur.

Keep batteries out of children's reach.
 It is dangerous that children swallow the battery.
 When you design mechanical hardware around the battery, please

fix the battery firmly in order to prevent children from removing it. When you store the batteries, please keep the batteries out of children's reach.

If a battery is swallowed, consult a physician immediately.

- If leaked liquid, alkaline, get in the eyes, do not rub them, wash them with clean water and consult a physician immediately.
- If leaked liquid, alkaline, stick to clothing, for protecting from irritation, wash them with clean water immediately.



- Do not reverse placement of (+) and (-)
- Do not solder directly to the battery
- Do not use new and used batteries together. Do not use different types of batteries together.
- Do not charge.
- Do not use nor leave the batteries in direct sunlight nor in high-temperature areas.
- Keep batteries away from direct sunlight, high temperature and humidity.
- Avoid letting battery contact water.

- Make sure to insert batteries without having (+) and (-) come in contact with metal parts of equipment.
- Read the equipment instruction manual and precautions carefully before using. Some usage or types of equipment do not suit the specifications or performance of these batteries.
- Remove batteries from the equipment, if finished using. Do not leave batteries connecting with equipment after using.
- In case of disposal, insulate between (+) and (-) of battery by an insulating material.