



Product: <u>1307A</u> ☑

Speaker Cable, 2 C #16 Str BC-OFHC, PVC Jkt, CM, DIR BUR, Flexible

Product Description

Speaker Cable, 2 Conductor 16 AWG (65 x 34) Oxygen-Free Bare Copper (High Conductivity), PE Insulation, PVC Jacket, CM, Direct Burial, Flexible

Technical Specifications

Product Overview

Suitable Applications:		Speaker C	Speaker Cable; Direct Burial; Indoor/Outdoor Home Theater; In-Wall Speaker; Outdoor Speaker				
Construction Details							
ductor	Number of Elemer	Cino	Ctus o dia s	Metavial			
Element			Stranding				
nductor(s)	2	16 AWG	65x34	BC - Bare Copper (Hig	h Conductivity)		
ulation Element	Material	Nom. Thic	kness No	om. Insulation Diameter	Color Code		
nductor(s)	PE - Polyethylene	0.013 in (0.	33 mm) 0.0	083 in (2.1 mm)	Black, Red		
Outer Jacket Material Nom. Thickness Nom. Diameter							
'C - Polyvir	nyl Chloride 0.022 in	(0.56 mm)	0.210 in (5.	33 mm)			
Overall Cable Diameter (Nominal): 0.210 in (5.33 mm)							
Mate - Polyvir	nyl Chloride 0.022 in	(0.56 mm)	0.210 in (5.				

Electrical Characteristics

Electricals

E	Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Velocity of Prop.	Max. Current
Co	nductor(s)	4.27 Ohm/1000ft	19.9 pF/ft (65.3 pF/m)	66%	18 Amps per conductor @ 30°C

Voltage

UL Voltage Rating 300 V (CM, CL3)

Mechanical Characteristics

Temperature UL Temperature

UL Temperature	Operating
75°C	-20°C To +75°C

Bend Radius

Stationary Min.	Installation Min.	
2.1 in (53 mm)	2.1 in (53 mm)	
Max. Pull Tension	n:	65 lbs (29 kg)
Bulk Cable Weigh	ht:	27 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor, Outdoor, Burial
Flammability / Reaction to Fire:	UL 1685 UL loading , IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, Article 800, CL3, CM
CEC / C(UL) Compliance:	CM
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6200UE

Product Notes

Notes:	Jacket has ROOM 1 2 3 4 5 6 7 8 9 0 ZONE A B C D printed on it.
--------	---

History

Update and Revision:	Revision Number: 0.491 Revision Date: 04-14-2023

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
1307A 010U500	Black	UnReel	500 ft	612825111283
1307A 0101000	Black	Reel	1,000 ft	612825111290
1307A 010Z1000	Black	ReelTuff Box	1,000 ft	612825435396
1307A 006U500	Blue, Light	UnReel	500 ft	612825111252
1307A 008U500	Gray	UnReel	500 ft	612825111269
1307A 0081000	Gray	Reel	1,000 ft	612825111276
1307A N3UU500	Green, Mil	UnReel	500 ft	612825111245
1307A 1SLU500	White 1SL	UnReel	500 ft	612825111306
1307A 1SL1000	White 1SL	Reel	1,000 ft	612825111313

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.