

4223F

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 4223F Premium Polyurethane Conformal Coating

Other Means of Identification: 4223F Vernis de Tropicalisation—Polyuréthane Premium

Related Part # 4223F-55ML, 4223F-1L, 4223F-4L, 4223F-20L

Recommended Use and Restriction on Use

Use: Conformal coating

Uses Advised Against: Not available

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

 +1-800-340-0772

FAX +1-800-340-0773

E-MAIL support@mgchemicals.com

WEB www.mgchemicals.com

 +1-905-331-1396

FAX +1-905-331-2682

E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

4223F
Section 2: Hazards Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Skin Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation
Hazardous to the Aquatic Environment Chronic	2	<i>none</i>	Environment

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
	H315: Cause skin irritation H336: May cause dizziness or drowsiness
	H411: Toxic to aquatic life with long lasting effects

Section continued on the next page

4223F

Continued...

Prevention	Precautionary Statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion proof equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P261	Avoid breathing mist, vapors, or spray.
P271	Use only outdoors or in well-ventilated area.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves, protective clothing, and eye protection.
P273	Avoid release to the environment.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P362 + P352	IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of water.
P332 + P313	If skin irritation occurs: Get medical advice or attention.
P363	Wash contaminated clothing before reuse.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTRE or doctor if you feel unwell.
P391	Collect spillage.
Storage	Precautionary Statements
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, and international regulations.

Section continued on the next page

4223F

Hazards Not Otherwise Specified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
64742-47-8	distillates, petroleum, hydrotreated light	45%
78-93-3	butan-2-one	9%

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF ON SKIN (or hair)	P303 + P361 + P352, P332 + P313, P363
Immediate Symptoms	<i>irritation, redness, dry skin</i>
Response	Take off immediately all contaminated clothing. Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Wash contaminated clothing before reuse.
IF INHALED	P304 + P340, P312
Immediate Symptoms	<i>dizziness, drowsiness, headaches, nausea, vomiting</i>
Response	Remove person to fresh air and keep comfortable for breathing. If feeling unwell: Call a doctor.
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>Low toxicity—mild irritation, redness</i>
Response	Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
IF SWALLOWED	P301 + P330 + P331
Immediate Symptoms	<i>Low toxicity—nausea, dizziness, drowsiness, headaches, vomiting, diarrhea</i>
Response	Rinse mouth. Do NOT induce vomiting.

4223F**Section 5: Fire Fighting Measures**

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool the containers.
Specific Hazards	Vapors are heavier than air, and may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.
Combustion Products	Produces CO and CO ₂
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	Use personal protection recommended in Section 8.
Precautions for Response	Remove or keep away all sources of ignition or extreme heat.
Environmental Precautions	Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Sprinkle inert absorbent compound (sand, diatomite, acid binders, universal binders) onto spill, then sweep into a corrosion resistant (plastic) waste container. Wash spill area with soap and water to remove the last traces of residue. RECOMMENDATION: Use a grounded stainless steel or carbon steel container.
Disposal Methods	Dispose of spill waste according to Section 13.

4223F
Section 7: Handling and Storage
Prevention

Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. No smoking.

Ground and bond container and receiving equipment. Take action to prevent static discharges. Use explosion proof equipment. Keep container tightly closed.

Avoid breathing mist, vapors, and spray. Use only outdoors or in well-ventilated area.

Avoid release to the environment.

Handling

Wear protective gloves, protective clothing, and eye protection.

Wash hands thoroughly after handling.

Collect spillage.

Storage

Store in a well-ventilated place. Keep cool. Store locked up.

Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
distillates, petroleum, hydrotreated light	ACGIH	200 mg/m ³	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada AB	200 mg/m ³	Not established
	Canada BC	200 mg/m ³ (Skin)	Not established
	Canada ON	200 mg/m ³	Not established
	Canada QC	Not established	Not established
butan-2-one	ACGIH	200 ppm	300 ppm
	U.S.A. OSHA PEL	200 ppm	Not established
	Canada AB	200 ppm	300 ppm
	Canada BC	50 ppm	100 ppm
	Canada ON	200 ppm	300 ppm
	Canada QC	150 ppm	300 ppm

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS² database and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Skin—can be absorbed through the skin

Section continued on the next page

4223F**Engineering Controls**

Ventilation Keep airborne concentrations below occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.
RECOMMENDATION: Ensure that glasses have side shields for lateral protection.

Skin Protection For likely contacts, use of protective nitrile gloves or other chemically resistant gloves.
For incidental contacts, use disposable nitrile, neoprene, PVC gloves, or other chemically resistant gloves.

Respiratory Protection For over-exposures up to 10 x OEL of mist, vapors, or spray, wear respirator such as a half-mask respirator with organic vapor cartridges.
Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.
RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section continued on the next page

4223F
Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit ^{b)}	1.8%
Appearance	Clear	Upper Flammability Limit ^{b)}	11.5%
Odor	Mild petroleum	Vapor Pressure @20 °C	Not available
Odor Threshold	Not available	Vapor Density	>2.5 (Air =1)
pH	Not available	Relative Density @25 °C	0.88
Freezing/Melting Point	Not available	Solubility in Water	Partially soluble
Initial Boiling Point ^{a)}	80 °C [176 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	-9 °C [15.8 °F]	Auto-ignition Temperature	440 °C [824 °F]
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Highly Flammable	Viscosity @40 °C	>20.5 mm ² /s

a) Values based on butan-2-one component

b) Values calculated based on Raoult's Law and LeChatelier principal

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid flames, sparks, other ignition sources and incompatible substances.
Incompatibilities	Oxidizing agents, strong reducing agents, strong acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

4223F
Section 11: Toxicological Information
Summary of Effects and Symptoms by Routes of Exposure

Eyes	May cause eye redness or mild irritation.
Skin	Causes skin irritation, dry skin and redness.
Inhalation	Exposure may lead to dizziness, drowsiness, headaches, nausea, and vomiting. Severe overexposure may lead to loss of consciousness.
Ingestion	It may cause nausea, dizziness, drowsiness, headaches, vomiting, and diarrhea.
Chronic	Prolonged and repeated exposure may cause dermatitis, defatting of the skin and adverse central nervous systems effects.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
distillates (petroleum) hydrotreated light	8 000 mg/kg Rat	4 000 mg/kg Rabbit	17.38 mg/L 4 h Rat
2-butanone	2 737 mg/kg Rat	6 480 mg/kg Rabbit	23 500 mg/m ³ 8 h Rat

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDSs were also consulted.

Other Toxicological Effects

Skin corrosion/irritation	Causes skin irritation based on the contribution of the distillates (petroleum) hydrotreated light.
Serious eye damage/irritation	Based on available data, the classification criteria are not met. The contribution of butan-2-one does not trigger classification of the mixture.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.

Section continued on the next page

4223F

Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	May cause dizziness or drowsiness
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	The liquid content is not an aspiration hazard. It has a kinematic viscosity >20.5 mm ² /s.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Distillates, petroleum, hydrotreated light is a chronic category 2 environmental toxicant.

The butan-2-one has minimal LC50 96 h of 3 130 mg/L for Pimephales promelas (fathead minnow); EC50 48 h 520 mg/L Daphnia magna (water flea).

Acute Ecotoxicity

See chronic ecotoxicity.

Chronic Ecotoxicity

Category 2

Toxic to aquatic life with long lasting effects.

Avoid release to the environment. Collect spillage.

Biodegradability

Non biodegradable

Other Effects

Volatile Organic Compounds (VOC) = 55% [486 g/L]

Section 13: Disposal Considerations

Dispose of contents in accordance with all local, regional, national, and international regulations.

4223F

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Sizes 5 L and under

4223F-55ML, 4223F-1L, 4223F-4L

Limited Quantity



Sizes greater than 5 L

4223F-20L

UN number: UN1263

Shipping Name: PAINT

Class: 3

Packing Group: II

Marine Pollutant: Yes



Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 0.5 L and under

4223F-55ML

Limited Quantity

Max Net Qty/Pkg =

1 L



Sizes up to 5 L (passenger), 60 L (cargo)

4223F-1L, 4223F-4L, 4223F-20L

UN number: UN1263

Shipping Name: PAINT

Class: 3

Packing Group: II

Marine Pollutant: Yes



Section continued on the next page

4223F**Sea****Refer to IMDG regulations.**

Sizes 5 L and under

4223F-55ML, 4223F-1L, 4223F-4L

Limited Quantity

Sizes greater than 5 L

4223F-20L

UN number: UN1263**Shipping Name:** PAINT**Class:** 3**Packing Group:** II

Marine Pollutant: Yes



Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information**Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.


Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

Section continued on the next page

4223F**USA****Other Classifications****HMIS[®] RATING**

HEALTH:	* 2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA[®] 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains butan-2-one (CAS# 78-93-3), which can be subject to the CERCLA reporting requirements at a threshold of 5000 lb (2268 kg).

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65

(Chemicals known to cause cancer or reproductive toxicity, USA)

This product does not contain any substances known to be listed in California.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

4223F**Section 16: Other Information**

Prepared by the	Regulatory Affairs Department
Date of Review	05 March 2020
Supersedes	21 January 2019
Reason for Changes:	Update to the emergency phone number information.

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page

4223F

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.