# Product data sheet **Characteristics**

# NSYS3CM406025

HMI encl. Spacial S3CM H400xW600xD250 IP54, IK10, RAL7035. Rear door.





N/	a	in
111	а	

Main	
Range	Spacial
Product name	Spacial S3CM
Application	Human-machine dialogue application
Category	Control enclosure
Enclosure nominal height	15.75 in (400 mm)
Enclosure nominal width	23.62 in (600 mm)
Enclosure nominal depth	9.84 in (250 mm)
Installation accessory type	Suspension system
Product destination	Interface
Device composition	1 body 1 door with lock 2 rail 1 reinforcement plate 1 front trim frame 1 cable gland plate

#### Complementary

Complementary		
Body type	Single piece body	
Door type	Solid	
Number of doors	Rear 1	-
Door opening side	Reversible 120 °)	-
Lock type	3 mm double-bar lock	-
Mounting plate description	Without mounting plate	
Type of gland plate	Standard	
Accessibility for operation	Rear	
Removable parts	Door by hinges Trim frame by screws 2 rails by screws Cable gland plate by screws	
Material	Enclosure and front face steel Trim frame aluminium	
Surface finish	Epoxy-polyester powder	-
Color	Enclosure Gray RAL 7035) Front face Gray RAL 7040)	
Net Weight	36.82 lb(US) (16.7 kg)	

#### Environment

IP degree of protection	IP54 IEC 60529
IK degree of protection	IK10 IEC 62262

#### Ordering and shipping details

Category	80033-ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	3606480212918
Nbr. of units in pkg.	1
Package weight(Lbs)	36.82 lb(US) (16.7 kg)



Returnability	No
Country of origin	ES

#### **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	16.54 in (42.0 cm)	
Package 1 width	24.41 in (62.0 cm)	
Package 1 Length	10.63 in (27.0 cm)	

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	<b>₽</b> Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

## Contractual warranty

Warranty

18 months