

High-Speed HDMI Cable with Ethernet (M/M) - 4K, No Signal Booster Needed, Black, 40 ft.

MODEL NUMBER: P568-040-HD





High-speed 4K cable connects audio/video components to an HDTV or monitor in your home theater or digital signage application.

Features

4K HDMI Cable Connects Home Theater or Digital Signage Audio/Video ComponentsThis highspeed HDMI cable securely connects HDMI-enabled Chromebooks, MacBooks, tablets, PCs, Blu-ray players, game consoles, Roku/Apple TV boxes or satellite/cable TV receivers to HDTVs, HD monitors, projectors or home theater receivers. It allows you to extend your HDMI signal as far as 40 feet (12.2 meters) from the source without connecting a signal booster or having to use more expensive active optical cable (AOC) or Cat5/6 cable. It also supports Ethernet, so no separate cable is needed to connect devices online.

Enjoy the Clarity of 4K HDMI Video with Multi-Channel AudioThis Tripp Lite 4K HDMI cable provides a pure digital connection that supports Ultra HD video resolutions up to 4096 x 2160 (4K x 2K) at 30 Hz for crystal-clear picture and sound.

Invest in Quality Construction for Reliable PerformanceHigh-quality materials ensure outstanding performance throughout the 24 AWG cable's lifetime. Contacts and connectors are gold-plated to resist corrosion. Double shielding reduces line noise (EMI/RFI) that can disrupt signals traveling through the HDMI cord. When used with an Apple digital A/V adapter, the cable supports iPad2 video mirroring for playing games, watching videos or displaying presentations.

40 ft. Cable Lets You Design an Audio/Video Application to Your SpecificationsThis long HDMI cable allows you greater flexibility in placing your home theater or digital signage components. For instance, your Blu-ray player or media server may be concealed some distance from the connected display for security purposes.

Specifications

OVERVIEW	
UPC Code	037332252791

Highlights

- 40 ft. length allows great flexibility in placing home theater or digital signage devices
- Supports UHD resolutions up to 4096 x 2160 (@ 30 Hz) for crystal-clear 4K x 2K video
- Gold-plated connectors and contacts enable maximum conductivity and minimum data loss
- Foil/braid shielding protects against EMI/RFI line noise that can distort or destroy data
- Plug-and-play operation with no booster required for easy, immediate installation

Applications

- Watch 4K video from a Blu-ray player, game console, laptop or tablet on an Ultra HD television, monitor or projector
- Connect a Chromebook or MacBook to a conference table's A/V box to give a video presentation on a large screen
- Play online or PC video games that display optimal graphics
- Combine with an Apple digital A/V adapter to support iPad2 video mirroring
- Send 4K video content to digital signs or point-of-sale displays

Package Includes

P568-040-HD High-Speed HDMI Cable, M/M, Black, 40 ft.



Product TypePassiveTechnologyHDMIVIDEO4096 x 2160 @ 3Max Supported Video Resolution4096 x 2160 @ 3HDR SupportNo3D Video SupportedNoINPUTProduct Length (in.)480Product Length (ft.)40PHYSICALColorColorBlackMaterial of ConstructionPVCCable Jacket MaterialPVCCable Jacket RatingVW-1Cable Outer Diameter (OD)10.0Wire Gauge (AWG)24Cable Length (in.)480Shipping Dimensions (hwd / in.)13.80 x 11.00 xShipping Weight (kg)1.29ENVIRONMENTALOperating Temperature Range0 - 45 °C (32 - 1Storage Temperature Range-40 - 80 °C (-40Relative Humidity5 - 90 %, NON-OCONNECTIONSNoSide A - Connector 1HDMI (MALE)Side B - Connector 1HDMI (MALE)			
VIDEO Max Supported Video Resolution 4096 x 2160 @ 3 HDR Support No 3D Video Supported No INPUT Yourget and the second and t			
Max Supported Video Resolution4096 x 2160 @ :HDR SupportNo3D Video SupportedNoINPUTProduct Length (in.)480Product Length (ft.)40PHYSICAL40ColorBlackMaterial of ConstructionPVCCable Jacket MaterialPVCCable Jacket RatingVW-1Cable Quter Diameter (OD)10.0Wire Gauge (AWG)24Cable Length (ft.)480Shipping Dimensions (hwd / in.)13.80 x 11.00 xShipping Weight (kg)1.29ENVIRONMENTAL0 - 45 °C (32 - 1Operating Temperature Range-40 - 80 °C (-40Relative Humidity5 - 90 %, NON-OCCONNUNICATIONSNoSide A - Connector 1HDMI (MALE)			
HDR SupportNo3D Video SupportedNoINPUTProduct Length (in.)480Product Length (ft.)40PHYSICALColorBlackMaterial of ConstructionPVCCable Jacket MaterialPVCCable Jacket RatingVW-1Cable Outer Diameter (OD)10.0Wire Gauge (AWG)24Cable Length (ft.)400Cable Length (ft.)480Shipping Dimensions (hwd / in.)13.80 x 11.00 xShipping Weight (kg)1.29ENVIRONMENTALOperating Temperature Range-40 - 80 °C (-40Relative Humidity5 - 90 %, NON-OConsumer Electronics Control (CEC) SupportedNoSide A - Connector 1HDMI (MALE)			
3D Video Supported No INPUT Product Length (in.) 480 Product Length (ft.) 40 PHYSICAL Color Black Material of Construction PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 10.0 Wire Gauge (AWG) 24 Cable Length (ft.) 40 Cable Length (in.) 480 Shipping Dimensions (hwd / in.) 13.80 x 11.00 x Shipping Dimensions (hwd / in.) 13.80 x 11.00 x Shipping Dimensions (hwd / in.) 13.80 x 11.00 x Shipping Dimensions (hwd / in.) 13.80 x 11.00 x Shipping Dimensions (hwd / in.) 13.80 x 11.00 x Shipping Weight (kg) 1.29 ENVIRONMENTAL 0 - 45 °C (32 - 1 Storage Temperature Range -40 - 80 °C (-40 Relative Humidity 5 - 90 %, NON-O Consumer Electronics Control (CEC) No Side A - Connector 1 HDMI (MALE)	30 Hz		
INPUT Product Length (in.) 480 Product Length (ft.) 40 Physical 40 Color Black Material of Construction PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 10.0 Wire Gauge (AWG) 24 Cable Length (ft.) 480 Shipping Dimensions (hwd / in.) 13.80 x 11.00 x Shipping Weight (kg) 1.29 Operating Temperature Range 0-45 °C (32 - 1 Storage Temperature Range -40 - 80 °C (-40) Relative Humidity 5 - 90 %, NON-OC Consumer Electronics Control (CEC) No Side A - Connector 1 HDMI (MALE)			
Product Length (in.)480Product Length (ft.)40PHYSICALEnvironment of ConstructionBlackColorBlackPVCCable Jacket MaterialPVCCable Jacket RatingVW-1Cable Outer Diameter (OD)10.0Wire Gauge (AWG)24Cable Length (ft.)400Cable Length (ft.)13.80 × 11.00 ×Shipping Dimensions (hwd / in.)13.80 × 11.00 ×Shipping Weight (kg)1.29ENVIRONMENTAL-40 - 80 °C (-40Qperating Temperature Range-40 - 80 °C (-40Relative Humidity5 - 90 %, NON-ORConsumer Electronics Control (CEC) SupportedNoSide A - Connector 1HDMI (MALE)			
Product Length (ft.) 40 PHYSICAL Black Color Black Material of Construction PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 10.0 Wire Gauge (AWG) 24 Cable Length (ft.) 40 Cable Length (ft.) 480 Shipping Dimensions (hwd / in.) 13.80 x 11.00 x Shipping Weight (kg) 1.29 ENVIRONMENTAL 0 - 45 °C (32 - 1 Operating Temperature Range -40 - 80 °C (-40 Relative Humidity 5 - 90 %, NON-O Consumer Electronics Control (CEC) No Supported No Side A - Connector 1 HDMI (MALE)			
PHYSICAL Color Black Material of Construction PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 10.0 Wire Gauge (AWG) 24 Cable Length (ft.) 40 Cable Length (ft.) 480 Shipping Dimensions (hwd / in.) 13.80 x 11.00 x Shipping Weight (kg) 1.29 Operating Temperature Range 0 - 45 °C (32 - 1 Storage Temperature Range -40 - 80 °C (-40) Relative Humidity 5 - 90 %, NON-0 Consumer Electronics Control (CEC) No Side A - Connector 1 HDMI (MALE)			
ColorBlackMaterial of ConstructionPVCCable Jacket MaterialPVCCable Jacket RatingVW-1Cable Outer Diameter (OD)10.0Wire Gauge (AWG)24Cable Length (ft.)40Cable Length (in.)480Shipping Dimensions (hwd / in.)13.80 x 11.00 xShipping Weight (kg)1.29ENVIRONMENTALOperating Temperature Range0 - 45 °C (32 - 1Storage Temperature Range-40 - 80 °C (-40)Relative Humidity5 - 90 %, NON-0Consumer Electronics Control (CEC) SupportedNoSide A - Connector 1HDMI (MALE)			
Material of ConstructionPVCCable Jacket MaterialPVCCable Jacket RatingVW-1Cable Outer Diameter (OD)10.0Wire Gauge (AWG)24Cable Length (ft.)40Cable Length (in.)480Shipping Dimensions (hwd / in.)13.80 x 11.00 xShipping Weight (kg)1.29ENVIRONMENTALOperating Temperature Range0 - 45 °C (32 - 1Storage Temperature Range-40 - 80 °C (-40)Relative Humidity5 - 90 %, NON-0Consumer Electronics Control (CEC) SupportedNoSide A - Connector 1HDMI (MALE)	PHYSICAL		
Cable Jacket MaterialPVCCable Jacket RatingVW-1Cable Outer Diameter (OD)10.0Wire Gauge (AWG)24Cable Length (ft.)40Cable Length (in.)480Shipping Dimensions (hwd / in.)13.80 x 11.00 xShipping Weight (kg)1.29ENVIRONMENTALOperating Temperature Range0 - 45 °C (32 - 1Storage Temperature Range-40 - 80 °C (-40Relative Humidity5 - 90 %, NON-OCOMMUNICATIONSNoConsumer Electronics Control (CEC) SupportedNoSide A - Connector 1HDMI (MALE)			
Cable Jacket RatingVW-1Cable Outer Diameter (OD)10.0Wire Gauge (AWG)24Cable Length (ft.)40Cable Length (in.)480Shipping Dimensions (hwd / in.)13.80 x 11.00 xShipping Weight (kg)1.29ENVIRONMENTALOperating Temperature Range0-45 °C (32 - 1Storage Temperature Range-40 - 80 °C (-40)Relative Humidity5 - 90 %, NON-0Consumer Electronics Control (CEC) SupportedNoSide A - Connector 1HDMI (MALE)			
Cable Outer Diameter (OD)10.0Wire Gauge (AWG)24Cable Length (ft.)40Cable Length (in.)480Shipping Dimensions (hwd / in.)13.80 x 11.00 xShipping Weight (kg)1.29ENVIRONMENTALOperating Temperature Range0 - 45 °C (32 - 1Storage Temperature Range-40 - 80 °C (-40)Relative Humidity5 - 90 %, NON-0COMMUNICATIONSNoConsumer Electronics Control (CEC) SupportedNoSide A - Connector 1HDMI (MALE)			
Wire Gauge (AWG)24Cable Length (ft.)40Cable Length (in.)480Shipping Dimensions (hwd / in.)13.80 x 11.00 xShipping Weight (kg)1.29ENVIRONMENTALOperating Temperature Range0 - 45 °C (32 - 1Storage Temperature Range-40 - 80 °C (-40)Relative Humidity5 - 90 %, NON-0Consumer Electronics Control (CEC) SupportedNoCONNECTIONSSide A - Connector 1HDMI (MALE)			
Cable Length (ft.)40Cable Length (in.)480Shipping Dimensions (hwd / in.)13.80 x 11.00 xShipping Weight (kg)1.29ENVIRONMENTALOperating Temperature Range0 - 45 °C (32 - 1Storage Temperature Range-40 - 80 °C (-40)Relative Humidity5 - 90 %, NON-0COMMUNICATIONSConsumer Electronics Control (CEC) SupportedNoCONNECTIONSSide A - Connector 1HDMI (MALE)			
Cable Length (in.)480Shipping Dimensions (hwd / in.)13.80 x 11.00 xShipping Weight (kg)1.29ENVIRONMENTALOperating Temperature Range0 - 45 °C (32 - 1Storage Temperature Range-40 - 80 °C (-40)Relative Humidity5 - 90 %, NON-0COMMUNICATIONSConsumer Electronics Control (CEC) SupportedNoCONNECTIONSSide A - Connector 1HDMI (MALE)			
Shipping Dimensions (hwd / in.) 13.80 x 11.00 x Shipping Weight (kg) 1.29 ENVIRONMENTAL 0-45 °C (32 - 1) Operating Temperature Range -40 - 80 °C (-40) Relative Humidity 5 - 90 %, NON-0 COMMUNICATIONS No Consumer Electronics Control (CEC) Supported No Side A - Connector 1 HDMI (MALE)			
Shipping Weight (kg) 1.29 ENVIRONMENTAL			
ENVIRONMENTAL Operating Temperature Range 0 - 45 °C (32 - 1) Storage Temperature Range -40 - 80 °C (-40) Relative Humidity 5 - 90 %, NON-0 COMMUNICATIONS Consumer Electronics Control (CEC) Supported No Side A - Connector 1 HDMI (MALE)	0.50		
Operating Temperature Range 0 - 45 °C (32 - 1) Storage Temperature Range -40 - 80 °C (-40) Relative Humidity 5 - 90 %, NON-0 COMMUNICATIONS Consumer Electronics Control (CEC) Supported No Side A - Connector 1			
Storage Temperature Range -40 - 80 °C (-40 Relative Humidity 5 - 90 %, NON-0 COMMUNICATIONS Consumer Electronics Control (CEC) Supported No Supported Side A - Connector 1			
Relative Humidity 5 - 90 %, NON-0 COMMUNICATIONS Consumer Electronics Control (CEC) Supported No CONNECTIONS HDMI (MALE)	15 °F)		
COMMUNICATIONS Consumer Electronics Control (CEC) Supported No CONNECTIONS Side A - Connector 1 HDMI (MALE)	- 176 °F)		
Consumer Electronics Control (CEC) No CONNECTIONS Side A - Connector 1 HDMI (MALE) HDMI (MALE)	CONDENSING		
Supported NO CONNECTIONS HDMI (MALE)			
Side A - Connector 1 HDMI (MALE)			
	CONNECTIONS		
Side B - Connector 1 HDMI (MALE)			
Connector Plating Gold			
Contact Plating Gold			



FEATURES & SPECIFICATIONS		
HDCP Specification	1.4	
STANDARDS & COMPLIANCE		
Certifications	Tested to RoHS and REACH	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

https://www.tripplite.com/products/product-certification-agencies