8501KUDR12V53

Plug in relay, Type KU, blade, 0.5 HP at 240 VAC, 10A resistive at 120 VAC, 8 blade, DPDT, 2 NO, 2 NC, 24 VDC coil



Main Product range 8501K Product type Relay Relay Type General purpose Mounting type Socket Contact composition DPDT 24 V DC [Uc] control circuit voltage Pilot light No indicator

Con	lqr	lem	nen	tar	١
				,	J

Horsepower rating	1 Hp 277 V AC	_
	0.33 hp 120 V AC	
Breaking capacity	3 A 120 V AC inductive control circuit UL 508	
	1.5 A 240 V AC inductive control circuit UL 508	
	10 A 277 V AC resistive control circuit UL 508	
	10 A 30 V DC resistive control circuit UL 508	
Maximum switching voltage	300 V AC	
	30 V DC	
Contact material	Silver alloy (AgNi)	
Operating time	20 ms - pick-up	
	20 ms - drop-out	
Shape of pins	Spade	
For use with	8501NR82	

Environment

LIMIOIIIICII	
Ambient temperature range - operational	-40131 °F (-4055 °C)
Product certifications	UL Listed UL Recognized CSA CE
Height	2.25 in (57.15 mm)
Width	1.37 in (34.80 mm)
Depth	1.4 in (35.56 mm)

Ordering and shipping details

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.50 in (3.81 cm)	
Package 1 width	1.50 in (3.81 cm)	
Package 1 Length	2.80 in (7.112 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile