


## High temperature 40 A SCRs

Datasheet - production data



### Features

- High junction temperature :  $T_j = 150^\circ\text{C}$
- High noise immunity  $dV/dt = 500 \text{ V}/\mu\text{s}$  up to  $150^\circ\text{C}$
- Gate triggering current  $I_{GT} = 15 \text{ mA}$
- Off-sat voltage  $600 \text{ V}$   $V_{DRM}/V_{RRM}$
- High turn on current rise  $dl/dt = 100 \text{ A}/\mu\text{s}$
- ECOPACK®2 compliant component

### Applications

- Motorbike voltage regulator circuits
- Inrush current limiting circuit
- Motor control circuits and starters
- Solid state relays

### Description

Thanks to its junction temperature  $T_j$  up to  $150^\circ\text{C}$ , the device offers high thermal performances operation up to 40 A. Its D²PAK package allows modern SMD designs as well as compact back to back configuration.

Its trade-off noise immunity ( $dV/dt = 500 \text{ V}/\mu\text{s}$ ) versus its gate triggering current ( $I_{GT} = 15 \text{ mA}$ ) and its turn-on current rise ( $dl/dt = 100 \text{ A}/\mu\text{s}$ ) allows to design robust and compact control circuit for voltage regulator in motorbikes and industrial drives, overvoltage crowbar protection, motor control circuits in power tools and kitchen aids, inrush current limiting circuits.

**Table 1: Device summary**

Order code	Package	$V_{DRM}/V_{RRM}$	$I_{GT}$
TN4015H-6G	D²PAK	600 V	15 mA

# 1 Characteristics

Table 2: Absolute maximum ratings (limiting values),  $T_j = 25^\circ\text{C}$  unless otherwise specified

Symbol	Parameter		Value	Unit	
$I_{T(\text{RMS})}$	RMS on-state current (180 ° conduction angle)	$T_c = 119^\circ\text{C}$	40	A	
$I_{T(\text{AV})}$	Average on-state current (180 ° conduction angle)	$T_c = 120^\circ\text{C}$	25	A	
		$T_c = 125^\circ\text{C}$	22		
		$T_c = 128^\circ\text{C}$	20		
$I_{TSM}$	Non repetitive surge peak on-state current	$t_p = 8.3 \text{ ms}$	394	A	
		$t_p = 10 \text{ ms}$	360		
$I^2t$	$I^2t$ value for fusing	$t_p = 10 \text{ ms}$	648	$\text{A}^2\text{s}$	
$dI/dt$	Critical rate of rise of on-state current $I_G = 2 \times I_{GT}$ , $t_r \leq 100 \text{ ns}$	$f = 60 \text{ Hz}$	100	$\text{A}/\mu\text{s}$	
$V_{DRM}/V_{RRM}$	Repetitive peak off-state voltage	$T_j = 150^\circ\text{C}$	600	V	
$V_{DSM}/V_{RSM}$	Non repetitive surge peak off-state voltage	$t_p = 10 \text{ ms}$	$V_{DRM}/V_{RRM} + 100$	V	
$I_{GM}$	Peak gate current	$t_p = 20 \mu\text{s}$	$T_j = 150^\circ\text{C}$	4	A
$P_{G(\text{AV})}$	Average gate power dissipation		$T_j = 150^\circ\text{C}$	1	W
$V_{RGM}$	Maximum peak reverse gate voltage			5	V
$T_{stg}$	Storage junction temperature range			-40 to +150	$^\circ\text{C}$
$T_j$	Maximum operating junction temperature			-40 to +150	$^\circ\text{C}$
$T_L$	Maximum lead temperature soldering during 10 s			260	$^\circ\text{C}$

Table 3: Electrical characteristics ( $T_j = 25^\circ\text{C}$  unless otherwise specified)

Symbol	Test Conditions		Value	Unit	
$I_{GT}$	$V_D = 12 \text{ V}$ , $R_L = 33 \Omega$	Max.	15	mA	
$V_{GT}$		Max.	1.3	V	
$V_{GD}$	$V_D = V_{DRM}$ , $R_L = 3.3 \text{ k}\Omega$	$T_j = 150^\circ\text{C}$	Min.	0.15	V
$I_H$	$I_T = 500 \text{ mA}$ , gate open		Max.	60	mA
$I_L$	$I_G = 1.2 \times I_{GT}$		Max.	80	mA
$dV/dt$	$V_D = 402 \text{ V}$ , gate open	$T_j = 150^\circ\text{C}$	Min.	500	$\text{V}/\mu\text{s}$
$t_{gt}$	$I_T = 80 \text{ A}$ , $V_D = 600 \text{ V}$ , $I_G = 100 \text{ mA}$ , $(dI_G/dt) \text{ max} = 0.2 \text{ A}/\mu\text{s}$		Typ.	1.9	$\mu\text{s}$
$t_q$	$V_D = 402 \text{ V}$ , $I_T = 40 \text{ A}$ , $V_R = 25 \text{ V}$ , $dV_D/dt = 50 \text{ V}/\mu\text{s}$ , $(dI_G/dt) \text{ max} = 30 \text{ A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$	Typ.	85	$\mu\text{s}$

Table 4: Static characteristics

Symbol	Test conditions		Value	Unit
$V_{TM}$	$I_{TM} = 80 \text{ A}, t_p = 380 \mu\text{s}$	$T_j = 25^\circ\text{C}$	Max.	1.6
$V_{TO}$	Threshold voltage	$T_j = 150^\circ\text{C}$	Max.	0.85
$R_D$	Dynamic resistance	$T_j = 150^\circ\text{C}$	Max.	10 $\text{m}\Omega$
$I_{DRM}, I_{RRM}$	$V_D = V_{DRM} = V_{RRM}$	$T_j = 25^\circ\text{C}$	Max.	10 $\mu\text{A}$
		$T_j = 150^\circ\text{C}$	Max.	6 $\text{mA}$


Table 5: Thermal parameters

Symbol	Parameter	Value	Unit
$R_{th(j-c)}$	Junction to case (DC)	Max.	0.8
$R_{th(j-a)}$	Junction to ambient (DC)	Typ.	$^{\circ}\text{C/W}$


**Notes:**(1)  $S$  = Copper surface under tab

## 1.1 Characteristics (curves)


**Figure 1: Maximum average power dissipation versus average on-state current**




**Figure 2: Average and DC on-state current versus case temperature**




**Figure 3: Average and D.C. on state current versus ambient temperature**




**Figure 4: Relative variation of thermal impedance versus pulse duration**






**Figure 5: Relative variation of gate trigger current and gate voltage versus junction temperature (typical values)**



**Figure 6: Relative variation of holding and latching current versus junction temperature (typical values)**





## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

- Epoxy meets UL94, V0
- Lead-free, halogen-free package

### 2.1 D<sup>2</sup>PAK package information

Figure 13: D<sup>2</sup>PAK package outline





Table 6: D<sup>2</sup>PAK package mechanical data

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.30		4.60	0.1692		0.1811
A1	2.49		2.69	0.0980		0.1059
A2	0.03		0.23	0.0011		0.0090
B	0.70		0.93	0.0275		0.0366
B2	1.25	1.40		0.0492	0.0551	
C	0.45		0.60	0.0177		0.0236
C2	1.21		1.36	0.0476		0.0535
D	8.95		9.35	0.3523		0.3681
D2	1.3		1.7	0.051		0.066
E	10.00		10.28	0.3937		0.4047
E1	8.3		8.7	0.326		0.342
E2	6.85		7.25	0.2696		0.2854
G	4.88		5.28	0.1921		0.2078
L	15.00		15.85	0.5905		0.6240
L2	1.27		1.40	0.050		0.0551
L3	1.40		1.75	0.0551		0.0688
R		0.40			0.0157	
V2	0°		8°	0°		8°

Figure 14: D<sup>2</sup>PAK recommended footprint (dimensions in mm)

### 3 Ordering information

Figure 15: Ordering information scheme




Table 7: Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
TN4015H-6G	TN4015H6	D <sup>2</sup> PAK	1.5 g	50	Tube
TN4015H-6G-TR	TN4015H6	D <sup>2</sup> PAK	1.5 g	1000	Tape and reel

### 4 Revision history

Table 8: Document revision history

Date	Revision	Changes
01-Aug-2016	1	Initial release.

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2016 STMicroelectronics – All rights reserved