

Duplex Multimode 62.5/125 Fiber Patch Cable (MTRJ/ST), 5M (16 ft.)

MODEL NUMBER: N308-05M



Highlights

- Premium PVC 62.5/125µm multimode patch cables
- Attenuation loss meets or exceeds the latest industry standards

System Requirements

 Any fiber optic hardware or NIC card requiring multimode duplex cable with MT-RJ/ST connectors

Package Includes

 5-meter duplex MMF cable MTRJ/ST 62.5/125 fiber

Features

- Manufactured from 62.5/125 duplex (zipcord) fiber
- PVC jacket
- Length: 5-meters (16.4ft) Connectors: MTRJ to 2 ST
- Insertion loss testing performed on every connector (0.2db typical) and provided with cable
- Beveled edge on ends of glass makes insertion of plug a breeze
- Fiber made from glass (not a polymer)
- Color coded shrouds identify transmit and receive
- Fiber optic distributed data interface (FDDI) rated
- OFNR (riser rated)

Specifications

OVERVIEW	RVIEW	
UPC Code	037332123688	
Technology	Multimode	
Optical Mode	OM1	
PHYSICAL		
Cable Jacket Color	Orange	
Connector Color	Black	
Cable Jacket Material	LSZH	
Cable Jacket Rating	OFNR	



Olad Diameter (science)	405	
Clad Diameter (microns)	125	
Core Diameter (microns)	62.5	
Number of Fibers	2	
Cable Length (ft.)	16.4	
Cable Length (m)	5.00	
Cable Length (in.)	196.9	
Minimum Bend Radius	20 mm (Dynamic); 10 mm (Static)	
Shipping Dimensions (hwd / in.)	0.10 x 6.60 x 9.00	
Shipping Dimensions (hwd / cm)	0.25 x 16.76 x 22.86	
Shipping Weight (lbs.)	0.10	
Shipping Weight (kg)	0.05	
Fiber Cable Length	5M (16.4 ft)	
ENVIRONMENTAL		
Operating Temperature Range	-4° to 140°F (-20° to 60°C)	
Storage Temperature Range	-4° to 140°F (-20° to 60°C)	
Operating Humidity Range	5% to 85% RH, Non-Condensing	
Storage Humidity Range		
Storage numidity Range	35% to 65% RH, Non-Condensing	
COMMUNICATIONS		
Network Compatibility	1 Gbps (Gigabit)	
Attenuation @ 850NM	3.0 dB/km	
Insertion Loss	MTRJ 0.50 dB; ST 0.20 dB	
CONNECTIONS Side A - Connector 1	MTRJ DUPLEX (MALE)	
Side B - Connector 1		
Endface Polish	ST DUPLEX (MALE) PC	
Endrace Polish	PC	
FEATURES & SPECIFICATIONS		
Push/Pull Tabs	No	
Breakout	No	
Trunk	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; REACH	
i roddot Compilance	NOID, NEADIT	



WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.