


## PEH532RDH4220M4S

Aliases (A541EJ222M200E)

PEH532, Aluminum Electrolytic, 2,200 uF, 20%, 200 VDC, -40/+105°C



Click [here](#) for the 3D model.

### Dimensions

D	35mm +/-0.5mm
L	55mm +/-1mm
S	22.5mm NOM
LL	4mm +/-1mm
F	2mm +/-0.1mm

### Packaging Specifications

Packaging	Bulk, Bag
Packaging Quantity	100

### General Information

Series	PEH532
Dielectric	Aluminum Electrolytic
Description	Snap-In, Aluminum Electrolytic
RoHS	Yes
Lead	4 Pin Short
AEC-Q200	No
Component Weight	85 g
Notes	Add 0.5mm To D And 1mm To L For Sleeving.
Shelf Life	208 Weeks

### Specifications

Capacitance	2,200 uF
Capacitance Tolerance	20%
Voltage DC	200 VDC
Temperature Range	-40/+105°C
Rated Temperature	105°C
Life	1500 Hrs (Rated Voltage And Ripple Current At 105C), 2000 Hrs (Rated Voltage At 105C)
Resistance	67 mOhms (100Hz 20C), 38 mOhms (100kHz 20C)
Ripple Current	3.1 Amps (100Hz 105C), 8.7 Amps (20kHz 40C)
Leakage Current	1320 uA (5min 20°C)