XY2CH14270TK

Telemecanique emergency stop rope pull switches XY2C, rope pull switch XY2CH, 240 V, AC, 10 A, XY2C



Main

Range of Product	Telemecanique Emergency stop rope pull switches XY2C
Device short name	XY2CH
Overvoltage category	Class I EN/IEC 61140 Class I NF C 20-030

Complementary

Complementary	
Tightening torque	7.0810.62 lbf.in (0.81.2 N.m)
Safety level	Can reach PL = e with the appropriate monitoring system and correctly wired EN/ISO 13849-1
	Can reach category 4 with the appropriate monitoring system and correctly wired EN/ISO 13849-1
	Can reach SIL 3 with the appropriate monitoring system and correctly wired EN/ IEC 61508
Safety reliability data	B10d = 4000000 value given for a life time of 20 years limited by mechanical or contact wear IEC 60947-5-5
Marking	CE
Mechanical durability	800000 cycles
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A
	0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	400 V 3)EN/IEC 60947-1
	300 VUL 508
	300 VCSA C22.2 No 14
Compatibility code	XY2CH

Environment

LITTIONICH		
Product certifications	CCC category NISD emergency stop devices CE	
Protective treatment	TC	
Ambient Air Temperature for Operation	-40158 °F (-4070 °C)	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Vibration resistance	10 gn 10300 Hz)EN/IEC 60068-2-6	
Shock resistance	50 gn 11 ms EN/IEC 60068-2-27	
IP degree of protection	IP66 IEC 60529	

Ordering and shipping details

22441-LIMIT SWITCHES,CABLE PULL
Т
3389119085717
1
2.31 lb(US) (1.05 kg)

Returnability	No
Country of origin	MA
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	3.58 in (9.1 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	7.68 in (19.5 cm)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
Contractual warranty	
Warranty	18 months