

REV INITIALS

DESCRIPTION

NOTES:
1. TOLERANCE ±.015 UNLESS NOTED OTHERWISE.
2. TOP CONDUCTIVE LAYER TO BE .007' THICK POLYESTER WITH AN ANTI-GLARE COATING
3. THE CONNECTOR IS LOCATED ON THE LEFT SIDE OF THE PANEL.
4. PIN ONE LOCATION IS THE TOP PIN WHEN VIEWING WITH CABLE TO THE LEFT.
5. PINOUT TO BE AS INDICATED.
FIN 1 - UPPER RIGHT.
PIN 3 - LOWER RIGHT.
PIN 3 - PLANE.
PIN 4 - UPPER LEFT.
6. TAIL TO BE TERMINATED USING AMP RECEPTACLE 2-487406-4 OR EQUIVALENT
7. HOUSING TO BE AMP PART NUMBER 487378-4 OR EQUIVALENT
8. TOTAL PANEL THICKNESS TO BE 0.087' NOMINAL.

DRN: PEH
CHKD: MLR
APVD: 12.1" DIAGONAL 5 WIRE TOUCHSCREEN DATE: 12/10/07 | SCALE: 1:1 DATE: 12/14/07 | PART NUMBER: DATE: CANNON FALLS, MN 55009 | TOL: ±,015 400403

MCTS