



TOP VIEW




**SECTION B-B
END VIEW**




Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
 Contact Factory (modshop@hammfg.com) for quotes
 Solid models of this enclosure available in .stp or .x_t
 (Part number and text placement/orientation on our products are subject to change,
 we do not recommend using them as a locating reference for modification purposes)


NOTE	
Purchased assembly includes box, lid, 2 Panels and 4 cover screws	
Molded from FR ABS (UL94-V0) plastic	
Recommended Cover screw torque -- 21-28 ozf-in (15-20 cN-m)	




**SECTION A-A
SIDE VIEW**



USEABLE PANEL AREA



INSIDE BOTTOM



INSIDE TOP
 MAXIMUM PCB LAYOUT
 DRAWINGS ARE AVAILABLE

Dimensions:
 mm
 [inches]

1552	
1552C Regular Enclosure	
Fire Retardant ABS Grey	1552C1GY
Fire Retardant ABS Black	1552C1BK
ACCESSORIES	
1552C End Panel (Pkg 10)	1552CPLGY-10 (Grey) 1552CPLBK-10 (Black)
1552C cover screw [#2 X 1/2" Self-Tap] (Pkg 50)	SC550-50 (Grey) SC550BK-50 (Black)
1552C Cable gland Kit [1 Cable Gland, 1 Tie Down, 2 Tie down screws]	1552CPGKITGY (Grey) 1552CPGKITBK (Black)
1552 Wall Mount Holder	1552CHGY (Grey) 1552CHBK (Black)
Tie Down Screw [#2 X 1/4" Self-Tap] (Pkg 50)	SC508-50
P.C. Board Plastite Self Tapping Screw [#2 x 3/16" Self-Tap] (PKG 100)	1553WTS100

**HAMMOND
MANUFACTURING**

1552C1

www.hammondmfg.com