

8810-A

BLACK RIGID URETHANE

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: 8810-A**Other Means of Identification:** Black Rigid Urethane**Related Part #** 8810-375ML, 8810-2.55L, 8810-60L

Recommended Use and Restriction on Use

Use: Urethane resin for use with hardeners**Uses Advised Against:** Not applicable

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA**☎** +1-800-340-0772**Fax** +1-800-340-0773**E-mail** support@mgchemicals.com**Web** www.mgchemicals.com**☎** +1-905-331-1396**Fax** +1-905-331-2682**E-mail** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

8810-A
BLACK RIGID URETHANE
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Sensitization Skin	1	Warning	Exclamation
Hazardous to the Aquatic Environment Chronic	3	none	none

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	Warning
Pictograms	Hazard Statements
	H317: May cause an allergic skin irritation
<i>none mandated</i>	H412: Harmful to aquatic life with long lasting effects

Section continued on the next page

8810-A
BLACK RIGID URETHANE

Continued...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P261	Avoid breathing mist, vapors, or spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves.
P273	Avoid release to the environment.
Response	Precautionary Statements
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Other Hazards

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	% (weight)
1318-02-1	zeolite	10%
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin)	1%
1333-86-4	carbon black	0.3%
68609-97-2	alkyl glycidyl ether	0.2%

8810-A
BLACK RIGID URETHANE
Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF ON SKIN	P302 + P352, P362 + P364
Immediate Symptoms	<i>dry skin, allergic dermatitis</i>
Response	Wash with plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice or attention.
IF INHALED	P304 + P340, P308 + P313
Immediate Symptoms	<i>low toxicity</i>
Response	Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice or attention.
IF IN EYES	P305 + P351 + P338
Immediate Symptoms	<i>low toxicity: redness, pain, blurred vision</i>
Response	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	<i>low toxicity: abdominal pain, nausea, diarrhea, (see inhalation symptoms)</i>
Response	Rinse mouth. Do NOT induce vomiting.

Section 5: Fire-Fighting Measures

Extinguishing Media	Use extinguishing media suitable for surrounding materials.
Specific Hazards	Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO,CO ₂) and toxic fumes.
Fire-Fighter	Wear self-contained breathing apparatus and full fire fighting turn-out gear.

8810-A**BLACK RIGID URETHANE****Section 6: Accidental Release Measures**

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing the mist, spray, or vapors. Remove or keep away all sources of ignition or extreme heat.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist, vapors, or spray. Avoid release to the environment.
Handling	Wear protective gloves, protective clothing, and eye protection or face protection. Contaminated work clothing should not be allowed out of the workplace.
Storage	Store locked up.

8810-A
BLACK RIGID URETHANE
Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
zeolite ^{a)}	ACGIH	10 mg/m ³	3 mg/m ³
	U.S.A. OSHA PEL	15 mg/m ³	5 mg/m ³
	Canada AB	Not established	Not established
	Canada BC	Not established	Not established
	Canada ON	Not established	Not established
carbon black ^{b)}	Canada QC	Not established	Not established
	ACGIH	3.5 mg/m ³	Not established
	U.S.A. OSHA PEL	3.5 mg/m ³	Not established
	Canada AB	3.5 mg/m ³	Not established
	Canada BC	3 mg/m ³	Not established
Canada ON	3.5 mg/m ³	Not established	
Canada QC	3.5 mg/m ³	Not established	

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database² and from suppliers' SDSs were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Supplier SDS

b) Respirable airborne particles.

Engineering Controls
Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Because carbon black is bound to the liquid mixture, it does not present an airborne hazard under normal use.

Section continued on the next page

8810-A**BLACK RIGID URETHANE****Personal Protective Equipment****Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Ensure that glasses have side shields for lateral protection.

Skin Protection

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Respiratory Protection

For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

8810-A
BLACK RIGID URETHANE
Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Black	Upper Flammability Limit	Not available
Odor	Mild	Vapor Pressure @20 °C	Not available
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	1.10
Freezing/Melting Point	Not available	Solubility in Water	Insoluble
Boiling Point ^{a)}	≥288 °C [≥550 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	230 °C [446 °F]	Auto-ignition Temperature ^{a)}	≥305 °C [≥581 °F]
Evaporation Rate	<1 (ButAc = 1)	Decomposition Temperature	Not available
Flammability	Non flammable	Viscosity @25 °C	324 mm ² /s

a) Values based on the principal component.

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures.
Conditions to Avoid	Direct sunlight, high temperatures, open flames, sparks and incompatible substances.
Incompatibilities	Strong oxidizing agents, strong acids, alkali
Polymerization	Will not occur
Decomposition	Product decomposes at 270 °C without melting. For thermal decomposition, see combustion products in Section 5.

8810-A
BLACK RIGID URETHANE
Section 11: Toxicological Information
Summary of Effects and Symptoms by Routes of Exposure

Eyes	Low toxicity: May cause redness, pain, and blurred vision.
Skin	May cause dry skin and allergic dermatitis.
Inhalation	Low toxicity
Ingestion	Low toxicity: May abdominal pain, nausea, and diarrhea. See also inhalation symptoms.
Chronic	Prolonged or repeated exposure may cause skin may cause skin allergies.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
polypropylene glycol	5 000 mg/kg Rat	Not Available	Not Available
zeolite	Not Available	Not Available	Not Available
reaction product: bisphenol-A- (epichlorhydrin)	2 000 mg/kg Rat	2 000 mg/kg Rat	Not Available
carbon black	15 400 mg/kg Rat	3 000 mg/kg Rabbit	Not Available
alkyl glycidyl ether	19 200 mg/kg Rat	4 000 mg/kg Rabbit	Not Available

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDSs were also consulted.

Section continued on the next page

8810-A**BLACK RIGID URETHANE****Other Toxicological Effects****Skin Corrosion/Irritation**

Based on available data, the classification criteria are not met.

Serious Eye Damage/Irritation

Based on available data, the classification criteria are not met.

Sensitization
(allergic reactions)

Reaction product: bisphenol-A-(epichlorhydrin) and alkyl glycidyl ether may cause skin sensitization.

Carcinogenicity
(risk of cancer)

Carbon black are possibly carcinogenic by airborne routes of exposures.

Because the carbon black is bound in the epoxy liquid mixture, it is not available as an airborne hazard (dust, mist, or spray) under normal use.

Carbon Black [1333-86-4]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A3: Confirmed Animal Carcinogen with Unknown Relevance to Humans

CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size)

NTP: Not listed

Mutagenicity
(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

Reproductive Toxicity
(risk to sex functions)

Based on available data, the classification criteria are not met.

Teratogenicity (risk of fetus malformation)

Based on available data, the classification criteria are not met.

STOT-Single Exposure

The n-butyl acetate, butan-2-one, and 1-methoxy-2-propanol acetate components can affect the central nervous system by inhalation causing drowsiness or dizziness.

STOT-Repeated Exposure

Based on available data, the classification criteria are not met.

Aspiration Hazard

Based on available data, the classification criteria are not met. There are no cat 1 substances, and the kinematic viscosity is $>20.5 \text{ mm}^2/\text{s}$ at $40 \text{ }^\circ\text{C}$.

8810-A**BLACK RIGID URETHANE****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The reaction product: bisphenol-A-(epichlorhydrin) ingredient is an acute category 2 environmental toxicant

The polypropylene glycol, zeolite, carbon black, alkyl glycidyl ether ingredient is not classified as an environmental hazard according to GHS criteria.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Category 3

Harmful to aquatic life with long lasting effects

Avoid release to the environment.

Biodegradability

Expected to be biodegradable. The volatile solvent constituents will oxidize rapidly in air by photochemical reaction.

Other Effects

Not available

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

8810-A**BLACK RIGID URETHANE****Section 14: Transport Information****Ground**

Refer to TDG (Canadian Transportation of Dangerous Goods regulations) and **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Not Regulated

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Not Regulated

Sea

Refer to IMDG regulations.

Not Regulated

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information**Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.


Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

Section continued on the next page

8810-A**BLACK RIGID URETHANE****USA****Other Classifications****HMIS® RATING**

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product contains methyl methacrylate, which is listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain ingredients that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product contains carbon black, but it is bound and exposures during normal conditions of uses are below the Safe Harbor Threshold.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

8810-A**BLACK RIGID URETHANE****Section 16: Other Information**

SDS Prepared by MG Chemicals' Regulatory Department

Date of Creation 12 June 2020

Supersedes 04 March 2020

Reason for Changes: Added new part number.

Reference

1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content
Wt	Weight

Section continued on the next page

8810-A**BLACK RIGID URETHANE****Technical Queries**

Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses

Manufacturing & Support

1210 Corporate Drive

Burlington, Ontario, Canada Surrey, British Columbia, Canada

L7L 5R6

Head Office

9347-193rd Street

V4N 4E7

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.