



NOTES:

1. Material: Polyamide (Nylon) (L-P-410), Composition 6/6
2. Finish: Plain
3. All Drawing Dimensions are in Inches [mm]
4. Unless otherwise specified, Edge Breaks, Radii or Countersinks 0.005-0.015
5. All features in accordance with NAS61

| | | | | | | |
|--|--|---|--|--------|--------|-----|
|  95 Silvermine Rd., Seymour CT 06483 Tel: 203-888-2133, Fax: 203-888-9860 | This Drawing is the Property of RAF. It contains confidential, proprietary information that is RAF property. Do not disclose to or duplicate for others except as authorized by RAF. | TOLERANCES ALL DIMENSIONS ARE INCHES (UNLESS OTHERWISE SPECIFIED) METALLIC LENGTHS <math><= 6</math> INCHES ± 0.005 LENGTH > 6 INCHES ± 0.010 DIAMETERS: ± 0.005 NON-METALLIC LENGTH: ± 0.010 DIAMETERS: ± 0.010 INTERNAL THREADS: MINIMUM THREAD DEPTH | COMPONENT | SPACER | | |
| | | | NAS61-02B-012 3/16" Round Spacer | | SCALE | REV |
| | | | 10.13 | | 03 | |
| | | | SHEET | | 1 of 1 | |