



Perfect-It™ 1-Step Finishing Material

33038 • 33039 • 33040 • 33041

Technical Data

March 2019

3M Part Number	3M Part Descriptor
33038	3M™ Perfect-It™ 1-Step Finishing Material, 33038, 8 fl oz, 12 per case
33039	3M™ Perfect-It™ 1-Step Finishing Material, 33039, 32 fl oz, 6 per case
33040	3M™ Perfect-It™ 1-Step Finishing Material, 33040, 1 Gallon, 4 per case
33041	3M™ Perfect-It™ 1-Step Finishing Material, 33041, Drum, 1 per case

Product Description 3M™ Perfect-It™ 1-Step Finishing Material is a high-performance, fast cutting finishing material designed to remove 3000 grit and finer scratches. It allows you to eliminate the use of traditional rubbing compounds and machine polishes, while still leaving a high-gloss finish with minimal swirl marks.

- Features**
- Removes 3M™ Trizact™ 8000 scratches, providing a 1-Step finish on most colors
 - Provides the cut of a compound and the swirl-free finish of a polish
 - Wetter formulation allows for longer work time without drying
 - Wipes off easily, requiring less clean up time

Typical Physical Properties NOTE: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

pH	8.0
Color	Light Purple
Density	1.05 g/mL
Viscosity	40,000 centipoise
Volatile Organic Compounds	16.0 % weight

Product Uses 3M™ Perfect-It™ 1-Step Finishing Material is developed to remove Trizact™ 8000 scratches during the paint finishing process of automotive clear coat surfaces, light industrial clear coat surfaces, marine gelcoat and paint finishes.

Directions for use Polish the surface between 1200 and 2000 Max RPM using a rotary polisher equipped with a Quick Connect 3M™ Perfect-It™ 1-Step Foam Finishing Pad.

1. Apply enough finishing material to work a 2' x 2' area. For best results, use enough material to leave a thin film on the surface for multiple passes before it begins to dry.

3M™ Perfect-It™ 1-Step Finishing Material

33038 • 33039 • 33040 • 33041

-
- Directions for use continued
2. Polish using medium pressure for the first passes. As the material begins to dry, use light pressure to pick up residual film and leave the best possible finish. Clean pads as needed.
 3. Use a microfiber towel to remove any residual film and/or sling before moving on to another panel or subsequent polishing step.

Applications Paint and gelcoat refinishing.

Storage and Handling Keep from freezing.

Precautionary Information Before using this product, please reference Product Label and/or Safety Data Sheet for Health and Safety Information. Note: Laws controlling the acceptable amounts of Volatile Organic Compounds (VOCs) vary by state, and in some cases by locality. For surface preparation and clean-up activities, consult federal, state and local regulations regarding use of products containing VOCs in your area.

Technical Information The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Use Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy and Disclaimer Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Automotive Aftermarket Division
3M Center, Building 0223-06-S-07
St. Paul, MN 55144-1000
1-877-666-2277 (1-877-MMM-CARS)
3MCollision.com