




## UDSK24-5/8"-15MM-F

Ruland UDSK24-5/8"-15MM-F, 5/8" x 15mm Double Universal Joint, Friction Bearing, Steel, Set Screw With Keyway, 1.495" (38.0mm) OD, 6.563" (166.7mm) Length





## **Description**

Ruland UDSK24-5/8"-15MM-F is a double cardan friction bearing universal joint with 0.6250" x 15mm bores, 3/16" x 5mm keyways, 1.495" (38.0mm) OD, 6.563" (166.7mm) length, and 5/16-18 set screws. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UDSK24-5/8"-15MM-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT24/38-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

**Product Specifications** 

Keyway (K1)         3/16 in         Keyway (K2)         5 mm           B1 Max Shaft Penetration         1.400 in (35.6 mm)         1.400 in (35.6 mm)           Joint Outer Diameter (OD)         1.495 in (38.0 mm)         Bore Tolerance         +0.0010 in / -0.0000 in (+0.00 / -0.0000 mm)           Length (L)         6.563 in (166.7 mm)         Center Yoke Length (LC)         2.313 in (58.8 mm)           Yoke Length (LY)         2.125 in (54.0 mm)         Hub Depth (LH)         1.400 in (35.6 mm)           Broached Set Screw         5/16-18         Screw Finish         Black Oxide           Peak Torque         9,000 in-lb (1,016.9 Nm)         Rated Torque         1,800 in-lb (203.4 Nm)           Max Operating Angle         90°         Material Specification         Alloy Steel           Manufacturer         Belden Universal         Country of Origin         USA           Recommended Lubricant         LUBRIPLATE No. 1200-2         Matching Boot Cover         UBOOT24/38-NI-KIT           UPC         63452932597         Tariff Code         8483.60.4000           UNSPC         25173810           Note 1         Performance ratings are for guidance only. The user must determine suitability for a particular applicance only.	Product Specifications			
B1 Max Shaft Penetration Joint Outer Diameter (OD) 1.495 in (38.0 mm) 1.495 in (38.0 mm) 1.495 in (38.0 mm) 1.495 in (38.0 mm) Bore Tolerance +0.0010 in /-0.0000 in (+0.00 /-0.000 mm)  Length (L) 5.563 in (166.7 mm) Center Yoke Length (LC) 2.313 in (58.8 mm) Yoke Length (LY) 2.125 in (54.0 mm) Hub Depth (LH) 1.400 in (35.6 mm)  Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 9,000 in-lb (1,016.9 Nm) Rated Torque 1,800 in-lb (203.4 Nm)  Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT UPC 63452932597 Tariff Code 8483.60.4000  UNSPC Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applicar California to cause cancer and birth defects or other reproductive harm. For more information go to	Bore (B1)	0.6250 in	Small Bore (B2)	15 mm
Joint Outer Diameter (OD)  1.495 in (38.0 mm)  Bore Tolerance  +0.0010 in / -0.0000 in (+0.00 / -0.0000 mm)  Length (L)  5.663 in (166.7 mm)  Center Yoke Length (LC)  2.313 in (58.8 mm)  Yoke Length (LY)  2.125 in (54.0 mm)  Hub Depth (LH)  1.400 in (35.6 mm)  Broached Set Screw  5/16-18  Screw Finish  Black Oxide  Peak Torque  9,000 in-lb (1,016.9 Nm)  Rated Torque  1,800 in-lb (203.4 Nm)  Max Operating Angle  90°  Material Specification  Alloy Steel  Manufacturer  Belden Universal  Country of Origin  USA  Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT24/38-NI-KIT  UPC  63452932597  Tariff Code  8483.60.4000  UNSPC  VOST 1  Performance ratings are for guidance only. The user must determine suitability for a particular applicar  Prop 65  WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Keyway (K1)	3/16 in	Keyway (K2)	5 mm
/ -0.000 mm)  Length (L) 6.563 in (166.7 mm) Center Yoke Length (LC) 2.313 in (58.8 mm)  Yoke Length (LY) 2.125 in (54.0 mm) Hub Depth (LH) 1.400 in (35.6 mm)  Broached Set Screw 5/16-18 Screw Finish Black Oxide  Peak Torque 9,000 in-lb (1,016.9 Nm) Rated Torque 1,800 in-lb (203.4 Nm)  Max Operating Angle 90° Material Specification Alloy Steel  Manufacturer Belden Universal Country of Origin USA  Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT  UPC 63452932597 Tariff Code 8483.60.4000  UNSPC 25173810  Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applicar  ↑ WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	B1 Max Shaft Penetration	1.400 in (35.6 mm)	<b>B2 Max Shaft Penetration</b>	1.400 in (35.6 mm)
Yoke Length (LY)  2.125 in (54.0 mm)  Hub Depth (LH)  1.400 in (35.6 mm)  Broached Set Screw  5/16-18  Screw Finish  Black Oxide  Peak Torque  9,000 in-lb (1,016.9 Nm)  Rated Torque  1,800 in-lb (203.4 Nm)  Max Operating Angle  90°  Material Specification  Alloy Steel  Manufacturer  Belden Universal  Country of Origin  USA  Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT24/38-NI-KIT  UPC  63452932597  Tariff Code  8483.60.4000  UNSPC  25173810  Performance ratings are for guidance only. The user must determine suitability for a particular applicar  Prop 65  MARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Joint Outer Diameter (OD)	1.495 in (38.0 mm)	Bore Tolerance	+0.0010 in / -0.0000 in (+0.025 mm / -0.000 mm)
Broached Set Screw 5/16-18 Screw Finish Black Oxide  Peak Torque 9,000 in-lb (1,016.9 Nm) Rated Torque 1,800 in-lb (203.4 Nm)  Max Operating Angle 90° Material Specification Alloy Steel  Manufacturer Belden Universal Country of Origin USA  Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT  UPC 63452932597 Tariff Code 8483.60.4000  UNSPC 25173810  Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applicar  Prop 65 AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Length (L)	6.563 in (166.7 mm)	Center Yoke Length (LC)	2.313 in (58.8 mm)
Peak Torque 9,000 in-lb (1,016.9 Nm) Rated Torque 1,800 in-lb (203.4 Nm)  Max Operating Angle 90° Material Specification Alloy Steel  Manufacturer Belden Universal Country of Origin USA  Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT  UPC 63452932597 Tariff Code 8483.60.4000  UNSPC 25173810  Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applica  Prop 65 △WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Yoke Length (LY)	2.125 in (54.0 mm)	Hub Depth (LH)	1.400 in (35.6 mm)
Max Operating Angle90°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT24/38-NI-KITUPC63452932597Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicarProp 65▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Broached Set Screw	5/16-18	Screw Finish	Black Oxide
Manufacturer  Belden Universal  Country of Origin  USA  Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT24/38-NI-KIT  UPC  63452932597  Tariff Code  8483.60.4000  UNSPC  25173810  Performance ratings are for guidance only. The user must determine suitability for a particular applicar  Prop 65  MARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Peak Torque	9,000 in-lb (1,016.9 Nm)	Rated Torque	1,800 in-lb (203.4 Nm)
Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT24/38-NI-KIT  Tariff Code  8483.60.4000  UNSPC  25173810  Performance ratings are for guidance only. The user must determine suitability for a particular applicar  Prop 65  WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Max Operating Angle	90°	Material Specification	Alloy Steel
UPC 63452932597 Tariff Code 8483.60.4000  UNSPC 25173810  Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applica  Prop 65 △WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Manufacturer	Belden Universal	Country of Origin	USA
UNSPC  25173810  Note 1  Performance ratings are for guidance only. The user must determine suitability for a particular applicar  Prop 65  △WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Recommended Lubricant	LUBRIPLATE No. 1200-2	Matching Boot Cover	UBOOT24/38-NI-KIT
Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applicate  Prop 65 ▲ WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	UPC	63452932597	Tariff Code	8483.60.4000
Prop 65  AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	UNSPC	25173810		
California to cause cancer and birth defects or other reproductive harm. For more information go to	Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
	Prop 65	·		