

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Protect It! 6-Outlet Surge Protector, 15 ft. Cord, 790 Joules, Diagnostic LED, Light Gray Housing

MODEL NUMBER: TLP615







Safeguard your computer, printer, scanner, router, modem and other small home electronics against dangerous surges, spikes and line noise. Recommended for any desktop, network or home application requiring AC line protection.

Description

Perfect for your home or office workstation, the TLP615 Protect It!® 6-Outlet Surge Protector features a surge protection rating of 790 joules to defend your sensitive electronic components against strong surges and spikes. In fact, Tripp Lite will repair or replace any connected equipment damaged by surges, including direct lightning strikes, up to \$20,000 for life (valid in the U.S., Canada and Puerto Rico only).

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP615 protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G). It also filters out electromagnetic interference (EMI) and radio frequency interference (RFI) that can disrupt your electronics and inflict hardware damage or data loss.

Your devices plug into six NEMA 5-15R outlets, one of which is placed at the end to accept a bulky transformer without blocking adjacent outlets. An integrated 15A circuit breaker protects all outlets and shuts down connected equipment in case of overload. The lighted on/off switch provides one-touch control over connected equipment. A diagnostic LED confirms your connected equipment is protected.

The 15-foot AC power cord with NEMA 5-15P plug gives you enough flexibility to reach distant outlets while fitting easily into your workstation or home theater setup. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the light gray plastic housing.

Features

790-Joule Surge Protection for Home or Office Electronics

• Protects your computer, printer, scanner, router, modem and other small home electronics against even

Highlights

- 6 NEMA 5-15R outlets—one designed for a bulky transformer
- 790-joule surge protection rating
- Filters out threatening EMI/RFI line noise
- 15A resettable circuit breaker prevents dangerous overloads
- 15 ft. AC power cord with NEMA
 5-15P plug

Package Includes

- TLP615 Protect It! 6-Outlet Surge Protector, Light Gray Housing
- Owner's manual



the strongest surges and spikes

- · Recommended for any desktop, network or home electronics application requiring AC line protection
- Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- · Filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss
- Exceeds IEEE 587 Category A and B surge suppression specifications 6 Outlets Accept Wide Range of Electronic Devices
- 6 NEMA 5-15R AC outlets accept most computers and peripherals
- Special end outlet designed for bulky transformers without blocking other outlets **Premium Safety Features**
- · Lighted on/off switch provides one-touch control over connected equipment
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing
- equipment damage and indicating replacement is required
- Diagnostic LED confirms protection status at a glance
- · Conforms to current UL 1449 3rd Edition safety standards
- ABS fire retardant plastic case provides extra safety and durability **Fits Effortlessly Into Your Workstation**
- 15 ft. AC power cord with NEMA 5-15P plug reaches distant outlets
- Keyhole slots on bottom panel provide convenient wall or desk mounting options Backed by Tripp Lite's Ultimate Lifetime Insurance
- \$20,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge
 - (U.S., Canada and Puerto Rico only)

Specifications

OVERVIEW		
UPC Code	037332166418	
OUTPUT		
Frequency Compatibility	60 Hz	
Output (Watts)	1800	
Output Receptacles	(6) 5-15R	
Circuit Breaker (amps)	15	
Overload Protection	15A resettable illuminated combo switch / circuit breaker	
Transformer Accommodation	(2) Yes	
Outlet Orientation	Single row of 6 outlets	
Right-Angle Outlets	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Input Cord Gauge Type14Voltage Compatibility (VAC)120Maximum Surge Amps355Input Plug TypeNEInput Cord Length (ft.)15Right-Angle PlugNoInput Cord Length (m)4.5Integrated Cord ClipNoUSER INTERFACE, ALERTS & CONTROLDiagnostic LED(s)YesSwitchesConDiagnostic LED DetailsBuilSURGE / NOISE SUPPRESSION790AC Suppression Joule Rating790AC Suppression Response Time< 1Protection ModesInclClamping Voltage (RMS)150	500 EMA 5-15P
Voltage Compatibility (VAC)120Maximum Surge Amps355Input Plug TypeNEInput Cord Length (ft.)15Right-Angle PlugNoInput Cord Length (m)4.5Integrated Cord ClipNoUSER INTERFACE, ALERTS & CONTROLDiagnostic LED(s)YesSwitchesConDiagnostic LED DetailsBuiSURGE / NOISE SUPPRESSIONAC Suppression Joule Rating790AC Suppression Response Time< 1	0 500 EMA 5-15P
Maximum Surge Amps 355 Input Plug Type NE Input Cord Length (ft.) 15 Right-Angle Plug No Input Cord Length (m) 4.5 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROL Diagnostic LED(s) Yes Switches Con Diagnostic LED Details Bui SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 790 AC Suppression Response Time < 1	500 EMA 5-15P
Input Plug Type NE Input Cord Length (ft.) 15 Right-Angle Plug No Input Cord Length (m) 4.5 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROL Diagnostic LED(s) Yes Switches Diagnostic LED Details Buil SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time < 1	EMA 5-15P
Input Cord Length (ft.) 15 Right-Angle Plug No Input Cord Length (m) 4.5 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROL Diagnostic LED(s) Yes Switches Diagnostic LED (s) Yes Switches Con Diagnostic LED Details Buil SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time < 1	
Right-Angle Plug No Input Cord Length (m) 4.5 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROL Diagnostic LED(s) Yes Switches Con Diagnostic LED Details Bui SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 790 AC Suppression Response Time < 1	
Input Cord Length (m) 4.5 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROL Diagnostic LED(s) Yes Switches Diagnostic LED (s) Yes Switches Con Diagnostic LED Details Bui SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 790 AC Suppression Response Time < 1	
Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROL Diagnostic LED(s) Yes Switches Con Diagnostic LED (s) Yes Switches Con Diagnostic LED Details Buil SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 790 AC Suppression Response Time < 1	
USER INTERFACE, ALERTS & CONTROL Diagnostic LED(s) Yes Switches Con Diagnostic LED Details Buil SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 790 AC Suppression Response Time < 1	57
Diagnostic LED(s) Yes Switches Con Diagnostic LED Details Buil SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time < 1	
Switches Con Diagnostic LED Details Bui SURGE / NOISE SUPPRESSION AC AC Suppression Joule Rating 790 AC Suppression Response Time < 1	DLS
Diagnostic LED Details Build SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 790 AC Suppression Response Time < 1	25
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 790 AC Suppression Response Time < 1	ombination AC circuit breaker and 2 position red illuminated on/off power switch
AC Suppression Joule Rating 790 AC Suppression Response Time < 1	ilt-in LED confirms suppressor "protection present" (green) status
AC Suppression Response Time< 1Protection ModesInclClamping Voltage (RMS)150	
Protection Modes Incl Clamping Voltage (RMS) 150	0
Clamping Voltage (RMS) 150	1 ns
	cludes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
	0
UL1449 Let Through Rating 500	0V
EMI / RFI Filtering Up	o to 20 dB
Auto Shut-Off Yes	28
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection No	
Cable (Coax) Protection No	
Network (Ethernet) Protection No	
PHYSICAL	
Shipping Dimensions (hwd / in.) 13.	.20 x 5.80 x 1.80
Shipping Dimensions (hwd / cm) 33.	.53 x 14.73 x 4.57
Shipping Weight (lbs.) 1.7	77
Shipping Weight (kg) 0.8	30
Unit Dimensions (hwd / in.) 10.	.8 x 1.85 x 1.23
Unit Dimensions (hwd / cm) 27.	
Unit Weight (lbs.) 1.6	.43 x 4.70 x 3.12



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Unit Weight (kg)	0.73
Material of Construction	Plastic
Integrated Keyhole Mounting Slots	Yes
Housing Color	Light Gray
Receptacle Color	Light gray
Color (AC Line Cord)	Light Gray
Color	Light Gray
Outlets Measurement (Center to Center)	28.5mm
Keyhole Slot Mounting Measurement (Center to Center)	Distance between slots = 101mm; Distance between slot height = 28mm
Anti-Microbial Protected	No
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd EDITION
UL1363 (Power Tap)	UL1363
Canada	cUL
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$20,000 Ultimate Lifetime Insurance

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies