

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Box mounting bases B10, With single locking latch, Material: Polyamide, Protective cover material: Polyamide, Cable outlets: 2, lateral, Height: 74 mm, Cable gland: none, Gland: no, 2x M25, Protective cover: Yes, Standard

Product Description

One screw connection opening is closed, however it can be opened using a screwdriver. Incl. two plastic reductions M32 to M25

Key Commercial Data

Packing unit	1 STK
Custom tariff number	85389099
Country of origin	Poland

Technical data

Dimensions

Height	74 mm
Width	57 mm
Length	93 mm

Ambient conditions

Degree of protection of housing (IP)	IP66 (when plugged in)	
	IP54 (with closed protective cover)	
Degree of protection of housing (NEMA)	4 (NEMA 250)	
	4X (NEMA 250)	
	12 (NEMA 250)	
Ambient temperature (operation)	-40 °C 125 °C	

General

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24, HV03-I-PT, HC- 3- EC	
Size	B10	
Housing type	Box mounting bases	
Color	black	
Locking type	With single locking latch	



Technical data

General

No. of cable outlets	2		
Cable exit	lateral		
Screw connection	none		
Type of the screw connection	2x M25		
Protective cover	Yes		
Housing material	Polyamide		
Seal material	NBR		
Material lock	Polyamide		
Material, protective cover	Polyamide		
Flammability rating according to UL 94	V0		
Assembly instructions	Two plastic reductions M32 to M25 are provided		
Connection	One of the two openings for the screw connections is sealed but can be broken open using a screwdriver.		

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 5.1	27260703
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

ETIM

ETIM 5.0 EC000437

Approvals

Approvals

Approvals			
EAC			
Ex Approvals			



Approvals

Approvals submitted

Approval details

EAC

Accessories

Accessories

Full screw connection

Cable gland - G-INS-M25-M68N-PNES-BK - 1411134



Cable gland, Cable gland material: Polyamide 6, External cable diameter 11 mm ... 17 mm, Shielding: No, Connecting thread: M25, Color: jet black RAL 9005

Cable gland - G-INS-M25-M68N-PNES-BK - 1411134



Cable gland, Cable gland material: Polyamide 6, External cable diameter 11 mm ... 17 mm, Shielding: No, Connecting thread: M25, Color: jet black RAL 9005

Plug for cable screw gland

Screw plug - A-INSP-M25-65N-P-BK - 1415207



Screw plug, Cable gland material: Polyamide fiberglass reinforced, Connecting thread: M25, Color: black

Protective cover



Accessories

Protective covers - HC-B10-BC-HI-PLBK - 1407693



HEAVYCON EVO hinged protective cover, size B10, for EVO plastic supporting base element, IP65, PA

Seal

Profile gasket - HC-B10-SP-RBK - 1407707



Profile gasket for HEAVYCON EVO supporting base element type B10

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com