


IMPEDANCE (Z)							
25 MHz		100 MHz		300 MHz			
62	Ω	161	Ω	333	Ω		
-	Ω	129	Ω	-	Ω		
	25 N		25 MHz 100 M 62 Ω 161	25 MHz 100 MHz 62 Ω 161 Ω	25 MHz 100 MHz 300 M 62 Ω 161 Ω 333		

Z vs. FREQUENCY



FREQUENCY (MHz)

AGILENT E4991A Impedance/Material Analyzer HP 16092A Test Fixture,

FERRITE CORE DIMENSIONS (SPEC):

- A 76.00 [2.992] ± 1.00 [.039]
- B $65.00 [2.559] \pm 1.00 [.039]$
- C 24.00 [.945] + 0.50 [.020]
- D 15.10 [.594] + 0.80 [.031] - 0.50 [.020]
- E $4.40 [.173] \pm 0.40 [.016]$

WEIGHT/1000 99.60 kgs [219.58 Lbs]

60.	0.08 [.003] 0.50 [.020	0.08
(DETAIL "A CHAMFER SCALE 5: TYPICAL	

NOTES:

1. COSMETIC SPECIFICATION REFER TO WI-QA-038.

DIMENSIONS ARE IN mm[INCHES].			This print is the property of Laird				
				Tech, and is loaned in confidence			
				subject to return upon request and with the understanding that no copies shall be made without the			
				written consent of Laird Tech. All rights to design or invention are			
				reserved.			
				PROJECT/PART NUMBER: REV DRAWN BY:			
				28R2992-000 A Jcai			
				DATE: 01/14/15 SCALE: 1 : 1 MATERIAL:			
Α	ORIGINAL DRAFT	01/14/15	Jcai				
REV	DESCRIPTION	DATE	INT	^{CAD} # R2992 FERRITE			