NSYTBP241910H

PC box IP66 IK08 RAL7035 Int.H225W175D100 Ext.H241W194D105 opaque PC cover H20



Main

Range	Thalassa
Product name	Thalassa TBP
Device Application	Multi-purpose
Category	Industrial box
Height	9.49 in (241 mm)
Width	7.64 in (194 mm)
Depth	4.21 in (107 mm)
Internal height	8.86 in (225 mm)
Internal width	6.89 in (175 mm)
Internal depth	3.94 in (100 mm)
Enclosure mounting	Wall mounted
Device composition	1 body
	1 cover
	4 cover screw
Body type	One piece moulded
Type of front cover	High plain cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	polycarbonate	
Color	Gray RAL 7035)	
Standards	UL 508 A IEC 62208	
Product Certifications	TÜV UL	
Electrical Insulation Class	Class II	
Mounting location	Outdoor	
Net Weight	1.76 lb(US) (0.8 kg)	

Environment

IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK08 IEC 62262
Fire resistance	1760 °F (960 °C)
Ambient Air Temperature for Storage	5140 °F (-1560 °C)
Operating temperature	-13176 °F (-2580 °C)

Ordering and shipping details

80033-ENCLOSURE SYSTEMS POLYESTER	
ES1	
3606480165702	
1	
28.22 oz (800.0 g)	
No	
HU	
	ES1 3606480165702 1 28.22 oz (800.0 g) No

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	4.88 in (12.4 cm)	
Package 1 width	7.95 in (20.2 cm)	
Package 1 Length	10.08 in (25.6 cm)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	9	
Package 2 Weight	17.55 lb(US) (7.962 kg)	
Package 2 Height	15.75 in (40 cm)	
Package 2 width	15.75 in (40 cm)	
Package 2 Length	23.39 in (59.4 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

· · · · · · · · · · · · · · · · · ·		
Warranty	18 months	