



## Sierra Wireless® WP Series Embedded Modules

#### **ULTRA-LOW POWER DOMAIN**

Ideal for remote solar or batterypowered applications, the WP Series integrated power management feature can reduce power consumption by 200x compared to previous modules, enabling new usecases for cellular. For example:

- Devices that only need to transmit data once a day can now run on a single battery for up to 3 years\*
- Devices that only need to transmit data once a week can now run on a single battery for 10 years\*

\*based on sending 100kb of data, powered by a standard consumer-grade battery, operating on a 2G network.



23mm

# Expect more, do more with the next-gen WP

Sierra Wireless® AirPrime® WP Series provides an integrated device-to-cloud architecture enabling IoT developers to build a Linux-based product on a single module and seamlessly send valuable user and product data to the cloud. Offering an application processor running the open source Legato® platform, GNSS receiver, and cellular modem with an ultra-low power domain, WP modules reduce system complexity and get you to market faster.

#### SIMPLIFY SYSTEM DEVELOPMENT WITH A DEVICE-TO-CLOUD ARCHITECTURE

- All the key hardware components of your connected product in a compact form factor to save board space and reduce total BOM (bill of materials)
- Integrated Legato platform that maintains your Linux distribution and includes an application framework, development tools, and community support
- Integrated AirVantage® cloud services make it easy to access product and user data into your backend enterprise applications.

## **FUTURE-PROOF YOUR PRODUCT DESIGNS**

- CF3® (common flexible form factor) module design provides worldwide coverage on 2G, 3G, 4G, and LPWA networks, is compatible with HL Series of modules, and capable of supporting new wireless technologies
- The professionally maintained open source Legato platform for IoT enables you to reuse software components and applications in future designs with no vendor lock-in
- AirVantage cloud services with big data storage grows with your deployments and can power future revenue-generating services as your business evolves

### KEEP YOUR PRODUCTS DEPLOYED FOR YEARS IN THE FIELD

- New ultra-low power domain can reduce power consumption by 200x opening new use-cases for cellular where 100% connectivity to the network is not required
- Application sandbox within the Legato platform hosts your proprietary software and provides a secure place for 3rd party applications to enable future services for your customers
- Unlimited FOTA (firmware over-the-air) powered by AirVantage maintains optimized connectivity as networks evolve and keeps your data transmission protected as new security threats arise

Target Region	WP7502	WP7504	WP7504-1	WP8548
	EMEA	Americas	Americas	Global
4G LTE	LIVILA	Americas	Americas	diobai
Category	Cat-3	Cat-3	Cat-3	
Frequency Bands	B1, B3, B7, B8, B20	B2, B4, B5, B12, B17, B25, B26	B2, B4, B5, B12, B17, B25, B26	
3G	- 17 - 27 - 21 - 22	,,,,,	,,,,,	
Technology supported	HSPA+, UMTS	HSPA+, UMTS	HSPA+, UMTS	HSPA+, UMTS
Frequency Bands	B1, B8	B2, B4, B5	B2, B4, B5	B1, B2, B5, B6, B8, B19
Technology supported	51,56	EVDO	52, 54, 55	51, 52, 53, 50, 50, 513
Frequency Bands		BC0, BC1, BC10		
2G		260, 861, 8610		
Technology supported	EDGE, GSM, GPRS	CDMA		EDGE, GSM, GPRS
Frequency Bands	900, 1800	BCO, BC1, BC10		850, 900, 1800, 1900
DATA SPEED	300, 1000	DC0, DC 1, DC 10		050, 500, 1000, 1500
Peak Download Rate	100 Mbps	100 Mbps	100 Mbps	42 Mbps
Peak Upload Rate	50 Mbps	50 Mbps	50 Mbps	5.76 Mbps
LOCATION SERVICES	30 Wildy3	30 Maps	30 Mibp3	3.70 Миррэ
Satellite Systems (Optional)	GPS, Galileo, Glonass	GPS, Galileo, Glonass	GPS, Galileo, Glonass	GPS, Galileo, Glonass
CORES	dr J, dalileo, dioliass	dr J, dailleo, diollass	dro, dalileo, dioliass	dro, dallieo, dioriass
Application Core	ARM® Cortex™- A5 (550MHz)	ARM® Cortex™- A5 (550MHz)	ARM® Cortex™- A5 (550MHz)	ARM® Cortex™- A5 (550MHz)
Application Core Telecom Core	Dual QDSP6 (600MHz)	Dual QDSP6 (600MHz)	Dual QDSP6 (600MHz)	Dual QDSP6 (600MHz)
	טעמו עטארס (סטטואורז)	Dual QD5P6 (600IVIH2)	טעמו עטאס (סטטואודע)	Dual QD5P6 (600lVIRZ)
EMBEDDED SOFTWARE  Pre-certified Firmware	✓	✓	✓	✓
APPLICATION FRAMEWORK	•	•	•	<b>v</b>
	1	1	1	l
Embedded Platform	Legato® open source	Legato® open source	Legato® open source	Legato® open source
Linux Distribution	Yocto, Long-term supported Linux Kernel (LTSI)	Yocto, Long-term supported Linux Kernel (LTSI)	Yocto, Long-term supported Linux Kernel (LTSI)	Yocto, Long-term supported Line Kernel (LTSI)
AUDIO CODECS	remer(ers)	Terrier (Er 51)	Tierrier (Er 51)	Tierrer (E131)
Digital audio	✓	✓	✓	✓
PCM/12S	<b>√</b>	✓	✓	✓
Codec: HR, FR, EFR, AMR	✓	✓	✓	✓
Echo cancellation & noise reduction	✓	✓	✓	✓
DTMF	<i>,</i> ✓	<i>,</i> ✓	<i>,</i> ✓	<i>,</i> ✓
USB DRIVERS				
Windows® 7 and 8	✓	✓	✓	✓
Linux Driver	✓	✓	✓	✓
INTERFACES				
UART	2	2	2	2
USB	1	1	1	1
12C	1	1	1	1
ADC	4	4	4	4
GPIO	20	20	20	20
Tx ON Indicator	1	1	1	1
SIM Interface 1.8V/3V	2	2	2	2
HARDWARE				
CF3™ Form Factor (LGA)	✓	✓	✓	✓
Snap-in socket option	<i>√</i>	<i>·</i>	·	<i>-</i>
Dimensions	22x23x4.4mm	22x23x4.4mm	22x23x4.4mm	22x23x4.4mm
Antenna: Diversity	✓	✓	∠ZXZ3X4.4IIIII	ZZAZJAS-SIIIII
<del>-</del>	<i>·</i>	<i>·</i>	<i>·</i>	
Antenna: MIMO TEMPERATURE RANGE	•	•	•	
Industrial Grade	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C
APPROVALS	+∪ C.U.TU3 C	40 C (U TO) C	40 C (U TO) C	40 C to 700 C
	CE, GCF	מדרמת ברר כרב יר	מדרמת ברר כרב יר	CE, FCC, PTCRB, GCF, IC, JRF/
Regulatory	CL, UCF	PTCRB, FCC, GCF, IC	PTCRB, FCC, GCF, IC	JPA, NCC
Carrier		AT&T, Sprint, T-Mobile	AT&T, Sprint, T-Mobile	AT&T
CLOUD SERVICES		✓	✓	✓
	✓	<b>v</b>		
Free Unlimited FOTA upgrades	✓ ✓	<b>√</b>	<i>·</i>	<i>·</i>

# Sierra Wireless WP SERIES EMBEDDED MODULES

	WD7601	WD7601-4	WD7603	WD7602-4
	WP7601	WP7601-1	WP7603	WP7603-1
Target Region	Americas	Americas	Americas	Americas
4G LTE				
Category	Cat-4	Cat-1	Cat-4	Cat-1
Frequency Bands 3G	B4, B13	B4, B13	B2, B4, B5, B12	B2, B4, B5, B12
Technology supported			HSPA+, UMTS	HSPA+, UMTS
Frequency Bands			B2, B4, B5	B2, B4, B5
DATA SPEED				
Peak Download Rate	150 Mbps	10 Mbps	150 Mbps	10 Mbps
Peak Upload Rate	50 Mbps	5 Mbps	50 Mbps	50 Mbps
LOCATION SERVICES	l			
Satellite Systems (Optional)	GPS, Galileo, Glonass, Beidou	GPS, Galileo, Glonass, Beidou	GPS, Galileo, Glonass, Beidou	GPS, Galileo, Glonass, Beidou
CORES				
Application Core	ARM® Cortex™- A7 (1.3GHz)	ARM® Cortex™- A7 (1.3GHz)	ARM® Cortex™- A7 (1.3GHz)	ARM® Cortex™- A7 (1.3GHz)
Telecom Core	Dual QDSP6 (600MHz)	Dual QDSP6 (600MHz)	Dual QDSP6 (600MHz)	Dual QDSP6 (600MHz)
EMBEDDED SOFTWARE	<b>I</b> ✓	✓	✓	✓
Secure Boot	<b>→</b>	✓	✓ ✓	✓ ✓
Pre-certified Firmware APPLICATION FRAMEWORK	<u>*</u>	•	<b>v</b>	<b>v</b>
Embedded Platform	Legato® open source	Legato® open source	Legato® open source	Legato® open source
Linux Distribution		Yocto, Long-term supported Linux		
AUDIO CODECS	Kernel (LTSI)	Kernel (LTSI)	Kernel (LTSI)	Kernel (LTSI)
Digital audio	<b>-</b>	✓	✓	✓
PCM/12S	<b>-</b>	✓	✓	✓
Codec: HR, FR, EFR, AMR	✓	✓	✓	✓
Echo cancellation & noise reduction	✓	✓	✓	✓
DTMF	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>
USB DRIVERS				
Windows® 7 and 8	✓	✓	✓	✓
Linux	✓	✓	✓	✓
INTERFACES				
UART	2	2	2	2
USB	1	1	1	1
12C	1	1	1	1
ADC	4	4	4	4
GPI0	18	18	18	18
Tx ON Indicator	1	1	1	1
SIM Interface 1.8V/3V	1	1	1	1
HARDWARE				
CF3™ Form Factor (LGA)	<b>√</b>	✓	✓	✓
Snap-in socket option	✓	✓	✓	✓
Dimensions	22x23x2.5mm ✓	22x23x2.5mm	22x23x2.5mm	22x23x2.5mm ✓
Antenna: Diversity	<b>→</b>	✓ ✓	✓ ✓	✓ ✓
Antenna: MIMO TEMPERATURE RANGE	<b>v</b>	<b>V</b>	<b>v</b>	<b>v</b>
Industrial Grade	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C
APPROVALS	-40 C (0 +85 C	-40 (10+85 (	-40 C t0 +85 C	-40 C t0 +85 C
Regulatory	FCC, IC	FCC, IC	FCC, IC	FCC, IC
Carrier	Verizon	Verizon	AT&T, T-Mobile	AT&T, T-Mobile
APPROVALS	VC.12011	VC2011	a., i Mobile	ai, i modiic
Optional Ready-to-Connect	<b>√</b>	✓	✓	✓
Sierra Wireless embedded SIM CLOUD SERVICES				
Free Unlimited FOTA upgrades	<b>I</b> ✓	✓	✓	✓
Device Management option	<i>-</i>	<i>√</i>	<i>,</i>	<i>,</i> ✓
Application Enablement option	· · · · · · · · · · · · · · · · · · ·	<i>→</i>	<i>,</i>	<i>,</i> ✓
Connectivity Management option	<b>√</b>	<b>√</b>	<b>√</b>	✓
connectivity inanagement option	•	•	•	•

Note: VoLTE supported as a firmware upgrade

	WP7607	WP7607-1	WP7608	WP7608-1	WP7609
Target Region	EMEA	EMEA	India/China	India/China	Australia
4G LTE	EMER	LINEA	mala/crima	maia cima	rascana
Category	Cat-4	Cat-1	Cat-4	Cat-1	Cat-4
Frequency Bands	B1, B3, B7, B8, B20, B28	B1, B3, B7, B8, B20, B28		B1, B3, B5, B8, B40, B41*	B1, B3, B5, B7, B8, B28
3G					
Technology supported	HSPA+, UMTS				
Frequency Bands	B1, B8	B1, B8	B1, B8	B1, B8	B1, B5, B8
2G	B 1, 50	51,50	51,50	51,50	51, 53, 50
Technology supported	EDGE, GSM, GPRS	EDGE, GSM, GPRS	EDGE, GSM, GPRS	EDGE, GSM, GPRS	
Frequency Bands	900, 1800	900, 1800	900, 1800	900, 1800	
DATA SPEED			,	,	
Peak Download Rate	150 Mbps	10 Mbps	150 Mbps	10 Mbps	150 Mbps
Peak Upload Rate	50 Mbps	5 Mbps	50 Mbps	5 Mbps	50 Mbps
LOCATION SERVICES			·	·	·
Satellite Systems (Optional)	GPS, Galileo, Glonass,				
	Beidou	Beidou	Beidou	Beidou	Beidou
CORES	ARM® Cortex™- A7				
Application Core	(1.3GHz)	(1.3GHz)	(1.3GHz)	(1.3GHz)	(1.3GHz)
Telecom Core	Dual QDSP6 (600MHz)				
EMBEDDED SOFTWARE					
Secure Boot	✓	<b>√</b>	<b>√</b>	✓	<b>✓</b>
Pre-certified Firmware	<b>✓</b>	✓	✓	✓	<b>✓</b>
APPLICATION FRAMEWORK					
Embedded Platform	Legato® open source				
Linux Distribution	Yocto, Long-term supported Linux Kernel (LTSI)				
AUDIO CODECS		· · ·			· · ·
Digital audio	✓	✓	✓	✓	✓
PCM/12S	✓	✓	✓	✓	✓
Codec: HR, FR, EFR, AMR	✓	✓	✓	✓	✓
Echo cancellation & noise reduction	✓	✓	✓	✓	✓
DTMF	✓	✓	✓	✓	✓
USB DRIVERS					
Windows® 7 and 8	_ <	✓	✓	✓	✓
Linux	✓	✓	✓	✓	✓
INTERFACES					
UART	2	2	2	2	2
USB	1	1	1	1	1
12C	1	1	1	1	1
ADC	4	4	4	4	4
GPIO	18	18	18	18	18
Tx ON Indicator	1	1	1	1	1
SIM Interface 1.8V/3V	1	1	1	1	1
HARDWARE					
CF3™ Form Factor (LGA)	<b>✓</b>	<b>√</b>	✓	<b>✓</b>	<b>√</b>
Snap-in socket option	<b>√</b>	<b>√</b>	<b>✓</b>	<b>√</b>	<b>✓</b>
Dimensions	22x23x2.5mm	22x23x2.5mm	22x23x2.5mm	22x23x2.5mm	22x23x2.5mm
Antenna: Diversity	<b>√</b>	✓	✓	<b>✓</b>	<b>✓</b>
Antenna: MIMO	_	✓	✓	✓	✓
TEMPERATURE RANGE					
Industrial Grade	-40°C to +85°C	-40°C to +85°C	-40°C/+85°C	-40°C/+85°C	-40°C to +85°C
APPROVALS					
Regulatory	GCF	GCF	CCC, GCF	CCC, GCF	GCF, RCM
Carrier	_				Telstra, Optus, Vodafone
CONNECTIVITY					
Optional Ready-to-Connect	✓	✓	✓	✓	✓
Sierra Wireless embedded SIM	_				
CLOUD SERVICES  Free Unlimited FOTA ungrades		✓		<b>√</b>	,
Free Unlimited FOTA upgrades	<b>√</b>		<b>√</b>		<b>√</b>
Device Management option	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>
Application Enablement option	✓	✓	✓	<b>√</b>	<b>✓</b>
Connectivity Management option	✓	✓	✓	✓	✓

<sup>\*</sup>B41 supported frequency range: (2535–2655 MHz) Note: VoLTE supported as a firmware upgrade

## Sierra Wireless WP SERIES EMBEDDED MODULES

	WD7700			
	WP7700	WP7702		
Target Region	Global	Global		
4G LTE	C	5 / 114 / 1154		
Category	Cat-M1/NB1	Cat-M1/NB1		
Frequency Bands	B1, B2, B3, B4, B5, B8, B12, B13, B17, B18, B19, B20, B26, B28	B1, B2, B3, B4, B5, B8, B12, B13, B17, B18, B19, B20, B26, B28		
2G		cell cone		
Technology supported		GSM, GPRS		
Frequency Bands		900, 1800		
DATA SPEED				
Peak Download Rate	Cat-M1: 300kbps   Cat-NB1: 27kbps	Cat-M1: 300kbps   Cat-NB1: 27kbps		
Peak Upload Rate	Cat-M1: 375kbps   Cat-NB1: 65kbps	Cat-M1: 375kbps   Cat-NB1: 65kbps		
LOCATION SERVICES				
Satellite Systems (Optional)	GPS, Galileo, Glonass, Beidou	GPS, Galileo, Glonass, Beidou		
CORES	ARM® Cortex™- A7 (1.3GHz)	ARM® Cortex™- A7 (1.3GHz)		
Application Core				
Telecom Core	Dual QDSP6 (600MHz)	Dual QDSP6 (600MHz)		
EMBEDDED SOFTWARE				
Secure Boot	<b>√</b>	<b>√</b>		
Pre-certified Firmware	✓	✓		
APPLICATION FRAMEWORK				
Embedded Platform	Legato® open source	Legato® open source		
Linux Distribution	Yocto, Long-term supported Linux Kernel (LTSI)	Yocto, Long-term supported Linux Kernel (LTSI)		
AUDIO CODECS				
Digital audio	✓	✓		
PCM/12S	✓	✓		
Codec: HR, FR, EFR, AMR	✓	✓		
Echo cancellation & noise reduction	✓	✓		
DTMF	✓	✓		
USB DRIVERS				
Windows® 7 and 8	_ <i>✓</i>	✓		
Linux	✓	✓		
INTERFACES				
UART	2	2		
USB	1	1		
12C	1	1		
ADC	4	4		
GPIO	18	18		
Tx ON Indicator	1	1		
SIM Interface 1.8V/3V	1	1		
SPI	1	1		
HARDWARE				
CF3™ Form Factor (LGA)	✓	✓		
Snap-in socket option	<b>√</b>	✓		
Dimensions	22x23x2.5mm	22x23x2.5mm		
Antenna: Diversity	√	✓		
Antenna: MIMO	✓	✓		
TEMPERATURE RANGE				
Industrial Grade	-40°C to +85°C	-40°C to +85°C		
APPROVALS				
Regulatory	PTCRB, FCC, GCF, IC	PTCRB, FCC, GCF, IC		
Carrier	AT&T, Verizon, NTT, Telstra, KT, SKT	AT&T, Verizon, NTT, Telstra, KT, SKT		
CONNECTIVITY	a., venzon, wit, reistid, M, SM	, , a, venzon, with tesail, ith six		
Optional Ready-to-Connect				
Sierra Wireless embedded SIM	$\checkmark$	✓		
CLOUD SERVICES				
Free Unlimited FOTA upgrades	✓	✓		
Device Management option	✓	✓		
Application Enablement option	✓	· ·		
Connectivity Management option	<i>✓</i>	· ·		
connectivity management option	•	•		

#### About Sierra Wireless

Note: VoLTE supported as a firmware upgrade

Sierra Wireless is building the Internet of Things with intelligent wireless solutions that empower organizations to innovate in the connected world. We offer the industry's most comprehensive portfolio of 2G, 3G, 4G, and LPWA embedded modules and gateways, seamlessly integrated with our secure cloud and connectivity services. OEMs and enterprises worldwide trust our innovative solutions to get their connected products and services to market faster. For more information, visit <a href="https://www.sierrawireless.com">www.sierrawireless.com</a>.

