NSYTBS342912T

ABS box IP66 IK07 RAL7035 Int.H325W275D120 Ext.H341W291D128 Transp.cover H20





Main

Range	Thalassa
Product name	Thalassa TBS
Device Application	Multi-purpose
Category	Industrial box
Height	13.43 in (341 mm)
Width	11.46 in (291 mm)
Depth	5.04 in (128 mm)
Internal height	12.80 in (325 mm)
Internal width	10.83 in (275 mm)
Internal depth	4.72 in (120 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 cover 4 cover screw
Body type	One piece moulded
Type of front cover	Low transparent cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	ABS (acrylonitrile butadiene-styrene)	
Color	Gray RAL 7035)	
	Transparent	
Standards	IEC 62208	
Product Certifications	TÜV	
Electrical Insulation Class	Class II	
IP degree of protection	IP66 conforming to NEMA 4.4X	
IK degree of protection	IK07 IEC 62262	
Glow wire resistance	1202 °F (650 °C) IEC 60695-2-11	
Ambient Air Temperature for Storage	5104 °F (-1540 °C)	
Operating temperature	-13140 °F (-2560 °C)	
Net Weight	3.19 lb(US) (1.448 kg)	

Ordering and shipping details

Category	80033-ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	3606480165566
Nbr. of units in pkg.	1
Package weight(Lbs)	3.22 lb(US) (1.46 kg)
Returnability	No
Country of origin	HU
- Country or origin	110

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.51 in (14.0 cm)
Package 1 width	11.81 in (30.0 cm)
Package 1 Length	13.98 in (35.5 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	4
Package 2 Weight	15.65 lb(US) (7.1 kg)
Package 2 Height	15.75 in (40.0 cm)
Package 2 width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Weight	194.01 lb(US) (88.0 kg)
Package 3 Height	53.54 in (136.0 cm)
Package 3 width	31.50 in (80.0 cm)
Package 3 Length	47.24 in (120.0 cm)

Offer Sustainability

Green Premium product
☐ REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
Yes
₫Yes
China RoHS Declaration
Product Environmental Profile

Contractual warranty

 •	
10 months	
18 MONTINS	