

**H11B1X, H11B2X, H11B3X
H11B1, H11B2, H11B3**



ISOCOM
COMPONENTS



OPTICALLY COUPLED ISOLATOR PHOTODARLINGTON OUTPUT

APPROVALS

- UL recognised, File No. E91231
- 'X' SPECIFICATION APPROVALS
 - VDE 0884 in 2 available lead form :
 - STD
 - G form
 - VDE 0884 in SMD approval pending
 - SETI approved, reg. no.151786-18

DESCRIPTION



The H11B_ series of optically coupled isolators consist of an infrared light emitting diode and NPN silicon photodarlington in a space efficient dual in line plastic package.

FEATURES

- Options :-
 - 10mm lead spread - add G after part no.
 - Surface mount - add SM after part no.
 - Tape&reel - add SMT&R after part no.
- High Current Transfer Ratio
- High Isolation Voltage ($5.3\text{ kV}_{\text{RMS}}, 7.5\text{ kV}_{\text{PK}}$)
- All electrical parameters 100% tested
- Custom electrical selections available

APPLICATIONS

- Computer terminals
- Industrial systems controllers
- Measuring instruments
- Signal transmission between systems of different potentials and impedances



ABSOLUTE MAXIMUM RATINGS (25°C unless otherwise specified)

Storage Temperature _____ -55°C to $+150^{\circ}\text{C}$
Operating Temperature _____ -55°C to $+100^{\circ}\text{C}$
Lead Soldering Temperature
(1/16 inch (1.6mm) from case for 10 secs) 260°C

INPUT DIODE

Forward Current _____ 80mA
Reverse Voltage _____ 5V
Power Dissipation _____ 105mW

OUTPUT TRANSISTOR

Collector-emitter Voltage BV_{CEO} _____ 30V
Collector-base Voltage BV_{CBO} _____ 50V
Emitter-collector Voltage BV_{ECO} _____ 5V
Power Dissipation _____ 150mW

POWER DISSIPATION

Total Power Dissipation _____ 250mW
(derate linearly 3.3mW/ $^{\circ}\text{C}$ above 25°C)

ISOCOM COMPONENTS LTD
Unit 25B, Park View Road West,
Park View Industrial Estate, Brenda Road
Hartlepool, Cleveland, TS25 1YD
Tel: (01429) 863609 Fax :(01429) 863581


ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise noted)






PARAMETER		MIN	TYP	MAX	UNITS	TEST CONDITION
Input	Forward Voltage (V_F) Reverse Voltage (V_R) Reverse Current (I_R)	3	1.2	1.5 10	V V μA	$I_F = 10\text{mA}$ $I_R = 10\mu\text{A}$ $V_R = 3\text{V}$
Output	Collector-emitter Breakdown (BV_{CEO}) Collector-base Breakdown (BV_{CBO}) Emitter-collector Breakdown (BV_{ECO}) H_{FE} Collector-emitter Dark Current (I_{CEO})	30 30 5		16K 100	V V V nA	$I_c = 1\text{mA}$ (note 2) $I_c = 100\mu\text{A}$ $I_E = 100\mu\text{A}$ $V_{CE} = 5\text{V}, I_c = 5\text{mA}$ $V_{CE} = 10\text{V}$
Coupled	Current Transfer Ratio (CTR)(Note 2) H11B1 H11B2 H11B3 Collector-emitter Saturation Voltage $V_{CE(SAT)}$ Input to Output Isolation Voltage V_{ISO} Input-output Isolation Resistance R_{ISO} Output Turn on Time t_{on} Output Turn off Time t_{off}	500 200 100 5300 7500 5×10^{10}		1.0	% % % V V_{RMS} V_{PK} Ω	1mA I_F , 5V V_{CE} 1mA I_F , 5V V_{CE} 1mA I_F , 5V V_{CE} 1mA I_F , 1mA I_C (note 1) (note 1) $V_{IO} = 500\text{V}$ (note 1) $V_{CC} = 10\text{V}, I_C = 10\text{mA}$, $R_L = 100\Omega$, fig.1

Note 1 Measured with input leads shorted together and output leads shorted together.

Note 2 Special Selections are available on request. Please consult the factory.

FIGURE 1



Collector Power Dissipation vs. Ambient Temperature**Current Transfer Ratio vs. Forward Current****Forward Current vs. Ambient Temperature****Collector Current vs. Collector-emitter Voltage****Collector-emitter Saturation Voltage vs. Ambient Temperature****Normalised Current Transfer Ratio vs. Ambient Temperature**