



Important notice

Dear Customer,

On 7 February 2017 the former NXP Standard Product business became a new company with the tradename **Nexperia**. Nexperia is an industry leading supplier of Discrete, Logic and PowerMOS semiconductors with its focus on the automotive, industrial, computing, consumer and wearable application markets

In data sheets and application notes which still contain NXP or Philips Semiconductors references, use the references to Nexperia, as shown below.

Instead of <http://www.nxp.com>, <http://www.philips.com>/ or <http://www.semiconductors.philips.com>/, use <http://www.nexperia.com>

Instead of sales.addresses@www.nxp.com or sales.addresses@www.semiconductors.philips.com, use salesaddresses@nexperia.com (email)

Replace the copyright notice at the bottom of each page or elsewhere in the document, depending on the version, as shown below:

- © NXP N.V. (year). All rights reserved or © Koninklijke Philips Electronics N.V. (year). All rights reserved


Should be replaced with:

- © **Nexperia B.V. (year). All rights reserved.**

If you have any questions related to the data sheet, please contact our nearest sales office via e-mail or telephone (details via salesaddresses@nexperia.com). Thank you for your cooperation and understanding,

Kind regards,

Team Nexperia



PHK12NQ03LT

N-channel TrenchMOS™ logic level FET

Rev. 02 — 02 March 2004

Product data

1. Product profile

1.1 Description

N-channel enhancement mode field-effect transistor in a plastic package using TrenchMOS™ technology.

1.2 Features

- Low on-state resistance
- Fast switching.

1.3 Applications



- DC-to-DC converters
- Portable equipment applications.

1.4 Quick reference data

- $V_{DS} \leq 30$ V
- $I_D \leq 11.8$ A
- $P_{tot} \leq 2.5$ W
- $R_{DSon} \leq 14$ mΩ

2. Pinning information

Table 1: Pinning - SOT96-1 (SO8), simplified outline and symbol

| Pin | Description | Simplified outline | Symbol |
|---------|-------------|--|---|
| 1,2,3 | source (s) | | |
| 4 | gate (g) | | |
| 5,6,7,8 | drain (d) |  Top view MBK187 |  MBB076 |

3. Ordering information

Table 2: Ordering information

| Type number | Package | Description | Version |
|-------------|---------|--|---------|
| | Name | | |
| PHK12NQ03LT | SO8 | Plastic small outline package; 8 leads | SOT96 |




PHILIPS

4. Limiting values

Table 3: Limiting values


In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol | Parameter | Conditions | Min | Max | Unit |
|-----------------------------|--|--|-----|----------|--------------------|
| V_{DS} | drain-source voltage (DC) | $25^{\circ}\text{C} \leq T_j \leq 150^{\circ}\text{C}$ | - | 30 | V |
| V_{GS} | gate-source voltage | | - | ± 20 | V |
| I_D | drain current | $T_{\text{amb}} = 25^{\circ}\text{C}$; pulsed; $t_p \leq 10\text{ s}$; Figure 2 and 3 | - | 11.8 | A |
| I_{DM} | peak drain current | $T_{\text{amb}} = 25^{\circ}\text{C}$; pulsed; $t_p \leq 10\text{ }\mu\text{s}$; Figure 3 | - | 35.3 | A |
| P_{tot} | total power dissipation | $T_{\text{amb}} = 25^{\circ}\text{C}$; pulsed; $t_p \leq 10\text{ s}$; Figure 1 | - | 2.5 | W |
| T_{stg} | storage temperature | | -55 | +150 | $^{\circ}\text{C}$ |
| T_j | junction temperature | | -55 | +150 | $^{\circ}\text{C}$ |
| Source-drain diode | | | | | |
| I_S | source (diode forward) current | $T_{\text{amb}} = 25^{\circ}\text{C}$; pulsed; $t_p \leq 10\text{ s}$ | - | 11.8 | A |
| Avalanche ruggedness | | | | | |
| $E_{DS(\text{AL})S}$ | non-repetitive drain-source avalanche energy | unclamped inductive load; $I_D = 7.7\text{ A}$; $t_p = 2.35\text{ ms}$; $V_{DD} \leq 30\text{ V}$; $V_{GS} = 10\text{ V}$; starting $T_j = 25^{\circ}\text{C}$ | - | 440 | mJ |




$$P_{der} = \frac{P_{tot}}{P_{tot}(25^{\circ}\text{C})} \times 100\%$$

Fig 1. Normalized total power dissipation as a function of ambient temperature.



$$I_{der} = \frac{I_D}{I_{D(25^{\circ}\text{C})}} \times 100\%$$

Fig 2. Normalized continuous drain current as a function of ambient temperature.



T_{amb} = 25 °C; I_{DM} is single pulse

Fig 3. Safe operating area; continuous and peak drain currents as a function of drain-source voltage.

5. Thermal characteristics

Table 4: Thermal characteristics

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|---------------|---|--|-----|-----|-----|------|
| $R_{th(j-a)}$ | thermal resistance from junction to ambient | mounted on a printed-circuit board; minimum footprint; $t_p \leq 10$ s; Figure 4 | - | - | 50 | K/W |

5.1 Transient thermal impedance








Fig 4. Transient thermal impedance from junction to ambient as a function of pulse duration.

6. Characteristics


Table 5: Characteristics $T_j = 25^\circ\text{C}$ unless otherwise specified.

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|-------------------------------------|--------------------------------------|---|-----|------|------|------------------|
| Static characteristics | | | | | | |
| $V_{(\text{BR})\text{DSS}}$ | drain-source breakdown voltage | $I_D = 250 \mu\text{A}; V_{GS} = 0 \text{ V}$ | 30 | - | - | V |
| $V_{GS(\text{th})}$ | gate-source threshold voltage | $I_D = 250 \mu\text{A}; V_{DS} = V_{GS}; T_j = 25^\circ\text{C}$; Figure 9 | 1 | - | 2 | V |
| I_{DSS} | drain-source leakage current | $V_{DS} = 24 \text{ V}; V_{GS} = 0 \text{ V}$ | | | | |
| | | $T_j = 25^\circ\text{C}$ | - | - | 1 | μA |
| | | $T_j = 100^\circ\text{C}$ | - | - | 5 | μA |
| I_{GSS} | gate-source leakage current | $V_{GS} = \pm 20 \text{ V}; V_{DS} = 0 \text{ V}$ | - | | 100 | nA |
| $R_{DS\text{on}}$ | drain-source on-state resistance | $V_{GS} = 4.5 \text{ V}; I_D = 10 \text{ A}$; Figure 8 | - | 11 | 14 | $\text{m}\Omega$ |
| | | $V_{GS} = 10 \text{ V}; I_D = 12 \text{ A}$; Figure 8 | - | 8.9 | 10.5 | $\text{m}\Omega$ |
| Dynamic characteristics | | | | | | |
| g_{fs} | forward transconductance | $V_{DS} = 15 \text{ V}; I_D = 10 \text{ A}$ | - | 34 | - | S |
| $Q_{g(\text{tot})}$ | total gate charge | $I_D = 15 \text{ A}; V_{DD} = 16 \text{ V}; V_{GS} = 5 \text{ V}$; Figure 13 | - | 17.6 | - | nC |
| Q_{gs} | gate-source charge | | - | 4 | - | nC |
| Q_{gd} | gate-drain (Miller) charge | | - | 4.4 | - | nC |
| C_{iss} | input capacitance | $V_{GS} = 0 \text{ V}; V_{DS} = 16 \text{ V}; f = 1 \text{ MHz}$; Figure 11 | - | 1335 | - | pF |
| C_{oss} | output capacitance | | - | 391 | - | pF |
| C_{rss} | reverse transfer capacitance | | - | 190 | - | pF |
| $t_{d(on)}$ | turn-on delay time | $V_{DD} = 16 \text{ V}; R_D = 10 \Omega; V_{GS} = 10 \text{ V}$ | - | 10.6 | - | ns |
| t_r | rise time | | - | 11.7 | - | ns |
| $t_{d(off)}$ | turn-off delay time | | - | 37 | - | ns |
| t_f | fall time | | - | 19 | - | ns |
| Source-drain (reverse) diode | | | | | | |
| V_{SD} | source-drain (diode forward) voltage | $I_S = 1 \text{ A}; V_{GS} = 0 \text{ V}$; Figure 12 | - | 0.7 | 1.0 | V |
| t_{rr} | reverse recovery time | $I_S = 2.3 \text{ A}; dI_S/dt = -100 \text{ A}/\mu\text{s}; V_{GS} = 0 \text{ V}$ | - | 70 | - | ns |

 $T_j = 25^\circ\text{C}$ **Fig 5.** Output characteristics: drain current as a function of drain-source voltage; typical values. $T_j = 25^\circ\text{C}$ and 150°C ; $V_{DS} > I_D \times R_{DSon}$ **Fig 6.** Transfer characteristics: drain current as a function of gate-source voltage; typical values. $T_j = 25^\circ\text{C}$ **Fig 7.** Drain-source on-state resistance as a function of drain current; typical values.


$$a = \frac{R_{DSon}}{R_{DSon}(25^\circ\text{C})}$$

Fig 8. Normalized drain source on-state resistance factor as a function of junction temperature.




$I_D = 250 \mu A$; $V_{DS} = V_{GS}$

Fig 9. Gate-source threshold voltage as a function of junction temperature.




$T_j = 25 ^{\circ}C$; $V_{DS} = 5 V$

Fig 10. Sub-threshold drain current as a function of gate-source voltage.




$V_{GS} = 0 V$; $f = 1 MHz$

Fig 11. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values.



$T_j = 25 ^{\circ}C$ and $150 ^{\circ}C$; $V_{GS} = 0 V$

Fig 12. Source (diode forward) current as a function of source-drain (diode forward) voltage; typical values.




$I_D = 15$ A; $V_{DD} = 16$ V

Fig 13. Gate-source voltage as a function of gate charge; typical values.

7. Package outline

SO8: plastic small outline package; 8 leads; body width 3.9 mm

SOT96-1



DIMENSIONS (inch dimensions are derived from the original mm dimensions)

| UNIT | A max. | A ₁ | A ₂ | A ₃ | b _p | c | D ⁽¹⁾ | E ⁽²⁾ | e | H _E | L | L _p | Q | v | w | y | z ⁽¹⁾ | θ |
|--------|----------------|----------------|----------------|----------------|----------------|------------------|------------------|------------------|------|----------------|-------|----------------|----------------|------|------|-------|------------------|----------|
| mm | 1.75 0.10 | 0.25 1.25 | 1.45 1.25 | 0.25 | 0.49 0.36 | 0.25 0.19 | 5.0 4.8 | 4.0 3.8 | 1.27 | 6.2 5.8 | 1.05 | 1.0 0.4 | 0.7 0.6 | 0.25 | 0.25 | 0.1 | 0.7 0.3 | 8° 0° |
| inches | 0.069 0.004 | 0.010 0.049 | 0.057 0.049 | 0.01 | 0.019 0.014 | 0.0100 0.0075 | 0.20 0.19 | 0.16 0.15 | 0.05 | 0.244 0.228 | 0.041 | 0.039 0.016 | 0.028 0.024 | 0.01 | 0.01 | 0.004 | 0.028 0.012 | |

Notes

- Plastic or metal protrusions of 0.15 mm (0.006 inch) maximum per side are not included.
- Plastic or metal protrusions of 0.25 mm (0.01 inch) maximum per side are not included.

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|--------------------|------------|--------|-------|--|------------------------|----------------------|
| | IEC | JEDEC | JEITA | | | |
| SOT96-1 | 076E03 | MS-012 | | | | 99-12-27 03-02-18 |

Fig 14. SOT96-1 (SO8).

8. Revision history

Table 6: Revision history

| Rev | Date | CPCN | Description |
|-----|----------|------|---|
| 02 | 20040302 | - | Product data (9397 750 12955) Modifications <ul style="list-style-type: none">• Data sheet updated to latest presentation standards.• Section 1.4 "Quick reference data" correction to I_D value.• Section 4 "Limiting values" I_D, I_{DM}, P_{tot} and I_S conditions and values corrected.• Section 4 "Limiting values" Figure 1, 2 and 3 corrected.• Section 4 "Limiting values" $E_{DS(AL)S}$ added.• Section 5 "Thermal characteristics" typ and max values corrected.• Section 5 "Thermal characteristics" Figure 4 corrected.• Section 6 "Characteristics" Figure 13 corrected. |
| 01 | 20020322 | - | Product data (9397 750 09405) |

9. Data sheet status

| Level | Data sheet status ^[1] | Product status ^{[2][3]} | Definition |
|-------|----------------------------------|----------------------------------|--|
| I | Objective data | Development | This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice. |
| II | Preliminary data | Qualification | This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product. |
| III | Product data | Production | This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). |

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

10. Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

12. Trademarks

TrenchMOS — is a trademark of Koninklijke Philips Electronics N.V.

11. Disclaimers

Life support — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors

Contact information

For additional information, please visit <http://www.semiconductors.philips.com>.

For sales office addresses, send e-mail to: sales.addresses@www.semiconductors.philips.com.

Fax: +31 40 27 24825

9397 750 12955

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.

Contents

| | | |
|-----------|--------------------------------|-----------|
| 1 | Product profile | 1 |
| 1.1 | Description | 1 |
| 1.2 | Features | 1 |
| 1.3 | Applications | 1 |
| 1.4 | Quick reference data | 1 |
| 2 | Pinning information | 1 |
| 3 | Ordering information | 1 |
| 4 | Limiting values | 2 |
| 5 | Thermal characteristics | 4 |
| 5.1 | Transient thermal impedance | 4 |
| 6 | Characteristics | 5 |
| 7 | Package outline | 9 |
| 8 | Revision history | 10 |
| 9 | Data sheet status | 11 |
| 10 | Definitions | 11 |
| 11 | Disclaimers | 11 |
| 12 | Trademarks | 11 |

© Koninklijke Philips Electronics N.V. 2004.

Printed in The Netherlands

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Date of release: 02 March 2004

Document order number: 9397 750 12955



PHILIPS

Let's make things better.