Data Sheet

Coaxial PCB Connector 81_MMCX-50-0-1/111_O

Description

Straight PCB plug

Interface Standards SUHNER-MMCX





Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	6 GHz	
Mechanical Data		
Board mounting type	through holes	
Weight	0.0008 kg	
Environmental Data		
Operating temperature	-55 °C to 155 °C	
2011/65/EU (RoHS)	compliant	
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
Related Documents		
Outline drawing	DOU-00013167	
Catalogue drawing	DCA-00013169	
Mounting hole	DOU-00012639	
Ordering Information		
Single package	81_MMCX-50-0-1/111_OE	
Bulk 100 pcs package	81_MMCX-50-0-1/111_OH	
Remarks		

PCB connector without stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.