	ד <u>ס</u> ד	п	D	0	₽ ≯	>	
4							4
ယ				LAYOUT SHOWN AS EX	XAMPLE		3
	Keying Shown as example						
		r dimension					
	-Standard : Based on MIL-DTL-38999 Series III Dim	Nominal					
	-Shell Material: AluminiumØS-Shell Plating: Olive drab CadmiumZ-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	29.4 Max 31 Max M18x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
N	-Contact Plating : Gold over copper Alloy 0.8µm minimum		<b></b>	FR	Not Listed		2
	-Durability : 500 Mating cycles -Delivered without Souriau contacts		PN: 8D513W04PAL				
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 19-10-20	016 First Release			
	-Mass : 19.8 g ± 10%		ISS DATE			MOD N°	,
			Designed By:	Date:	CUSTOMER DRAWING	i	_
			TITLE	Alumin	ium Plug 8D series		
_	BASIC SERIES:     8D     5     -     13     W     04     P     A     L       SHELL TYPE     : Plug with RFI Shielding     -     13     W     04     P     A     L	Delivered W/O Contacts	SCALE NA	General linear Tolerances:	NPRDS / PROJECT 859		
	CONTACT TYPE : Standard Crimp Contact	ORIENTATION : A		· · ·	This document is the p SOURIAU	property of	- '
	SHELL SIZE : 13 CONTACT TYPE : PIN(500 Matings)		SOURIAU WWW.SOURIAU.COM it must not be reproduced or communicated without permiss				
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 13-04	FORMAT	SOURIAU		SHEET	_
			A3	8D513W(		1/2	
,	H G F	E	D	C	B A		

r	Ŧ	۵	н <b>г</b>	m		0
		Contact Layout				
4	×	$ \begin{array}{c}                                     $				
		D         (mm)         (mm)           +.000 (0.00)         +.150 (3.81)           +.146 (3.71)         +.035 (0.89)           +.000 (0.00)        083 (2.11)          146 (3.71)         +.035 (0.89)				
ω						
	1					
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommendat
S						Countr FR
						PN: 8D513V
					A 19-10-20	116 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
<u> </u>					SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D513W
	Н	G	F	E	D	C

	ω		A			
					4	
					3	
	on-conformit					
r of th	n does not co ne Parties or b n, technical no	oy a third part	у			
ntry R						
W04PAL						
		CUSTONAS		MOD N°		
CUSTOMER DRAWING						
inium Plug 8D series						
r	NPRDS / PROJECT					
859 This document is the property of						
.CO	M	SOURIAU it must not be reproduced or communicated without permission				
UC	DRG N°			SHEET		
	1PAL-C			2/2		
	В		А			