				EN	Mail Address:	Password: Forgot Me
	60	Manufact	urer of			
JE	36	ESD Sta	urer of atic Control Pro	ducts	Remember me	Go Regist
Home	Promotions	Products	Technical	Service	s Sales Reps Distributor	
On-Line C	atalog				SEARCH	CATALOG HOME
Banana	Plug Adapte	rs	Feat	ures and	d Benefits:	
	09750 09750 0000	09780 09782			ters designed to d banana plug America	accept
	scription gator Clip	ana Jack 10-3	32 x 1/2" threaded	d hole acce	epts standard bana	ana plug or 10-
09700 Alli	ge Clip with Bar					· -
09750 Lar	ge Clip with Bar thread g Terminal Bana					

Per ESD 6.1 "Provisions may be made to include a resistor where it may be required for a purpose other than ESD."

ESD Handbook TR 20.20 paragraph 5.1.3 Basic Grounding Requirements "The first step in ensuring that everything in an EPA is at the same electrical potential is to ground all conductive components of the work area (worksurfaces, people, equipment, etc.) to the same electrical ground point. This point is called the common point ground. The next step in completing the ground circuit is to connect the common point ground to the equipment ground (third wire, green)"

One Megohm resistor is required in wrist straps, however, the recommended practice is hard ground per ANSI/EOS/ESD S6.1 that is no resistor between the common point ground terminal and a worksurface, floor mat, or shelving. Per ANSI/ESD S20.20 Table 1 Grounding System Technical Requirement, the Recommended Range is less than 1 ohm AC impedance.

 West Coast: 3651 Walnut Ave., Chino, CA 91710
 East Coast: 90 Hudson Road, Canton, MA 02

 Phone: (909) 627-8178 Fax: (909) 627-7449
 Phone: (781) 821-8370 Fax: (781) 575-017

 Home
 Promotions
 Products
 Technical
 Services
 Contact
 ESD Information

Copyright © 2006 Desco Industries, Inc. All Rights Reserved