## Bolton AL4 <sup>1</sup>/<sub>2</sub>" Coaxial Cable Spool

## BT974990

## Bolton AL4 "Half-Inch" plenum-rated low-loss coaxial cable is available by the spool. Made for integrators and those needing long, straight cable runs.

- $\cdot$  Ultra Low Loss 50ohm Cable, priced per foot, meant for long, straight cable runs
- Plenum-rated, high quality corrugated aluminum insulation
- Wide range of applications, such as indoor distribution, broadcast, various base stations, wireless cellular, and others
- $\cdot$  For transport of any RF signal with lowest possible loss

NOTE: Connectors and termination sold separately



BOLTON B

CABLE STUFF	Product Specifications may change without prior notice.
Dielectric Material	PE spline
Jacket Material	PVC
Inner Conductor Material	Copper-clad aluminum wire
Outer Conductor Material	Corrugated aluminum
DIMENSIONS & MECHANICAL STUFF	
Diameter Over Jacket	15.748 mm   0.62 in
Inner Conductor OD	4.572 mm   0.18 in
Outer Conductor OD	14.046 mm   0.553 in
Nominal Size	1/2 in
Minimum Bend Radius, multiple Bends	127 mm   5 in
Minimum Bend Radius, Single Bend	63.5 mm   2.5 in
ELECTRICAL STUFF	
Cable Impedance	50 ohm ±2 ohm
dc Resistance, Inner Conductor	1.575 ohms/km   0.48 ohms/kft
dc Resistance, Outer Conductor	1.575 ohms/km   0.48 ohms/kft
dc Test Voltage	4000 V
Insulation Resistance	100000 MOhms-km
Jacket Spark Test Voltage (rms)	5000 V
Operating Frequency Band	1–6000 MHz



isales@boltontechnical.com
⊕ www.boltontechnical.com

 5010 Wright Road, Suite 115 Stafford, TX, 77477

