# XE2NP2168

Limit switch contact block, Limit switches XC Standard, 1 co, 1 NO, 1 nc mbb gold flashed connector



#### Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch contact block
Device short name	XE2N
Associated body	ZCD26 ZCP26 ZCKJ6D ZCKM6 ZCKL6 ZCKS6 ZCKJ6
Number of poles	2
Contacts type and composition	1 NO + 1 NC
Contact operation	Slow-break, make before break

### Complementary

Product Compatibility	XCKM	
	XCKS	
	XCKL	
	XCKJ	
	XCKD	
	XCKP	
Electrical connection	Screw-clamp terminals 1 x 0.52 x 2.5 mm²	
Contacts insulation form	Zb	
Contacts material	Gold flashed contacts	
Positive opening	With	
Minimum actuation speed	6 m/min	
Contact code designation	A300, AC-15 (Ue = 240 V), le = 3 A 10 A EN/IEC 60947-5-1 appendix A	
	Q300, DC-13 (Ue = 250 V), le = 0.27 A EN/IEC 60947-5-1 appendix A	
Maximum resistance across terminals	25 mOhm IEC 60255-7 category 3	
[Ui] rated insulation voltage	300 VUL 508	
	500 V 3)IEC 60947-1	
	300 VCSA C22.2 No 14	
[Uimp] rated impulse withstand voltage	6 KV IEC 60664	
	6 kV IEC 60947-1	
Short-circuit protection	10 A cartridge fuse gG	
Electrical durability	5000000 Cycles, DC-13 120 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C	
	5000000 Cycles, DC-13 24 V, 13 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C	
	5000000 cycles, DC-13 48 V, 9 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C	

#### Ordering and shipping details

Category	22449-LIMIT SWITCHES,ACCESSORIES	
Discount Schedule	Т	
GTIN	3389110196245	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.74 oz (21.0 g)	
Returnability	No	
Country of origin	ID	

# Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	4.33 in (11 cm)	
Package 1 width	0.98 in (2.5 cm)	
Package 1 Length	2.95 in (7.5 cm)	

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile

### Contractual warranty

Warranty	18 months
vvarianty	10 months