





Toll Fr<mark>ee: (800) 494-6104</mark>

Insulated Pliers/Cutters

	Description	Page
	Insulated Lineman's Pliers	4
	Insulated Combination Pliers	4
	Insulated Heavy Duty Diagonal Cutters	5
<11	Insulated High Leverage Diagonal Cutters	5
	Insulated Serrated Edge Cutters	5
	Insulated Pliers - Long & Flat Nose	6
-	Insulated Pliers - Bent & Round Nose	e 6
	Insulated Wire Stripper	6
199	Insulated Waterpump Pliers	7
	Insulated Pliers Sets Insulated Belt Pack Pouch Sets	8 7

Insulated Adjustable Wrenches

Description



Insulated Adjustable Wrenches 9 8", 10", 12", 15" OAL

Page

Insulated Industrial Pliers/Cutters

-	
-12-	
and a	
Ø	
.**††¥	2 2
	States and

Description	Page
Insulated Lineman's Pliers	10
Insulated Long Nose Pliers	10
Insulated Diagonal Cutters	10
Insulated High Leverage Cutters	s 10
Insulated Serrated Edge Cutters	s 10
Insulated Stripping Pliers	10
Insulated Crimping Pliers	10
Insulated Industrial Tool Sets	11

Insulated Inomic Pliers



DescriptionPageInsulated Inomic Pliers8Inomic Combo Pliers8Inomic Long Nose Pliers1Inomic Diagonal Cutters8

Vinyl Grip Pliers & Cutters

	Description	Page
	Combination Pliers	12
cia	Stripping Pliers	13
	Long Nose Pliers	13
	Bent Long Nose Pliers	13
	Long Flat Nose Pliers	13
	Long Round Nose Pliers	13
	Adjustable Pliers	14
SI.	Cable Cutters	15
	Diagonal Cutters	15
	High Lev. End Cutting Nippers	16
	Carpenter's End Nippers	16
30	Mason Nippers	16
	Retaining Ring Pliers	18-19
	MagicTip Safety Notched Ring Pliers	20-21
and the	Crimping Pliers	15,45
AA AA	Standard Pliers/Cutters Sets	17
	Belt Pack Pouch Sets	17
	Molded Grip Shears	16

Pipe Wrenches Narrow Style

Description



Narrow Style Pipe Wrenches 22 S-Jaw, 45° Angle, 90° Angle

Page



ComfortGrip Crimpers

Description	Page
Ratchet End Sleeve Crimper	23
Ratchet Crimper For Standard Connectors	23
Ratchet Crimper Push On Terminals	23
Ratchet Crimper For Eye Terminals	23

Industrial SoftGrip Pliers & Cutters

-11

-11

Ċ

-

~? 0-......

	Description	Page
	Combination Pliers	24
	Linemans Crimpers	24
	Stripping Pliers	24
-	Long Nose Pliers	25
~	Bent Long Nose Pliers	25
	Flat Nose Pliers	25
~	Long Round Nose	25
	Diagonal Cutters	26
A ANDINA	Cable Cutters	26
	Adjustable Pliers	26
	Industrial SoftGrip Tool Sets	27

Precision Electronic Pliers/Cutters

	Description	Page
	Electronic Diagonal Cutters Wide Pointed Head	28
\sim	Electronic Diagonal Cutters Wide Shape with Wire Holding Spring	28
\mathbf{x}	Electronic Diagonal Cutters Narrow Shape	28
\sim	Electronic Diagonal Cutters Full Flush Cutters w/Wire Trapping Spring	29
	Electronic Diagonal Cutters 48° Front Cutter/Long Nose Pliers	29
\sim	Electronic Diagonal Cutters Oblique 30° Cutting Nippers	29
×C	Electronic Diagonal Cutters Short Nose Precision Pliers	29
	Electronic Stripping Pliers	25,29

	SD Safe Pliers/Cutters
	Description
	ESD Safe Diagonal Cutters Small, Wide & Oval Tapered Hea
	ESD Safe Diagonal Cutters With Carbide Cutters
¢13	ESD Safe Oblique Angled Cu
<u>_</u>	ESD Safe Oblique Front Cutte
	ESD Safe End Cutters
	ESD Safe Snipe/Bent Nose P
-	ESD Safe Needle Nose Pliers
	ESD Safe Short Round Nose
	ESD Safe Short Flat Nose
	ESD Safe Tool Sets

	Description	Page	
-	ESD Safe Diagonal Cutters Small, Wide & Oval Tapered Head	30-32	
<u>}</u>	ESD Safe Diagonal Cutters With Carbide Cutters	32	
-	ESD Safe Oblique Angled Cutters	s 33	
~	ESD Safe Oblique Front Cutters	33	
•	ESD Safe End Cutters	34	
-	ESD Safe Snipe/Bent Nose Pliers	s 34	
-	ESD Safe Needle Nose Pliers	34	
~	ESD Safe Short Round Nose	35	
-	ESD Safe Short Flat Nose	35	
2	ESD Safe Tool Sets	33,35	
4.			

ESD Safe Proturn Pliers & Cutters



Desc	ription	Page
	irn Wire Strippers 20 AWG	36
	Irn Pliers Flat, Bent, Round Nose	36-37
	sion Cutters/Flush Cut 45° Angle	37-38

Stripping & Crimping Tools

	Description	Page
	PortaCrimp Frame	39
	PortaCrimp Dies	40-42
	PortaCrimp Sets	39
H.	Professional Crimp Tools	42
	Crimping Tools	43-45
	Self Adj. Cut & Strip Tools	46



328 Combination Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, \triangle up to 1000 Volt. Individually Tested. DIN ISO 5746 Extra long cutting edge for flat & round cables. Cutting edges additionally induction hardened to approx. 60HRC. Special CV tool steel forgings, Chrome finish. Use for gripping and holding as well as cutting soft and hard wires and cables.

Item			Cutting Capacity			
No.	mm	Inch	Copper AWG	Pkg.	lbs.	
32814 Z01016006	160	6.3	#10	1	.53	
32816 Z01018006	180	7.0	#9	1	.58	
32818 Z01020006	200	8.0	#8	1	.72	

32820 High Leverage Combination Pliers. Insulation According to EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, Aup to 1000 Volt. Individually Tested. DIN ISO 5746 Extra long cutting edge for flat and round cables. Cutting edges additionally induction hardened to approx. 64HRC. C 60 Special tool steel. Use for gripping, pulling & holding as well as cutting wires and cables ranging in hardness from soft to extremely hard. Two component soft grip ergonomic handles.

Item		-	Cutting Capacity		5 - 3
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32820 Z02022506	225	9.0	#4	1	.86

22841 Insulated Crimping Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, Aup to 1000 Volt. Individually Tested.

Semi-circular profiles for secure connection between end sleeve and conductor. Long life is achieved through additional induction hardening to 64HRC. CV 60 special tool steel hardened & tempered.

ltem					1	.	
No.	mm	Inch	mm2	AWG	Pkg.	lbs.	
32841	180	7.0	0.25-2.5	6-30	1	.57	



∕⊠1000volt

Insulated High Leverage Combination Pliers







Insulated Diagonal Cutters





40% easier cuts and significantly longer tool life

Insulated Serrated Edge Cable Cutters



Insulated Stripping Pliers ∕⊠1000volt

32861 Diagonal Cutters W/Stripping Holes. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, \bigwedge up to 1000 Volt. Individually Tested.

Drop-forged from special tool steel, cutters additionally induction hardened (approx. 60HRC), chrome-nickel plated, mirror-polished. Ergonomic comfort grip with slip guard. Holes in the cutting edge for stripping copper wire of Ø 1.5 and 2.5. Strips AWG sizes #10 & #14. Item Cutting Capacity

No.		mm		Copper AWG	Pkg.	lbs.	
32861	Z14016006		6.3	#6	1	.55	

328 Diagonal Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, Aup to 1000 Volt. Individually Tested. DIN ISO 5749 Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 60HRC. Special tool steel hardened and tempered. For soft & medium hard wire. 32832 & 32834 for soft, hard & piano wire.

Item				Cutting Capacity	-	-
No.		mm	Inch	Copper AWG	Pkg.	lbs.
32830	Z12014006	140	5.5	#6	1	.47
32832	Z12016006	160	6.3	#6	1	.49
32834	Z12018006	180	7.0	#6	1	.62

328 High Leverage Diagonal Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, \Leftrightarrow up to 1000 Volt. Individually Tested. DIN ISO 5749 Semi-circular. Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 64HRC. C 60 special tool steel hardened and tempered to high quality. For soft, hard and piano wire, lay-on joint, optimized power transmission.

Item	4		Cutting Capacity	/	÷.*	
No.	mm	Inch	Copper AWG	Pkg.	lbs.	
32835 Z16	016006 160	6.3	#6	1	.64	
32836 Z16	018006 180	7.0	#5	1	.67	
32838 Z16	020006 200	8.0	#4	1 1	.80	

328 Serrated Edge Cable Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, ightarrow up to 1000 Volt. Individually Tested. Light, clean cutting ground precision cutting edges. Durable cutting is achieved through additional inductive hardening to approx. 62HRC. Special tool steel, hardened & tempered. For cutting of copper & aluminum cables without crushing.

Item						5-3
No.	mm	Inch	Ø	mm2	Pkg.	lbs.
32826 Z500230	06 160	6.3	16	50	1	.42
32828 Z500170	06 200	8.0	20	60	1	.67

32860 Stripping Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, A up to 1000 Volt. Individually Tested. Heavy duty forged with induction hardened cutting edges for even stripping of insulation. Drop-forged from special tool steel, chrome & nickel plated, mirror-polished. Ergo comfort grip with slip guard. Spring & adjusting screw, for stripping up to Ø 5mm/#4 Awg.

Item			Stripping Capacity		5-3	
No.	mm	Inch	Copper AWG	Pkg.	lbs.	
32860 Z55016006	160	6.3	#4 - #28	1	.50	



Premium Tools





Insulated Bent Nose Pliers Angled 40°



Insulated Long Flat Nose Pliers

Item			Cutting Capacity		£-7
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32806 Z05016006	160	6.3	#10	1	.32
32808 Z05020006	200	8.0	#8	1	.42

328 Bent Nose Pliers With Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, \triangle up to 1000 Volt. Individually Tested.

Drop-forged from special tool steel, cutters additionally induction hardened (approx. 60HRC), chrome-nickel plated, mirror-polished. Ergonomic comfort grip with slip guard. Half-round jaws, serrated gripping surface, nose bent 40°.

Item			Cutting Capacity	and the second second		
No.	mm	Inch	Copper AWG	Pkg.	lbs.	
32804 Z05120006	200	8.0	#8	1	.43	
32807 Z05116006	160	6.3	#10	1	.32	

32870 Round Nose Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, aup to 1000 Volt. Individually Tested. Drop-forged from special tool steel, individually induction hardened, chrome and nickel plated, mirror-polished. Ergonomic comfort grip with slip guard. Serrated jaws.

Item					
No.	mm	Inch	Pkg.	lbs.	
32870 Z09016006	160	6.3	1	.34	

32810 Long Flat Nose Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, ☆ up to 1000 Volt. Individually Tested. DIN ISO 5745 Extra long head. Serrated Jaws are induction hardened. Special CV tool steel forgings, Chrome finish. Two component Soft Grip handles. Use for Gripping and right-angle bending of wires and sheet metal parts.

Item	-		
No.	mm	Inch	Pkg. lbs.
32810 Z07016006	160	6.3	1.39

WARNING!

Insulated Tools are intended to provide protection against accidental contact with charged energized circuits. For maximum safety we recommend de-energizing all circuits whenever possible before starting work on electrical apparatus or conductors. Always visually inspect insulation on tools before use, do not use tools if insulation shows signs of wear or damage to the insulated areas of the tool. Wear appropriate eye protection when using hand tools. Use NFPA70E certified insulated protective outer wear when appropriate.

Use & Care Guide For Insulated Tools:

Store tools to minimize risk of damage to insulation, always wear approved eye protection, Inspect insulation prior to each use of any insulated tool. Use insulated tools where the ambient temperature is between -20 to $+70^{\circ}$ C. Have a qualified safety technician visually inspect insulation on tools annually for safe use.



Insulated Stripping Pliers



☆1000Volt

10250Insulated Stripping Pliers. Insulation According to EN/IEC60900, DIN ISO 8976, ASTM F-1505 & CSA Specification.

Individually Tested. Wide long head with ridged gripping surface, shears blade and firm wire stripping stations. Wire stripping stations 0.81 / 1.0 / 1.3 / 1.6 / 2.0 / 2.59mm, AWG 20 / 18 / 16 / 14 / 12 / 10.

Item No.	mm	Inch	Ø	AWG	Pkg.	lbs.	
10250	160	6.3"	0.81-2.59	20-10	5	.26	



$\widehat{\times}$ 1000Volt

29250End Cutters, With Insulated Handle. Insulation According
to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification.Individually Tested.Blade alloyed tool steel.Individually Tested.Blade alloyed tool steel.Induction hardened.ItemOALOALCapacity

No.	mm	Inch	Inch	lbs.	pkg.
29250	250	10.0"	7/8"	1.1	1

Wiha Insulated Waterpump Pliers



1000Volt

29240 Waterpump Pliers, With Insulated Handle

Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification, Up To 1000 Volt. Individually Tested.

Box joint.	Chrom	Chrome-vanadium steel, drop forged, oil hardened							
Item	OAL	OAL	Capacity	£-5					
No.	mm	Inch	Inch	lbs.	pkg.				
20240	240	0 5"	7/8"	1 1	1				

Wiha Canvas Pliers Holster

· Canvas holster with belt clip and belt loop

- · Security pliers strap
- · Screwdriver holder in the front

91256	Pliers Canvas Holster							
Item	Wid	th	Heigh	it 🗲 🗣				
No.	Size)	Size	lbs.	pkg.	Each		
91256	3.5	х	6.75	.15	1	\$5.98		



Wiha Insulated Belt Pack Pouch Sets





32871 3 Piece Insulated Pliers/Cutters & Multi-Bit Set In Belt Pack Pouch. Tools meet EN/IEC, ASTM, VDE, NFPA70E & CSA standards. Pliers chrome finish for long lasting corrosion protection. Soft grip ergo designed handle body, safety slip guard. Insulated Multi-bit screwdriver includes Slotted, Phillips & Square bits.

Item No.	Pliers/Cutters & Multi-Bit Set						
32871	6.3" / 160mm Diagonal Cutters						
÷.*	8.0" / 200mm Long Nose Pliers						
lbs.	Set Includes Bit Holder & The Following Bits:						
1.67	Slotted: 4.5, 6.5mm Phillips: 1, 2 Square: 1, 2						



32873 3 Piece Insulated Pliers/Cutters In Belt

Pack Pouch. Tools meet EN/IEC, ASTM, VDE, NFPA70E & CSA standards. Pliers chrome finish for long lasting corrosion protection. Soft grip ergo designed handle body, safety slip guard.

Item No.	Pliers & Cutters
32873	6.3" / 160mm Diagonal Cutters
sta i	8.0" / 200mm Long Nose Pliers
lbs. 2.07	8.0" / 200mm Combination Pliers





32872 5 Piece Insulated Pliers/Cutters & Screwdrivers In Belt Pack Pouch. Tools meet EN/IEC, ASTM, VDE, NFPA70E & CSA standards. Pliers chrome finish for long lasting corrosion protection. Soft grip ergo designed handle body, safety slip guard. Insulated cushion grip drivers, multi-component. Blade CVM tool steel, hardened.

Item No.	Pliers/Cutters & Screwdrivers	
32872	6.3" / 160mm Diagonal Cutters	
et e	8.0" / 200mm Long Nose Pliers	
lbs.	Insulated Screwdrivers:	
1.77	Slotted: 3.0, 4.5mm Phillips: 2	



Wiha Insulated Pliers and Cutters Sets



 Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome and nickel plated, mirror-polished.

In zipper carry case

32891 10 Piece Pliers & Screwdriver Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, \triangle up to 1000 volt. Individually Tested.

Item# 32891 Set Includes:	Jan 105. 5.44	
32818 - 8.0" Combination Pliers	32808 - 8.0" Long Nose	
32838 - 8.0" Side Cutters	32848 - 6.75" Cable Cutters	
32860 - 6.3" Universal Wire Stripper		
Insulated Phillips #1, #2, #3	Insulated Slotted 4.5, 6.5mm	



 Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome and nickel plated, mirror-polished.

$extsf{2}$ 1000volt

Item# 32889 Set Includes:	
32806 - 6.3" Long Nose Pliers	
32814 - 6.3" Lineman's Pliers	
32820 - 9.0" Lineman's Pliers	
32860 - 6.3" Wire Stripping Pliers	

Wiha Inomic 1000Volt Insulated Pliers

Insulation Standards:

EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA



☆1000volt

32850 Inomic Combo Pliers. Insulation According to EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, Aup to 1000 volt. Individually Tested. DIN ISO 5749 Precision machined forged head. Induction hardened for longest tool life. Cross hatched flat jaw & deep cut radius jaws for secure gripping of the work piece. Cutting edges are matched for precise cutting action. Award winning ergonomic design with head mounted at 23° angle to grip for reduced user fatigue. Palm side of grip has molded soft panel for added comfort in prolonged use.

Item			Cutting Capacity		5°3
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32850 Z01016180	180	7.0	#6	1	.46
32852 Inomic Lon	g Nose	Pliers			
Item			Cutting Capacity		5-3
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32852 Z01016160	160	6.3	#6	1	.43
32854 Inomic Diag	onal C	utters			
Item			Cutting Capacity		<u>.</u>
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32854 Z01016160	160	6.3	#6	1	.41



Tools Meet 10,000 Volt Test Standards Rated to 1000 Volt ac or 1500 Volt dc

or 1500 Volt dc



32859 3 Pc. Insulated Inomic Pliers/Cutters Set Meets ASTM, EN/IEC, NFPA, CSA, ISO specifications. Award winning ergonomic design with head mounted at 23° angle to grip for reduced user fatigue.

 Item# 32859
 Set Includes:

 32850 - Combo Pliers
 3285

 32852 - Long Nose Pliers
 9123

Ibs. 1.4532854 - Diagonal Cutters91230 - Inomic Holster (Includes 3)

91230	Inomic Canvas Holster					
Item	Width		Height	_		
No.	Size		Size	lbs.	pkg.	
91230	4.0	х	4.5	.05	1	





9

Premium Tools







 Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM

 F-1505-01, NFPA70E & CSA, A up to 1000 volt. Individually Tested.

 Item

 ← ← Cutting Capacity

			e anning e appending			
No.	mm	Inch	Copper AWG	Pkg.	wt.	
32926	160	6.3	#10	1	.36	
32923	200	8.0	#8	1	.46	

Insulated Diagonal Cutters



Insulated Combo Pliers With Dynamic Joint

Long life high performance

dynamic 60/40 joint

32930 Insulated Industrial High Leverage Combination Pliers. Insulation According to EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, \triangle up to 1000 volt. Individually Tested. DIN ISO 5746

Item			Cutting Capacity	-		
No.	mm	Inch	Copper AWG	Pkg.	wt.	
32930	200	8.0	#4	1	.92	

Insulated Heavy Duty Cable Cutters



32927 Insulated Industrial Serrated Edge Cable Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, \triangle up to 1000 Volt. Individually Tested.

Item			a			
No.				mm2	Pkg.	IDS.
32927	200	8.0	20	60	1	.78

Insulated Stripping Pliers



☆1000volt

32947 Insulated Industrial Stripping Pliers. Insulation According to VDE 0682/part 201, DIN 7437, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, 1000 volt rated. Individually Tested. DIN ISO 5745

32947	160	6.3	#4 - #28	1	.46	
No.	mm	Inch	Copper AWG	Pkg.	wt.	
Item		-	Stripping Capacity		5.5	

Insulated Crimpers



☆1000volt

32945 Insulated Industrial Crimping Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, \triangle up to 1000 Volt. Individually Tested.

Item						.
No.	mm	Inch	mm2	AWG	Pkg.	wt.
32945	180	7.0	0.25-2.5	6-30	1	.64



Wiha Insulated Industrial Tool Sets







32986 11 Pc. Pliers/Cutters & Screwdriver Set. Insulation According to VDE 0682/part 201, DIN EN 60900, EN/IEC 60900, ASTM F-1505-01, NFPA70E, A up to 1000 volt. Individually Tested. Item# 32986 Set Includes: Jbs. 3.62 32926 - 6.3" Long Nose Pliers 32933 - 6.3" Diagonal Cutters 32930 - 8.0" Combination Pliers 32947 - 6.3" Stripping Pliers Insulated Slotted: 3.0, 4.5, 5.5mm Insulated Phillips: #1, #2 Insulated Square: #1, #2







☆1000Volt



32987 8 Pc. Pliers & Cutters Set. Insulation According to VDE 0682/part 201, DIN EN 60900, EN/IEC 60900, ASTM F-1505-01, NFPA70E, A up to 1000 volt. Individually Tested. In Roll Out Pouch Item# 32987 Set Includes: Jbs. 5.52

32926 - 6.3" Long Nose Pliers 32923 - 8.0" Long Nose Pliers 32917 - 9.0" Lineman's w/Cutters 32927 - 8.0" Cable Cutters

32933 - 6.3" Diagonal Cutters 32929 - 8.0" H.D. Diagonal Cutters 32947 - 6.3" Stripping Pliers 32945 - 7.0" Crimpers



32988 22 Pc. Pliers/Cutters & SlimLine Blade Set. Insulation According to VDE 0682/part 201, DIN EN 60900, EN/IEC 60900, ASTM F-1505-01, NFPA70E, lpha up to 1000 volt. Individually Tested. Item# 32988 Set Includes: Jbs. 5.74 32923 - 8.0" Long Nose Pliers 32933 - 6.3" Diagonal Cutters 32917 - 9.0" Lineman's w/Cutters 32929 - 8.0" H.D. Diagonal Cutters 32927 - 8.0" Cable Cutters 32947 - 6.3" Stripping Pliers 32945 - 7.0" Crimpers 15 Pc. SlimLine Blade Set includes: Insulated SlimLine Blade Holder Xeno: #1, #2 Slotted: 3.0, 4.0, 5.5, 6.5 Phillips: #1, #2 TORX*: T8, T10, T15, T20 Square: #1, #2

Tools meet ASTM, IEC, VDE, EN. NFPA & CSA standards







 \Rightarrow 1000Volt

32981 3 Pc. Insulated Industrial Pliers & Cutters **Insulated Pliers & Cutters** Item No.

32981 8.0" Combo Pliers, 8.0" Long Pliers, 8.0" Diagonal Cutters Jbs. 2.18



Tools meet ASTM, IEC, VDE, EN, NFPA & CSA standards

32983 5 Pc. Insulated Industrial Diagonal Cutters & Screwdrivers Item No. Insulated Diagonal Cutters & Screwdrivers 32983 6.3"/160mm Diagonal Cutter

Insulated Divers: Slotted: 3.0, 4.5mm • Phillips: #1, #2 Jbs. 1.17



32984 6 Pc. Insulated Industrial Combo Pliers & Screwdrivers **Insulated Combination Pliers & Screwdrivers** Item No. 32984 8.0" Combination Pliers & 8" Long Nose Pliers Divers: Slotted: 3.0, 4.5mm • Phillips: #2 • Square: #2 Jbs. 2.06

In Belt Pack Pouch Tools meet ASTM, standards ightarrow 1000Volt

IEC VDE EN NFPA & CSA

32985 7 Pc. Insulated Industrial Pliers/Cutters & Screwdrivers Insulated Pliers/Cutters & Screwdrivers Item No. 32985 8.0" Combo Pliers, 6.3" Long Nose, 6.3" Diagonal Cutters Insulated Divers: Slotted: 3.0, 4.5mm • Phillips: #1, #2

Jbs. 2.30







32616 Lineman's Pliers "5-in-1" Professional Design Deep cut radius conduit jaws for non-slip griping. Extra long induction hardened precision matched cutting edges. Lower crimping jaw accepts most standard non-insulated electrical connectors. Large head with square anvil surface on each side. Made from premium CV tool steel forgings. Vinyl coated cushion grips for best user comfort.

Item			Cutting Capacity	-	£
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32616 Z01122001	225	9.0	#4	1	.88



326 Combination Pliers With Cutters DIN ISO 5746

Extra long cutting edge for flat and round cables. Serrated jaws. Cutting edges additionally induction hardened to approx. 60HRC. C.V. Special tool steel. For gripping and holding as well as cutting soft and hard wires and cables. Soft vinyl grips, oil & solvent resistant.

Item			Cutting Capacity	-	5-3
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32603 Z01016001	160	6.3	#10	1	.41
32606 Z01018001	180	7.0	#9	1	.50
32609 Z01020001	200	8.0	#8	1	.63

High Leverage Combination Pliers

326 High Leverage Heavy Duty Combination Pliers DIN ISO 5746								
Extra long cutting edge for flat and round cables. Serrated jaws.								
Cutting edges additionally induction hardened to approx. 60HRC.								

C.V. Special tool steel forgings. Use For gripping, pulling & holding as well as cutting soft, hard & piano wires and cables. Soft vinyl grips are oil & solvent resistant.

Item		↔	Cutting Capacity		.
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32612 Z02020001	200	8.0	#4	1	.61
32615 Z02022501	225	9.0	#4	1	.78





326 Long Nose Pliers With Cutters DIN ISO 5745

Long nose pliers. Extra long cutters for flat and round cables. Serrated Jaws. Cutting edges additionally induction hardened to approx. 60 HRC. Special CV tool steel forgings. Soft vinyl grips are oil & solvent resistant.

Item			Cutting Capacity		5
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32618 Z05016001	160	6.3	#10	1	.28
32621 Z05020001	200	8.0	#8	1	.86



326 Bent Long Nose Pliers With Cutters DIN ISO 5745

Long nose pliers angled 40°. Extra long cutters for flat and round wire. Partially Serrated Jaws. Cutting edges additionally induction hardened to approx. 60 HRC. Special CV tool steel forgings. Soft vinyl grips are oil & solvent resistant.

Item			Cutting Capacity	-	£-5
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32623 Z05116001	160	6.3	#10	1	.28
32625 Z05120001	200	8.0	#8	1	.96







32630 Long Flat Nose Pliers DIN ISO 5745

Extra long head. Serrated Jaws are induction hardened. Special CV tool steel forgings. Use for gripping and right-angled bending of wires and sheet metal parts. Soft vinyl grips are oil & solvent resistant.

Item					
No.	mm	Inch	Pkg.	lbs.	
32630 Z07016001	160	6.3	1	.26	



32633 Long Round Nose Pliers DIN ISO 5745

Extra long head. Serrated Jaws are induction hardened. Special CV tool steel forgings. Use for gripping and uniform round bending of wires and sheet metal parts. Soft vinyl grips are oil & solvent resistant.

Item			-		
No.	mm	Inch	Pkg.	lbs.	
32633 Z09016001	160	6.3	1	.25	

32645 Stripping Pliers DIN ISO 5744

Heavy duty forged with induction hardened cutting edges for even stripping of insulation. Easy to use adjusting screw allows the stripping diameter to be set. Opening spring for effortless and sensitive handling of pliers. C.V. special tool steel. For Stripping up to Ø 5mm/#4 AWG conductor cross-section. Soft vinyl grips.

Item			Stripping Capacity		÷
No.	mm	Inch	Copper Awg#	Pkg.	lbs.
32645 Z55016001	160	6.3	#4 - #28	1	.31



Toll Fr<mark>ee: (800) 494-6104</mark>

Wiha Soft Grip Pliers & Cutters

Standard Adjustable Pliers



326 Adjustable Pliers - Box Type DIN ISO 5745

10 different opening sizes provide optimal adjustment to objects being gripped. Long durability achieved through additional induction hardening of jaws to approx. 58-60 HRC. Chrome-vanadium tool steel, hardened and tempered. Soft vinyl grips are oil and solvent resistant.

Item			Capa	cities	Constant P		
No.	mm	Inch	Round	Hex	Pkg.	lbs.	
32660 Z21001180	180	7.0	1.25	1 1/2	1	.35	
32661 Z21001250	250	10.0	1.75	2.0	1	.67	
32663 Z21001300	300	12.0	2.0	2 1/4	1	1.17	



- · Open and slide to adjust opening size
- Audible click at each locking position
- Close to lock

Rapid Adjustable - Push Button Pliers



- Fast push button jaw release
- Finger jam protection in all settings



32669 3 Piece Push Button Set

Drop-forged from special tool steel, individually high frequency induction hardened. Precision formed. Soft vinyl grips, oil & solvent resistant.

Item# 32669	Set Includes:	↓ Ibs. 2.50
32664 - Push	Button Adjustable	Water Pump Pliers - 7.0"
32665 - Push	Button Adjustable	Water Pump Pliers - 10.0"
32667 - Push	Button Adjustable	Water Pump Pliers - 12.0"

32668 Slide Lock Adjustable Pliers - Wiha QuickFix - Box Type DIN ISO 8976 Super fast and easily adjusted pliers. Long durability achieved through additional induction hardening of jaws to approx. 56 HRC. Finger jam protection for safe operation in all settings. Chromevanadium tool steel, hardened and tempered. Soft vinyl grips.

Item		<->	Capad	cities		£-5
No.	mm	Inch	Round	Hex	Pkg.	lbs.
32668 Z23025001	250	10.0	1 1/4	1 1/2	1	.72

326 Push Button Adjustable Water Pump Pliers - DIN ISO 8976 Extra narrow head for working in restricted spaces. Rapid and simple push button setting and locking. Long durability achieved by additional inductive hardening of gripper jaws to approx. 58-60 HRC. Finger jam protection in all settings ensures safe operation. Chrome-vanadium tool steel, hardened and tempered. Soft vinyl grips. For gripping and holding pipes and angular profiles such as hex nuts in the installation area.

Item		↔	Capa	cities	(1993)	.	
No.	mm	Inch	Round	Hex	Pkg.	lbs.	
32664 Z22001180	180	7.0	1.25	1 1/2	1	.35	
32665 Z22001250	250	10.0	1.75	2.0	1	.80	
32667 Z22001300	300	12.0	2.0	2 1/4	1	1.21	



32670 3 Piece Adjustable Pliers Set

Drop-forged from special tool steel, individually high frequency induction hardened. Precision formed. Soft vinyl grips, oil & solvent resistant.

Item# 32670 Set Includes:	Jbs. 2.52
32660 - Adjustable Pliers, Box Type	e - 7.0"
32661 - Adjustable Pliers, Box Type	e - 10.0"
32663 - Adjustable Pliers, Box Type	e - 12.0"



Wiha Soft Grip Pliers & Cutters





Cable Cutters





326 Diagonal Cutters DIN ISO 5749

Low wear lap joint, riveted and able to withstand high levels of load. Low force cutting action, clean cutting. Long life edge is achieved through additional induction hardening to approx. 60 HRC. Special CV tool steel hardened and tempered. For soft & medium hard wire. Soft vinyl grips.

Item			Cutting Capacity	-		
No.	mm	Inch	Copper AWG	Pkg	g. Ibs.	
32638 Z12014001	140	5.5	#6	1	.33	
32642 Z12016001	160	6.3	#6	1	.49	
32639 Z12018001	180	7.0	#6	1	.54	

326 High Leverage Cutters DIN ISO 5749

Semi-circular. Low wear lap joint, riveted and able to withstand high levels of load. Low force action, clean cutting. Long life is achieved through additional induction hardening of cutting edge to 64 HRC. CV 60 special tool steel hardened and tempered. Soft vinyl grips.

Item			Cutting Capacity		
No.	mm	Inch	Copper AWG	Pkg	. Ibs.
32646 Z16016001	160	6.3	#6	1	.42
32649 Z16018001	180	7.0	#5	1	.50
32652 Z16020001	200	8.0	#4	1	.63

326 Cable Cutters Light, energy-saving & clean cutting with specially ground precision cutting edges. Long life is achieved through additional induction hardening of cutting edge to 64 HRC. CV 60 special tool steel hardened and tempered. Soft vinyl grips. For cutting of copper & aluminum cables without crushing, also suitable for stripping. Not for steel cable, wires and copper conductors with hard coatings.

Item			Cutting Capacity		5-2	
No.	mm	Inch	Copper/Aluminum	Pkg	. Ibs.	
32600 Z50101160	160	6.3	16mm	1	.34	
32602 Z50101200	200	7.9	20mm	1	.62	

326 Crimping Pliers DIN ISO 5743

Semi-circular profiles for secure connection between end sleeve and conductor. Long life is achieved through additional induction hardening to 64 HRC. CV 60 special tool steel hardened & tempered. Soft vinyl grips.

Item	-					* **
No.	mm	Inch	mm2	AWG	Pkg.	lbs.
32604 Z60001145	145	5.75	0.25-2.5	14-30	1	.29
32605 Z60001180	180	7.0	0.25-16	6-30	1	.57

57872 Proturn Stripping Pliers

Wide long head with ridged gripping surface, shears blade and firm wire stripping stations. With opening spring and locking mechanism. Wire stripping stations 0.81 / 1.0 / 1.3 / 1.6 / 2.0 / 2.59mm,

AVVG	207	18/	16/	14/	12/	10.	

#57872	mm	Inch	Ø	AWG	Pkg.	lbs.	
	180	7.0	0.81-2.59	20-10	5	.124	

15



Premium Tools

Wiha Soft Grip Pliers & Cutters



32698 3 Piece Pliers & Cutters Set

Drop-forged from special tool steel, individually high frequency induction hardened. Precision formed. Soft vinyl grips, oil & solvent resistant.

Item# 32698 Set Includes: 32606 - Combination Pliers 32618 - Long Nose Pliers Jbs. 1.39 32642 - Diagonal Cutters



326 High Leverage End Cutting Nippers DIN ISO 5749 Low wear lap joint, riveted and able to withstand high levels of load. Low force action, clean cutting. Long life cutting edges are achieved through additional induction hardening to approx. 60 HRC. Special CV tool steel forgings hardened and tempered. Soft vinyl grips are oil & solvent resistant.

Item				Cutting Capacity	-	<u> </u>	
No.		mm	Inch	Copper AWG	Pkg.	lbs.	
32657	Z17001160	160	6.3	#6	1	.41	
32658	Z17018001	180	7.0	#5	1	.61	
32659	Z17020001	200	8.0	#4	1	.75	



32648 2 Piece Pliers & Cutters Set

Drop-forged from special tool steel, individually high frequency induction hardened. Precision formed. Soft vinyl grips, oil & solvent resistant.

Item# 32648Set Includes:Image: Image: Image:



326 Carpenter's End Nippers DIN ISO 9243

High cutting performance and reduced effort achieved through the precise formation of the cutting blade after assembly. Long life cutting edges achieved by additional induction hardening. Special CV tool steel, hardened and tempered. Soft vinyl grips are oil & solvent resistant.

Item			(Internet)	5 ° 5
No.	mm	Inch	Pkg.	lbs.
32671 Z30018001	180	7.0	1	.62
32672 Z30001200	200	8.0	1	.86



32610 Multipurpose Electrician's Heavy Duty Shears

High alloy carbon steel, hardened, burnished surface. Sturdy model, straight, very robust, micro-toothed cutting.

Item			10000		
No.	mm	Inch	Pkg.	lbs.	
32610	145	5.75	1	.05	
32611	SoftGrip Ele	ctrician's a	& Craftsma	n Shears	
ltem			and the second sec	5°3	
No.	mm	Inch	Pkg.	lbs.	
32611	145	5.75	1	.05	



326 Mason Nippers DIN ISO 9243

High cutting performance and reduced effort achieved through the precise formation of the cutting blade after assembly. Long life induction hardened cutting edges. Special tool steel, hardened and tempered. Soft vinyl Grips are oil & solvent resistant.

ltem				Cutting Capacity	-	÷.+
No.		mm	Inch	Hard Wire AWG	Pkg.	lbs.
32674	Z31022001	220	8.75	#12	1	.76
32676	Z31025001	250	10.0	#12	1	.98
32678	Z31028001	280	11.0	#12	1	1.00
32680	Z31030001	300	12.0	#12	1	1.06

Wiha Soft Grip Nippers



Wiha Soft Grip Pliers & Cutters

Wiha Soft Grip Belt Pack Pouch Sets



32601 4 Piece Pliers & Cutters Set

Drop-forged from special tool steel, individually high frequency induction hardened. Precision formed. Soft vinyl grips, oil & solvent resistant. In roll-up pouch.

G

Item# 32601 Set Includes:	••• lbs. 3.16
32609 - Combination Pliers - 8.0"	32661 - Water Pump Pliers - 10.0"
32618 - Long Nose Pliers - 6.3"	32642 - Diagonal Cutters - 6.3"







32653 3 Piece Pliers/Cutters In Belt Pack Pouch

Pliers precision formed. Jaws & cutters induction hardened. Soft vinyl grips are oil & solvent resistant. SoftFinish cushion grip drivers, multi-component. Durable canvas belt pack pouch.

Item No.	Pliers & Cutters
32653	8.0" / 200mm High Leverage Cutters
	8.0" / 200mm Combo Pliers
	8.0" / 200mm Long Nose Pliers
	July 105. 2.02



32608 8 Piece Pliers & Cutters In Canvas Pouch

Pliers precision formed. Jaws & cutters induction hardened. Long life edge is achieved through additional induction hardening to approx. 60 HRC. Soft vinyl grips are oil & solvent resistant. Oat Includ

Item No.	Set Includes:
32608	6.3" / 160mm Combination Pliers
	6.3" / 160mm Long Nose Pliers
• •	8.0" / 200mm Long Nose Pliers
lbs.	6.3" / 160mm Diagonal Cutters
4.42	6.3" / 160mm Long Flat Nose Pliers
	6.3" / 160mm Long Round Nose Pliers
	8.0" / 200mm High Leverage Cutters
	9.0" / 225mm High Leverage Combo Pliers



Durable Canvas Belt Pack Pouch



32655 5 Piece Pliers/Cutters & Screwdrivers In Belt Pack Pouch Pliers precision formed. Jaws & cutters induction hardened. Soft vinyl grips are oil & solvent resistant. Screwdriver blades CVM tool steel, hardened, hard chromed. SoftFinish cushion grip drivers, multi-component. Durable canvas belt pack pouch.

man oomponom	Barabio barrie borr p	non ponon
Item No.	Pliers & Cutters	
32655	6.3" / 160mm Diagor	nal Cutters
	8.0" / 200mm Long N	lose Pliers
	Cushion Grip Screv	vdrivers:
	Slotted: 3.0, 4.5mm	Phillips: 2
.	Ibs. 1.62	



Wiha Soft Grip Pliers & Cutters



326 Straight Internal Retaining Ring Pliers DIN ISO 5256

Shape C, straight tips. Die forged cylindrical precision formed. Chrome-vanadium special tool steel. For inserting & removing internal retaining rings.

Item			C	C	• Tip		
No.	mm	Inch	Inch	mm	Inch/mm	Pkg.	lbs.
32681	139	5.5	5/16-1/2	8-13	.035/.9	1	.27
32682	140	5.5	1/2-1	12-25	.050/1.3	1	.27
32683	180	7.0	3/4-2 3/8	19-60	.070/1.5	1	.42
32684	225	8.9	1 1/2-4	40-100	.090/2.3	1	.63
32654	310	12.2	3.5-5.5	85-140	.126/3.2	1	1.13



326 90° Angle Internal Retaining Ring Pliers DIN ISO 5254

Shape D, 90° angled tips. Die forged cylindrical precision formed. CV Special tool steel. For inserting & removing internal retaining rings. Soft vinyl grips.

Item			C	ಲಿ	• Tip		5-3
No.	mm	Inch	Inch	mm	Inch/mm	Pkg.	lbs.
32685	139	5.5	5/16-1/2	8-13	.035/.9	1	.27
32686	140	5.5	1/2-1	12-25	.050/1.3	1	.27
32687	180	7.0	3/4-2 3/8	19-60	.070/1.5	1	.43
32688	225	8.9	1 1/2-4	40-100	.090/2.3	1	.62
32656	310	12.2	3.5-5.5	85-140	.126/3.2	1	1.14

Retaining Ring Pliers - External

326 Straight External Retaining Ring Pliers DIN ISO 5254

Shape A, straight tips. Die forged cylindrical precision formed. CV special tool steel. For fitting & removing external retaining rings. Soft vinyl grips.

Item			C	U	• Tip	-	
No.	mm	Inch	Inch	mm	Inch/mm	Pkg.	lbs.
32689	139	5.5	1/8-3/8	3-10	.035/.9	1	.28
32690	140	5.5	3/8-1	10-25	.050/1.3	1	.28
32691	180	7.0	3/4-2 3/8	19-60	.070/1.5	1	.45
32692	225	8.9	1 1/2-4	40-100	.090/2.3	1	.62
32662	310	12.2	3.5-5.5	85-140	.126/3.2	1	1.13

90° Angle Retaining Ring Pliers - External



326 90° Angled External Retaining Ring Pliers DIN ISO 5254

Shape B, 90° angled tips. Die forged cylindrical precision formed. CV special tool steel. For fitting & removing external retaining rings. Soft vinyl grips.

	0	-		0	0		
Item	*		ඊ	C	• Tip	-	.
No.	mm	Inch	Inch	mm	Inch/mm	Pkg.	lbs.
32694	139	5.5	1/8-3/8	3-10	.035/.9	1	.28
32695	140	5.5	3/8-1	10-25	.050/1.3	1	.28
32696	180	7.0	3/4-2 3/8	19-60	.070/1.5	1	.44
32697	225	8.9	1 1/2-4	40-100	.090/2.3	1	.63
32666	310	12.2	3.5-5.5	85-140	.126/3.2	1	1.16



Wiha Forged Retaining Ring Pliers



32693 8 Piece Straight Retaining Ring Pliers Set Straight tips. Die forged cylindrical precision formed. Chrome-vanadium special tool steel. For inserting & removing internal and external retaining rings.

Item# 32693 Set Includes: Internal Retaining Ring - Shape C 32681 5/16-1/2" / 8-13mm / tip .035 32682 1/2-1" / 12-25mm / tip .050 32683 3/4-2-3/8" / 19-60mm / tip .070 32684 1-1/2-4" / 40-100mm / tip .090

Jbs. 3.65 External Retaining Ring - Shape A 32689 1/8 - 3/8" / 3-10mm / tip .035 32690 3/8 - 1" / 10-25mm / tip .050 32691 3/4 - 2-3/8" / 19-60mm / tip .070 32692 1/2 - 4" / 40-100mm / tip .090



32626 4 Piece Straight Internal Ring Pliers Set Shape C, straight tips. Die forged cylindrical precision formed. Chrome-vanadium special tool steel. For inserting & removing internal retaining rings.

Item# 32626 Set Includes: 32681 5/16-1/2" / 8-13mm / tip .035 32682 1/2-1" 12-25mm / tip .050

Jbs. 1.60 32683 3/4-2 3/8" 19-60mm / tip .070 32684 1 1/2-4" 40-100mm / tip .090



32628 4 Piece Straight External Ring Pliers Set Shape A, straight tips. Die forged cylindrical precision formed. CV special tool steel. For fitting & removing external retaining rings. Soft vinyl grips.

Item# 32628 Set Includes: 32689 1/8-3/8" / 3-10mm / tip .035 32690 3/8-1" 10-25mm / tip .050

Jbs. 1.52 32691 3/4-2 3/8" 19-60mm / tip .070 32692 1 1/2-4" 40-100mm / tip .090



32629 4 Piece 90° Angle External Ring Pliers Set Shape B, 90° angled tips. Die forged cylindrical precision formed. CV special tool steel. For fitting & removing external retaining rings. Soft vinyl grips.

Item# 32629 Set Includes: 32694 1/8-3/8" / 3-10mm / tip .035 32695 3/8-1" 10-25mm / tip .050

Jbs. 1.52 32696 3/4-2 3/8" 19-60mm / tip .070 32697 1 1/2-4" 40-100mm / tip .090



32627 4 Piece 90° Angle Internal Ring Pliers Set Shape D, 90° angled tips. Die forged cylindrical precision formed. CV Special tool steel. For inserting & removing internal retaining rings. Soft vinyl grips.

Item# 32627 Set Includes: 32685 5/16-1/2" / 8-13mm / tip .035 32686 1/2-1" 12-25mm / tip .050

Jbs. 1.56 32687 3/4-2 3/8" 19-60mm / tip .070 32688 1 1/2-4" 40-100mm / tip .090



Wiha MagicTip Safety Ring Pliers







346 MagicTip Straight Internal Safety Ring Pliers DIN ISO 5256

Shape C, straight tips. Precision machined tips of Chrome-vanadium special tool steel. For inserting & removing internal retaining rings.

Item				ల	C	• Tip		5-3
No.		mm	Inch	Inch	mm	Inch/mm	Pkg.	lbs.
34608	Z334J0001	140	5.5	5/16-1/2	8-13	.035/.9	1	.21
34609	Z334J1001	140	5.5	1/2-1	12-25	.050/1.3	1	.21
34610	Z334J2001	180	7.1	3/4-2 3/8	19-60	.070/1.5	1	.34
34611	Z334J3001	220	8.7	1 1/2-4	40-100	.090/2.3	1	.54
34612	Z334J4001	305	12.0	3.5-5.5	85-140	.126/3.2	1	.90

346 MagicTip 90° Angle Internal Safety Ring Pliers DIN ISO 5254

Shape D, 90° angled tips. Precision machined tips of Chrome-vanadium Special tool steel. For inserting & removing internal retaining rings. Soft vinvl grips.

Item				C	ಲಿ	• Tip		£**
No.		mm	Inch	Inch	mm	Inch/mm	Pkg.	lbs.
34613	Z335J0101	140	5.5	5/16-1/2	8-13	.035/.9	1	.21
34614	Z335J1101	140	5.5	1/2-1	12-25	.050/1.3	1	.21
34615	Z335J2101	180	7.1	3/4-2 3/8	19-60	.070/1.5	1	.34
34616	Z335J3101	220	8.7	1 1/2-4	40-100	.090/2.3	1	.54
34617	Z335J4101	305	12.0	3.5-5.5	85-140	.126/3.2	1	.90





Precision Machined To Hold Rings Securely

Saves Time & Money

Improves Productivity





MagicTip 90° Angle Safety Ring Pliers - External





In Canvas Roll-Up Pouch

34651 4 Pc. Straight Safety & Standard Ring Pliers Set

Shape A & C, straight tips. Precision machined tips of Chromevanadium special tool steel. For inserting & removing retaining rings.

Item# 34651 Set Includes:	• lbs. 1.54
34609 1/2-1" / 12-25mm / tip .050	34619 3/8-1" / 10-25mm / tip .050
34610 3/4-2 3/8" / 19-60mm / tip .070	34620 3/4-2 3/8" / 19-60mm / tip .070



34609 1/2-1" / 12-25mm / tip .050 34614 90° 1/2-1" / 12-25mm / tip .050

34619 3/8-1" / 10-25mm / tip .050 34624 90° 3/8-1" / 10-25mm / tip .050

346 MagicTip Straight External Safety Ring Pliers DIN ISO 5254

Shape A, straight tips. Precision machined tips of Chrome-vanadium special tool steel. For fitting & removing external retaining rings. Soft vinyl grips.

Item		-		C	U	• Tip	-	5-3	
No.		mm	Inch	Inch	mm	Inch/mm	Pkg.	lbs.	
34618	Z344A0001	140	5.5	1/8-3/8	3-10	.035/.9	1	.20	
34619	Z344A1001	140	5.5	3/8-1	10-25	.050/1.3	1	.20	
34620	Z344A2001	185	7.3	3/4-2 3/8	19-60	.070/1.5	1	.34	
34621	Z344A3001	240	9.5	1 1/2-4	40-100	.090/2.3	1	.57	
34622	Z344A4001	300	11.8	3.5-5.5	85-140	.126/3.2	1	1.00	

346 MagicTip 90° Angled External Safety Ring Pliers DIN ISO 5254 Shape B, 90° angled tips. Precision machined tips of Chrome-vanadium special tool steel. For fitting & removing external retaining rings. Soft vinvl grips.

Item				C	C	• Tip	-		
No.		mm	Inch	Inch	mm	Inch/mm	Pkg.	lbs.	
34623	Z345A0101	140	5.5	1/8-3/8	3-10	.035/.9	1	.20	
34624	Z345A1101	140	5.5	3/8-1	10-25	.050/1.3	1	.20	
34625	Z345A2101	185	7.3	3/4-2 3/8	19-60	.070/1.5	1	.34	
34626	Z345A3101	240	9.5	1 1/2-4	40-100	.090/2.3	1	.57	
34627	Z345A4101	300	11.8	3.5-5.5	85-140	.126/3.2	1	1.00	



34653 4 Pc. Straight Safety & Standard Ring Pliers Set Shape A & C, straight tips. Precision machined tips of Chromevanadium special tool steel. For inserting & removing retaining rings. Item# 34653 Set Includes: Jbs. 1.54 34608 5/16-1/2" / 8-13mm / tip .035 34618 1/8-3/8" / 3-10mm / tip .035 34610 3/4-2 3/8" / 19-60mm / tip .070

34620 3/4-2 3/8" / 19-60mm / tip .070



34654 4 Pc. 90° Safety & Standard Ring Pliers Set Shape D & B, 90° tips. Precision machined tips of Chrome-vanadium special tool steel. For inserting & removing retaining rings.

Item# 34654 Set Inclu	des: 🖌
34613 5/16-1/2" / 8-13mm	
34615 3/4-2 3/8" / 19-60mr	n / tip .070 3

bs. 1.54 34623 1/8-3/8" / 3-10mm / tip .035 34625 3/4-2 3/8" / 19-60mm / tip .070



Wiha Pipe Wrenches Narrow Style



329 Pipe Wrenches Narrow Style / S-Jaw

S-Jaw shape angled 45°. Self clamping gripping of pipes and hex nuts at 3 points. Comfortable handle profile. Rapid adjusting nut. Hardened chrome-vanadium steel, induction hardened jaws. Safe and secure grip on pipes and hex nuts.

Item	Inch	Max. grip	maximum	53	-	
No.	Length	pipe dia.	jaw opening	lbs.	Pkg.	
32970	12.60	1	40mm (1.5")	2.4	1	
32971	16.38	1.5	55mm (2.1")	2.4	1	
32972	21.06	2	67mm (2.6")	3.9	1	

All Steel Narrow Profile Pipe Wrenches

Easy access 20% Narrower profile heads

Comfortable handle profile

Rapid adjusting nut with acme thread

Extra heavy duty hardened CV steel, induction hardened jaws

Safe and secure grip with back raked serrated jaws

Pipe Wrenches Narrow Style - 45°

329 Pipe Wrenches Narrow Style - 45°

Narrow shape angled 45°. Safe and secure grip angled jaw teeth. Comfortable handle profile. Rapid adjusting nut. Hardened chromevanadium steel, induction hardened jaws. Safe and secure grip on pipes, flat work-pieces and nuts.

Item	Inch	Max. grip	Clamping	53	-	
No.	Length	pipe dia.	range	lbs.	Pkg.	
32974	12.36	1	40mm (1.5")	1.8	1	
32975	16.77	1.5	55mm (2.1")	2.1	1	
32976	22.44	2	67mm (2.6")	6.3	1	



329 Pipe Wrenches Narrow Style - 90°

Narrow shape angled 90°. Safe and secure grip angled jaw teeth. Comfortable handle profile. Rapid adjusting nut. Hardened chromevanadium steel, induction hardened jaws. Safe and secure grip on pipes, flat work-pieces and nuts.

Item	Inch	Max. grip	Clamping	.		
No.	Length	pipe dia.	range	lbs.	Pkg.	
32978	12.20	1	40mm (1.5")	2.2	1	
32979	16.54	1.5	55mm (2.1")	3.2	1	
32980	22.05	2	67mm (2.6")	6.0	1	



32995 3 Piece Pipe Wrench Sets

Hardened chrome-vanadium steel, induction hardened jaws. Safe and secure grip on pipes, flat work-pieces and nuts.

Item# 32995	Set Includes:	 lbs. 5.60
32970 - 12.60"	S-Jaws	32978 - 12.20" 90° Jaws
32974 - 12.36"	45° Jaws	



32996 3 Piece Narrow Style 90° Pipe Wrench Sets Narrow shape angled 90°. Safe and secure grip angled jaw teeth. Comfortable handle profile. Rapid adjusting nut.

Item# 32996	Set Includes:
32978 - 12.20"	Narrow Style 90°
32979 - 16.54"	Narrow Style 90°

, ↓ ↓ Ibs. 10.80 32980 - 22.05" Narrow Style 90°



Wiha Ratchet Crimpers



43612 Ratchet End Sleeve Crimper

Crimps Insulated & non-insulated end sleeves. 6 crimp positions range AWG 26-18, 18-16, 14, 12, 10, 8. Soft grip non-slip handles. Factory set auto release at end of crimp cycle.

Item		Inch	AWG			
No.		Length	Range	lbs.	Pkg.	
43612	Z62000106	220mm/8.6"	26-8	1.18	1	1,112



Ratchet Crimper Push On Terminals 43624

Crimps Insulated & non-insulated terminals. 4 crimp positions range AWG 22-20, 20-16, 16-14, 12-10. Soft grip non-slip handles. Factory set auto release at end of crimp cycle.

Item		Inch	AWG	÷.+	-
No.		Length	Range	lbs.	Pkg.
43624	Z62000306	220mm/8.6"	22-10	1.06	1



43618 Ratchet Crimper For Standard Connectors

Crimps Insulated & non-insulated connectors. 3 crimp positions range AWG 20-16 red, 16-14 blue, 12-10 yellow. Soft grip non-slip handles. Factory set auto release at end of crimp cycle.

Item		Inch	AWG	.	CONTRACT OF CONTRACT OF CONTRACT
No.		Length	Range	lbs.	Pkg.
43618	Z62000206	220mm/8.6"	20-10	1.06	1



43643 Ratchet Crimper For Eye Terminals

Crimps Insulated & non-insulated terminals. 4 crimp positions range AWG 26-20, 20-14, 12-10, 8-6. Soft grip non-slip handles. Factory set auto release at end of crimp cycle.

Item		Inch	AWG			
No.		Length	Range	lbs.	Pkg.	
43643	Z62000406	220mm/8.6"	26-6	1.02	1	







Made by Wiha

Wiha Industrial SoftGrip Pliers & Cutters



309 Industrial Long Nose Pliers With Cutting Edge DIN ISO 5745

Long nose pliers. Extra long cutters for flat and round wires. Gripping surfaces serrated in parts. Cutting edges additionally induction hardened to approx. 62HRC. Special tool steel. Two component SoftGrip handle.

Item			Cutting Capacity		5-3
No.	mm	Inch	AWG	Pkg.	lbs.
30911 Z05002160	160	6.3	#10	1	.41
30913 Z05002200	200	8.0	#10	1	.56





Industrial SoftGrip Long Round Nose Pliers



	S	Stripping Plie	ers	
\bigotimes		Witha Electrosic	40,0	
		2402.00 000 AWG 20-10/ 00.01 - 02.00 mm		
Prom Wina				28,9

30919 Industrial Long Flat Nose Pliers DIN ISO 5745

Inch

6.3

8.0

mm

160

200

Extra long head. Gripping surfaces serrated and induction hardened. Special tool steel. Two component SoftGrip handle. Gripping and right-angled bending of wires and sheet metal parts.

Cutting Capacity Copper AWG

#10

#10

Pkg. lbs.

1

1

.42

.57

Item			-	5-3	
No.	mm	Inch	Pkg.	lbs.	
30919 Z07002160	160	6.3	1	.43	

30921 Industrial Long Round Nose Pliers DIN ISO 5745

Extra long head. Gripping surfaces serrated and induction hardened. Special tool steel. Two component SoftGrip handle. Gripping and bending of wires and sheet metal parts.

Item			(inclusion)	.	
No.	mm	Inch	Pkg.	lbs.	
30921 Z09002160	160	6.3	1	.39	

56871 Stripping Pliers

Wide long head with ridged gripping surface, shears blade and firm wire stripping stations. With opening spring and locking mechanism. Wire stripping stations 0.81 / 1.0 / 1.3 / 1.6 / 2.0 / 2.59mm,

AWG	20 /	18/	16/	14/	12/	10

#56871	mm	Inch	Ø	AWG	Pkg.	lbs.
	180	7.0	0.81-2.59	20-10	5	.15



Made by Wiha

Wiha Industrial SoftGrip Pliers & Cutters Industrial SoftGrip Diagonal Cutters



309 Industrial Diagonal Cutters DIN ISO 5749

Low wear lap joint, riveted and able to withstand high levels of load. Low force action, clean cutting. Long life cutting edge is achieved with additional induction hardening to approx. 62HRC. Special CV tool steel forgings hardened and tempered. For soft & medium hard wire.

Item			Cutting Capacity		£.7
No.	mm	Inch	Copper AWG	Pkg.	lbs.
30923 Z12002140	140	5.5	#8	1	.45
30925 Z12002160	160	6.3	#7	1	.57
30927 Z12002180	180	7.0	#6	1	.69

Industrial SoftGrip H. Leverage Diag. Cutters

Industrial SoftGrip Cable Cutters





Semi-circular. Low wear lap joint, riveted and able to withstand high levels of load. Low force action, clean cutting. Long life cutting edges are achieved through additional induction hardening to approx. 62HRC.

309 Industrial High Leverage Diagonal Cutters DIN ISO 5749

C60 special CV tool steel hardened and tempered.

nem				Cutting Capacity			
No.		mm	Inch	AWG	Pkg.	lbs.	
30929	Z16002160	160	6.3	#6	1	.57	
30931	Z16002180	180	7.0	#6	1	.68	
30933	Z16002200	200	8.0	#6	1	.89	

309 Industrial Cable Cutters DIN ISO 5749

Energy saving & clean cutting cable cutters with specially ground precision cutting edges. Long life cutting edges are achieved through additional induction hardening to approx. 62HRC. C60 special CV tool steel hardened and tempered. Two component SoftGrip ergo handle.

Item			Cutting Capacity		÷.
No.	mm	Inch	Copper/Aluminum	Pkg.	lbs.
30926 Z50102160	160	6.3	16mm	1	.56
30928 Z50102200	200	8.0	20mm	1	.87

30937 Industrial Adjustable Pliers DIN ISO 8976

10 opening settings provides optimal adjustment to objects being gripped. Long life achieved through additional induction hardening of jaws to approx. 62HRC. Chrome-vanadium tool steel forgings, hardened and tempered. Two component SoftGrip ergonomic handle. Black finish.

Item			Capac	ities		÷.÷
No.	mm	Inch	Round	Hex	Pkg.	lbs.
30937 Z21002250	250	10.0	1 3/4"	2"	1	.94

30943 Industrial Slide Lock Adjustable Pliers - Box Joint - With Push Button Setting. DIN ISO 8976 Extra narrow head for working small spaces. Rapid and simple push button setting and locking. Long life achieved through additional induction hardening of jaws to approx. 62HRC. Finger jam protection for safe operation at all settings. CVM tool steel forgings, hardened and tempered. SoftGrip handles.

Item			Capac	ities		÷.
No.	mm	Inch	Round	Hex	Pkg.	lbs.
30943 Z22025005	250	10.0	1 3/4"	2"	1	.95



ComfortGrip Slide Lock Adjustable Pliers

With box joint

GS Rapid adjust

- · Close to lock
- · Open and slide to adjust opening size
- Audible click at each locking position

32969 Slide Lock Adjustable Pliers - Wiha QuickFix - Box Joint DIN ISO 8976 Super fast and easily adjusted pliers. Long durability achieved through additional induction hardening of jaws to approx. 56 HRC. Finger jam protection for safe operation at all settings. Chrome-vanadium tool steel forgings, hardened and tempered. Chrome finish with ergonomic ComfortGrip handles.

Item			Capacities	
No.	mm	Inch	Round Hex	Pkg. Ibs.
32969 Z23025005	250	10.0	1 1/4" 1 1/2"	1 .80

Industrial SoftGrip Pliers & Cutters Sets



30993 3 Piece Industrial SoftGrip Pliers & Cutters Set

Maximum comfort in daily use, smooth operation and optimum force transmission without uncomfortable pressure points. Cutters additionally induction hardened. Anti-slip soft dual material handles for safe gripping, ergonomic shape for maximum user comfort.

Item# 30993 Set Includes:	
30905 Combination Pliers - 8.0"	
30925 Diagonal Cutters - 6.3"	
30911 Long Nose Pliers - 6.3"	





5-2 lbs. 1.76

30990 4 Piece Industrial SoftGrip Pliers & Cutters Set

Maximum comfort in daily use, smooth operation and optimum force transmission without uncomfortable pressure points. Cutters additionally induction hardened. Anti-slip soft dual material handles for safe gripping, ergonomic shape for maximum user comfort.

Item# 30990 Set Includes:

GS

9.0" - Heavy Duty Combination Pliers	
8.0" - Long Nose Pliers	
8.0" - High Leverage Diagonal Cutters	lbs.
7.0" - ComfortGrip Stripping Pliers	2.81



Industrial SoftGrip Pliers & Cutters Sets



Made by Wiha



30998 8 Piece Industrial SoftGrip Pliers & Cutters Set Maximum comfort in daily use, smooth operation and optimum force transmission without uncomfortable pressure points. Cutters additionally induction hardened. Anti-slip soft dual material handles for safe gripping, ergonomic shape for maximum user comfort.

Item# 30998 Set Includes:

6.3" - Combination Pliers

9.0" - Heavy Duty Combination Pliers	
6.3" - Long Nose Pliers	\$~\$
8.0" - Long Nose Pliers	lbs.
5.5" - Diagonal Cutters	4.91
8.0" - High Leverage Diagonal Cutters	
10.0" - Adjustable Pliers	
7.0" - ComfortGrip Stripping Pliers	



30991 18 Piece Industrial SoftGrip Pliers/Cutters, Screwdrivers & Wrenches Set Maximum comfort in daily use, smooth operation and optimum force transmission without uncomfortable pressure points. Cutters additionally induction hardened. Anti-slip soft dual material handles for safe gripping, ergonomic shape for maximum user comfort.

Item# 30991 Set In	cludes:	
8.0" - Combination Pl	iers	
6.3" - Long Nose Plie	rs	
6.3" - Diagonal Cutte	rs	
10.0" - Adjustable Pli	ers	lbs.
Slotted: 5/32, 1/4"	Phillips: 1, 2	6.76
Torx: T15, T20, T25	Square: 1, 2	
Wrenches: 1/4"x5/16'	', 3/8x7/16", 1/2x9/16", 3/4x7/8"	



Wiha Precision Electronic Pliers & Cutters







Full Flush





10	For an ab	solutely	flush cu	ut of copper wire.
13.5	#56818	mm	Inch	Cut Capacity
5.0	£	138	5.5	1.3mm/16AWG
ull Flush				

mm Inch

#56815

56815 Precision	Electronic Diago	onal Cutters, Wide Pointed Head
Cutting edge - sem	i flush. With retur	n spring. C70 special tool steel.
Universal small dia	gonal cutter for cu	itting copper wires.
Item No.	Cut	Medium

Capacity

138 5.5 2.0mm/12AWG

56818 Precision Electronic Diagonal Cutters, Wide Pointed Head Cutting edge - full flush. With return spring. C70 special tool steel.

Pkg.

5

Hard Wire

0.8

lbs.

.22

Pkg. lbs.

5

.23

Semi Flush



Electronic Diagonal Cutters



56825	Precisi	on Elec	tronic Diagonal Cu	utters, W	/ide Shape With
Wire Ho	Iding Sp	oring W	ide, Pointed head.	Cutting	edge - full flush.
With retu	ırn sprin	g & fixtu	re for holding ends	of wires	that have been cut
off. C70	special	tool stee	el. For an absolutel	y flush c	ut of copper wire.
#56825	mm	Inch	Cut Capacity	Pkg.	lbs.
	138	5.5	1.3mm/16AWG	5	.23

Full Flush

56812 Precision Elec	tronic Diagonal Cu	utters, Narrow Shape
Extra narrow, short head	I for working in parti	cularly restricted spaces.
Cutting edge - full flush.	With return spring.	C70 special tool steel. Fo
absolutely flush cutting c	of copper wires in dif	fficult to access locations.

#56812	mm	Inch	Cut Capacity	Pkg.	lbs.
	118	4.5	0.8mm/20AWG	5	.19

Full Flush

121





Full Flush

56813 Precision Electronic Diagonal Full Flush Cutters With Wire Trapping Spring Extra narrow, short head for working in particularly restricted spaces. Cutting edge - full flush. With return spring. C70 special tool steel. For absolutely flush cutting of copper wires in difficult to access locations.

#56813	mm	Inch	Cut Capacity	Pkg.	lbs.	
	128	5.0	1.0mm/18AWG	5	.19	





Full Flush

56833 Electronic Oblique 48° Cutter

Wide pointed head. Cutting edge - full flush. With cutting edge at 48° for cutting obliquely from above or from the side. C70 special tool steel. For absolutely flush cutting of copper wires in difficult to access locations.

#56833	mm	Inch	Cut Capacity	Pkg.	lbs.
	138	5.5	1.3mm/16AWG	5	.22



56830 Electronic Narrow 30° Front Cutter / Long Nose Pliers Extremely narrow, short head for working in particularly restricted spaces. Cutting edge - full flush. Edge at 30° to face end of pliers for cutting obliquely from above or form the side. C70 special tool steel. For absolutely flush cutting of copper wires in difficult to access locations. #56830 mm Inch **Cut Capacity** 118 4.5 0.6mm/22AWG

Ele	ectror	nic Po	pinted P	liers
×			Wiba Electronic	
W	_	96	1	
	()	-		
	-			- Contractor



56801 Electronic Short Nose Precision Pliers

Narrow, short head. Smooth jaws. Width at tip is only 1.2mm. C70 special tool steel. For holding small components as well as for holding and angling wires.

	138	5.5	5 F	00	
#56801	mm	Inch	Pkg.	lbs.	

Pkg.

5

lbs.

.19





56871 Electronic Stripping Pliers

Wide long head with ridged gripping surface, shears blade and firm wire stripping stations. With opening spring and locking mechanism. Wire stripping stations 0.81 / 1.0 / 1.3 / 1.6 / 2.0 / 2.59mm, AWG 20 / 18 / 16 / 14 / 12 / 10.

#56871	mm	Inch	Ø	AWG	Pkg.	lbs.	
	180	7.0	0.81-2.59	20-10	5	.15	



Two component handle with non-slip life & endurance, mirror soft grip surface, polished finish protects the hand and reduces manual effort & user fatigue ESD standard IEC 61340-5-1 Semi-Flush Cutter **Beveled Cutter** Welded double leaf spring Hardened & annealed high carbon tool Ultra Full Flush Flush Cutter steel, induction hardened cutting edges Precision Cutters Tapered Head 32703 Precision Cutters, Small Tapered Head, Semi Flush Cutters drop-forged for an ideal material structure. Precise aligned 9.5mm cutting edges are additionally induction hardened at a hardness of Approx. 64ºHRC. Two component non-slip soft grip handle, ESD Safe Dissipative. ESD standard IEC 61340-5-1 5mm #32703 Inch Copper Head Wdth Pkg. lbs. mm 115 4.5 1.0 9.5mm 1 .19 115mm **Precision Cutters Tapered Head** 32705 Precision Cutters, Small Tapered Head, Flush Cutters drop-forged for an ideal material structure. Precise aligned 9.5mm cutting edges are additionally induction hardened at a hardness of Approx. 64ºHRC. Two component non-slip soft grip handle, ESD Safe Dissipative. ESD standard IEC 61340-5-1 6.0mm #32705 mm Inch Copper Head Wdth Pkg. lbs. 115 4.5 1.0 9.5mm 1 .19 115mm

Ground Back, Semi Flush

mm

115

Inch

4.5

5mm

#32702



Semi Flush

Flush

10



32704 Precision Cutters, Small Tapered Head With Hollow Ground Back, Flush

Copper Head Wdth

9.5mm

Pkg.

1

lbs. .19

32702 Precision Cutters, Small Tapered Head With Hollow

9.5mm Cutters drop-forged for an ideal material structure. Precise aligned cutting edges are additionally induction hardened at a hardness of Approx. 64ºHRC. Two component non-slip soft grip handle, ESD Safe Dissipative. ESD standard IEC 61340-5-1

1.0

9.5mm Cutters drop-forged for an ideal material structure. Precise aligned cutting edges are additionally induction hardened at a hardness of Approx. 64ºHRC. Two component non-slip soft grip handle, ESD Safe Dissipative. ESD standard IEC 61340-5-1

#32704	mm	Inch	Copper	Head Wdth	Pkg.	lbs.
	115	4.5	1.0	9.5mm	1	.19

WW\ Wiha ESD Safe Pliers & Cutters	w.wihatools.com
Precision Cutters Wide Tapered Head Bevel	32706Precision Cutters, Wide Tapered Head, BevelCutters drop-forged for an ideal material structure. Precise alignedmcutting edges are additionally induction hardened at a hardness ofApprox. 64°HRC. Two component non-slip soft grip handle,ESD Safe Dissipative. ESD standard IEC 61340-5-1m#32706mmInchCopperHead WdthPkg.Ibs.1154.51.411.0mm1.20
Precision Cutters Wide Tapered Head	Approx. 64°HRC. Two component non-slip soft grip handle, ESD Safe Dissipative. ESD standard IEC 61340-5-1

Precision Cutters Wide Tapered Head		32710	Precis	ion Cu	itters, Wid	de Tapered He	ead, Ful	Flush	
Full Flush	Support 11 ()mm					aterial structur		100 X	
T dill T tdisti	*	cutting ed	-			uction hardene			
		and the second second				nt non-slip soft	· ·	dle,	
		ESD Safe	Dissip	ative.	ESD stand	dard IEC 6134	0-5-1		
	7.5mm	#32710	mm	Inch	Copper	Head Wdth	Pkg.	lbs.	
			115	4.5	1.0	11.0mm	1	.23	
D < 115mm >									







Wiha ESD Safe Pliers & Cutters

Precision Cutters Slim Oval Form	\$	32714			And a second reason of the second	im Oval Head,			
Full Flush	A					naterial structur			
Professional ESD	9.5mm	cutting ed	ges ar	e addit	ionally ind	uction hardened	d at a ha	dness of	
		Approx. 6	4°HRC	C. Two	componer	nt non-slip soft	grip hand	lle,	
	4	ESD Safe	Dissip	oative.	ESD stand	dard IEC 61340)-5-1		
	6.0mm	#32714	mm	Inch	Copper	Head Wdth	Pkg.	lbs.	
	*		115	4.5	1.0	10.0mm	1	.23	
D 115mm									



		32716
A DECK	▲	Cutters of
	n1.5mm	cutting e
	V	Approx.
		ESD Sa
Co L	7.5mm	#32716

Precision Cutters, Wide Oval Head, Bevel drop-forged for an ideal material structure. Precise aligned edges are additionally induction hardened at a hardness of 64ºHRC. Two component non-slip soft grip handle, fe Dissipative. ESD standard IEC 61340-5-1 mm Inch Copper Head Wdth Pkg. lbs. 11.0mm 115 4.5 1.4 1 .19

Precision C	utters Wide Oval Form	
Flush	150	
	you Provide a	
\/ ←	115mm >	

		32720	Precis	ion Cu	itters, Wid	le Oval Head,	Flush		
		Cutters di	op-forg	ed for	an ideal m	aterial structure	e. Prec	ise aligned	
	11.5mm	cutting ed	ges are	additi	onally indu	iction hardened	d at a ha	ardness of	
/		Approx. 6	4ºHRC.	Two	componen	t non-slip soft	grip har	ndle,	
		ESD Safe	Dissipa	ative.	ESD stand	lard IEC 61340)-5-1		
.0	↑ 7.5mm	#32720	mm	Inch	Copper	Head Wdth	Pkg.	lbs.	
	*		115	4.5	1.2	11.0mm	1	.19	- 0.14





	32718	Precision Cutters, Wide Oval Head Ca	rbide
	Cutting	Edges, Bevel	
١	Cutters of	lrop-forged for an ideal material structure.	Precise

4 3/8 1.6

110

aligned carbide cutting edge. Two component non-slip soft grip handle, ESD Safe Dissipative. ESD standard IEC 61340-5-1 Pkg. #32718 mm Inch Copper Head Wdth lbs.

11.0mm

1

.20

Precision Cutt	ters Wide Oval Form	
Flush		
	Was freeman b	
D .	—— 115mm ———— 🕨	

e	32721	Precis	sion Cu	utters, Wic	le Oval Head \	Nith Wi	re
▲	Trapping						
11.0mm بل	Cutters di	op-for	ged for	an ideal m	aterial structure	e. Preci	se aligned
V					ction hardened		
	Approx. 6	4ºHRC	. Two	componen	t non-slip soft g	grip han	dle,
↑ 7.5mm	ESD Safe Dissipative. ESD standard IEC 61340-5-1						
	#32721	mm	Inch	Copper	Head Wdth	Pkg.	lbs.
		115	4.5	1.2	11.0mm	1	.23

www	wihatools.com
	Premium Tools
Wiha ESD Safe Pliers & Cutters	
Oblique Angled Cutters	32722 Oblique Angled Cutters, 29°, FlushOblique Cutters drop-forged for an ideal material structure. Precisealigned cutting edges are additionally induction hardened at a hardnessof Approx. 64°HRC. Two component non-slip soft grip handle,ESD Safe Dissipative. ESD standard IEC 61340-5-1#32722mmInchCopperHead WdthPkg.Ibs.1154.51.212.0mm1.24
Oblique Angled Cutters Ultra Full Flush	32724 Oblique Angled Cutters, 29°, Full FlushOblique Cutters drop-forged for an ideal material structure. Precisealigned cutting edges are additionally induction hardened at a hardnessof Approx. 64°HRC. Two component non-slip soft grip handle,ESD Safe Dissipative. ESD standard IEC 61340-5-1#32724mmmmInchCopperHead WdthPkg.Ibs.1154.51.012.0mm1.24
Oblique Angled Cutters Semi Flush	32726Oblique Angled Cutters, 29°, Short Head, Semi FlushOblique Cutters drop-forged for an ideal material structure. Precise aligned cutting edges are additionally induction hardened at a hardness of Approx. 64°HRC. Two component non-slip soft grip handle, ESD Safe Dissipative. ESD standard IEC 61340-5-1#32726mmInchCopperHead WdthPkg.Ibs.1154.51.212.0mm1.24
Oblique Front Cutters Flush	32728Oblique Front Cutters, Very Small Head, 40°, FlushOblique Cutters drop-forged for an ideal material structure. Precisealigned cutting edges are additionally induction hardened at a hardnessof Approx. 64°HRC. Two component non-slip soft grip handle, ESDSafe Dissipative. ESD standard IEC 61340-5-1#32728mmInchCopperHead WdthPkg.Iso5.10.68.5mm1.21
ESD Safe Tool Set In Canvas Pouch	32793 11 Piece Set, 4 ESD Safe Pliers, Slotted & PhillipsScrewdriversPliers drop-forged for an ideal material structure.Two component non-slip soft grip handle. ESD standard IEC 61340-5-1#32793 11 piece ESD Safe Pliers & Slotted/Phillips Precision Drivers Set in custom case includes:ESD Safe Pliers & Cutters32705 4.5" Tapered Flush Cutters32742 4.5" Snipe Nose Pliers32728 4.375" Oblique Cutters32746 5.7" Long Nose PliersESD Safe Screwdrivers27220 Slotted 2.0mm

27225 Slotted 2.5mm 27230 Slotted 3.0mm

27235 Slotted 3.5mm

.....

27305 Phillips #00 27310 Phillips #0 27320 Phillips #1



Toll Fr<mark>ee: (800) 494-6104</mark>

Wiha ESD Safe Pliers & Cutters

End Cutters Extra Slim	Tip Width	32732	End Cu	utters, E	Extra Slim	, Semi Flush	n ×		
Semi Flush	7.0mm			1073		I material str			0.0573
The Protocol ED	V.omm	-	Č			tion hardened			of
		2000-00				non-slip soft	-	dle,	
	A A	ESD Safe	Dissipa	ative. E	SD standa	rd IEC 61340)-5-1		
	2.9mm 6.0mm	#32732	mm	Inch	Copper	Tip Wdth	Pkg.	lbs.	
	*	· · · · · · · · · · · · · · · · · · ·	130	5.1	0.6	4.1mm	1	.16	
D 4 130mm									

End Cutter	s Wide Head
Flush	
8 ×0	uns tratement too
	-115mm

0	11.5mn ♥
16.5mm	7.5mm

32734	End C	utters,	Wide Hea	id, Flush		
End Cutt	ers drop	-forgeo	l for an ide	al material stru	icture.	Precise aligned
cutting e	dges are	additio	onally indu	ction hardened	l at a ha	ardness of
Approx.	64°HRC.	Two	componen	t non-slip soft g	grip han	ndle,
ESD Saf	e Dissipa	ative. I	ESD stand	ard IEC 61340	-5-1	
#32734	mm	Inch	Copper	Head Wdth	Pkg.	lbs.
	115	4.5	1.4	11.0mm	1	.18





	32742	ESD Safe P	liers, S	hort Snipe Nose	(Chain	Nose)
A	Straight,	Serrated Ja	ws			
mm	Pliers dro	op-forged for	an ideal	material structure.	Preci	isely aligned,
1	jaws, har	dened. Two	compor	nent non-slip soft g	rip han	dle,
	ESD Safe	e Dissipative.	ESD s	tandard IEC 61340)-5-1	
n mm	#32742	mm	Inch	Head Wdth	Pkg.	lbs.
1		120	4 3/4	9.5mm	1	20



	32744	ESD Safe	Pliers,	Snipe Nose (Ch	ain Nos	e)
A	Bent 45°,	Smooth	Jaws			
т 9.5mm	Pliers drop	-forged fo	or an idea	al material struct	ure. Pre	cisely aligned,
*	jaws, harde	ened. Tw	o compoi	nent non-slip sof	t grip ha	ndle,
	ESD Safe	Dissipativ	/e. ESD	standard IEC 61	340-5-1	
6.5mm	#32744	mm	Inch	Head Wdth	Pkg.	lbs.
¥ I		120	4 3/4	9.5mm	1	.20



	32746	ESD Safe	e Pliers,	Long Needle No	se Pliers	з,	
	Straight,	Serrated	Jaws				
mm	Pliers dro	op-forged f	or an idea	al material structu	re. Prec	isely alig	jned,
jaws, hardened. Two component non-slip soft grip handle,							
(ESD Safe	e Dissipativ	ve. ESD	standard IEC 613	340-5-1		
nm	#32746	mm	Inch	Head Wdth	Pkg.	lbs.	
1		145	5 3/4	12.0mm	1	.27	



Wiha ESD Safe Pliers & Cutters **ESD Safe Pliers** Needle Nose, Bent 90° A * 10 7.5mm 145mm

32748 ESD Safe Pliers, Needle Nose Pliers, Bent 90°, **Smooth Jaws** 12.0mm Pliers drop-forged for an ideal material structure. Precisely aligned, jaws, hardened. Two component non-slip soft grip handle, ESD Safe Dissipative. ESD standard IEC 61340-5-1

	#32748	mm	Inch	Head Wdth	Pkg.	lbs.	
1	#32140		mon	neau wuin	FKg.	ibs.	
		145	5 3/4	12.0mm	1	.21	



32750 ESD Safe Pliers, Short Round Nose Pliers, **Smooth Jaws** Pliers dron-forged for an ideal material structure. Precisely aligned

Fliers drop-h	orgeu ior	an luear	material structur	e. Fieus	sely aligheu,	
jaws, harder	ned. Two	compon	ent non-slip soft	grip hand	dle,	
ESD Safe D	issipative.	ESD st	andard IEC 613	40-5-1		
#32750	mm	Inch	Head Wdth	Pkg.	lbs.	
	120	4 3/4	9.5mm	1	.17	



32752	ESD	Safe	Pliers,	Short	Flat	Nose	Pliers	,
Smooth	Jaws							
		1.4						

Pliers drop-fo	orged for	an ideal i	material structure	e. Precis	sely aligned,	
jaws, harden	ed. Two	compone	ent non-slip soft	grip hand	dle,	
ESD Safe Di	ssipative.	ESD sta	andard IEC 6134	10-5-1		
#32752	mm	Inch	Head Wdth	Pkg.	lbs.	
	120	4 3/4	9.5mm	1	.16	





32790 4 Piece ESD Safe Pliers Set In Custom Case Pliers dropforged for an ideal material structure. Two component non-slip soft grip handle. ESD Safe Dissipative. ESD standard IEC 61340-5-1

#32790 4 piece ESD Safe Pliers Set Set includes: 32716 4.5" Oval Side Cutters 32752 4.75" Flat Nose Pliers July 105. 2.06

32746 5.75" Long Nose Pliers 32728 4.375" Oblique Cutters



ESD standard IEC 61340-5-1

32791 11 Pc. Set, 4 ESD Safe Pliers, SYSTEM 4 Slotted & Phillips 5 Pc. Set & 2 ESD Safe Tweezers Pliers drop-forged for an ideal material structure. Two component non-slip soft grip handle. ESD Safe Precision handle & 4 CVM tool steel blades. Tweezers anti-static conductive, ESD Safe Hypo allergenic, anti-magnetic stainless. #32791 11 piece ESD Safe Pliers, Tweezers & SYS 4 precision

Set in custom case includes:	
ESD Safe Pliers & Cutters	
32716 4.5" Oval Side Cutters	32746 5.75" Long Nose Pliers
32752 4.75" Flat Nose Pliers	32728 4.375" Oblique Cutters
SYSTEM 4 Set in separate pouch	
28000 ESD Safe Conductive Precision Ha	andle
Slotted: 1.5, 2.0, 3.0 & 4.0	Phillips: 000, 00, 0 & 1
ESD Safe Tweezers: 44501 AA SA ESD	44510 7a SA ESD
1bs 2 43	







45810	Protu	n ES	D Safe Wire	Strippe	ər				
ESD sta	ndard I	EC 61	340-5-1. C7	0 speci	al tool s	steel.			
Glare fre	e, blac	k finis	h. ESD Safe	handle	with no	on-slip	grips		
Strips 0.3	2, 0.3,	0.4, 0.	.5, 0.6, 0.8mr	n					
#45810	mm	Inch	Strips AWG	А	В	С	Pkg.	lbs.	
	165	6.5	30 to 20	30mm	12mm	4mm	1	.25	





45811	Protur	n ESD :	Safe Lo	ng Nose	Pliers			
ESD star	ndard IE	EC 6134	40-5-1.	C70 spe	cial tool	steel.		
Glare fre	e, black	c finish.	ESD S	afe hand	le with n	on-slip g	rips.	
#45811	mm	Inch	А	В	С	Pkg.	lbs.	
	160	6.3	2mm	30mm	3mm	1	.18	



45812	Proturi	n ESD S	Safe Fla	t Nose S	mooth	Jaws P	liers	
ESD stan	dard IE	C 6134	0-5-1. (C70 spec	ial tool s	steel.		
Glare free	e, black	finish.	ESD Sa	afe handl	e with ne	on-slip g	grips.	
#45812	mm	Inch	А	В	С	Pkg.	lbs.	
	160	6.3	2mm	32mm	3mm	1	.18	


Wiha ESD Safe Proturn Pliers & Cutters

Surface resistance of handles is 10° - 10° Ohms







45813 Proturn ESD Safe Bent Nose Pliers ESD standard IEC 61340-5-1. C70 special tool steel. Glare free, black finish. ESD Safe handle with non-slip grips. #45813 mm Inch В C Pkg. lbs. Α 152 6.0 2mm 30mm 4mm 1 .18



45814 Proturn ESD Safe Round Nose Pliers ESD standard IEC 61340-5-1. C70 special tool steel. Glare free, black finish. ESD Safe handle with non-slip grips. #45814 mm Inch A B С Pkg. lbs. 152 6.0 2mm 22mm 3mm 1 .17





45820 Proturn ESD Safe 21° Precision Cutters/Flush Cut ESD standard IEC 61340-5-1. C70 special tool steel. Glare free, black finish. ESD Safe handle with non-slip grips. #45820 mm Inch AWG A В C Pkg. lbs. 127 5.0 18/1mm 13mm 12mm 3mm 1 .16





45821 Proturn ESD Safe 45° Precision Cutters/Flush Cut ESD standard IEC 61340-5-1. C70 special tool steel. Glare free, black finish. ESD Safe handle with non-slip grips. #45821 mm Inch AWG A C Pkg. lbs. В 5.0 18/1mm 10mm 9mm 2mm 1 .14 127





45822 Proturn ESD Safe 21° Precision Cutters/Flush Cut ESD standard IEC 61340-5-1. C70 special tool steel. Glare free, black finish. ESD Safe handle with non-slip grips. #45822 mm Inch AWG A C Pkg. lbs. В 140 5.5 16/1.3mm 13mm 12mm 3mm 1 .15



Toll Free: (800) 494-6104



Wiha ESD Safe Proturn Pliers & Cutters

Surface resistance of handles is 106 - 109 Ohms



45890 26 Pc. Set, Proturn ESD Safe Pliers, Precision Slotted & Phillips Screwdrivers, Precision Micro Bit Set & ESD Safe Tweezers ESD Proturn Pliers glare free, black finish, ESD Safe non-slip soft grips. ESD Safe Precision Slotted & Phillips screwdrivers, CVM tool steel blades. Precision ESD Safe Micro Bit handle holds Micro Bit extension and 4mm Micro bits. Anti-static Tweezer conductive, ESD Safe Hypo allergenic, anti-magnetic stainless.

#45890 26 Piece ESD Safe Pliers, Precision Screwdrivers, Micro Bit Set & ESD Tweezer In Custom Case Includes:

ESD Safe Proturn Strippers, Pliers & Cutters

45810 - 6.5" Wire Stripper	45811 - 6.3" Long Nose Pliers
45813 - 6.0" Bent Nose Pliers	45823 - 5.25" 21° Precision Cutters
ESD Safe Slotted & Phillips Pre-	cision Screwdrivers
Slotted: 2.0, 2.5, 3.0mm	Phillips: 0, 1
ESD Micro Bit Handle, Micro Bit	Extension & 14 Micro Bits 4mm
Hex: .7, .9, 1.3, 1.5, 2.0, 2.5, 3.0	Torx: T4, T5, T6, T7, T8, T9, T10
ESD Safe Tweezer: 44532 00 SA	ESD - 120mm Heavy Duty Strong,
Tapered To Strong Point	
↓ ↓ Ibs. 2.05	

45823Proturn ESD Safe 21° Precision Cutters/Flush CutESD standard IEC 61340-5-1.C70 special tool steel.Glare free,black finish.ESD Safe handle with non-slip grips.#45823mm InchAWGABC1335.2514/1.6mm10mm10mm1.14

45824Proturn ESD Safe 45° Precision Cutters/Flush CutESD standard IEC 61340-5-1. C70 special tool steel. Glare free,
black finish. ESD Safe handle with non-slip grips.#45824mm Inch AWG A B C Pkg. lbs.
140 5.5 14/1.6mm 13mm 12mm 2.5mm 1 .16

Wiha Canvas Pouches



91201	Roll-Up I	Pouch Wih	a canvas	roll-up pouch has 8 pockets
Item	Width	Height		
No.	Size	Size	lbs.	pkg.
91201	26.75	x 16.5	.60	1



91205 Belt Pack Pouch

Wiha canvas belt pack pouch holds 3 Pliers & 2 Screwdrivers

Item	Width	Height	£.\$		
No.	Size	Size	lbs.	pkg.	
91205	5.25 x	9.5	.19	1	









Each die includes storage clip







- Top Quality: 50,000 cycle tested frame for longest life & consistent performance
- Reliable: Parallel, full cycle, ratchet controlled action ensures consistent accurate crimps
- · Easy To Use: Designed to give user full visibility of the crimping process
- · Versatile: Quickly and easily inter-change crimp dies on the job
- No More Lost Die Parts! Practical design uses guide pin to keeps die components together
- · Practical: Pocket size dies are compact & easy to carry
- Ergonomic: Reduced effort ratchet assisted crimping use one hand or two with extended grip
- · Economical: One tool frame to do the job of many, select only the dies you need

PortaCrimp Tool Sets



43190 4 Piece PortaCrimp Die Set Electrical

Reliable,	ratchet controlled, ensures consiste	ent and ac	curate crimp.
Item		.	
No.	Set includes: Tool frame &	lbs.	Pkg.
43190	43129, 43128, 43142	5.0	1



43191 4 Piece PortaCrimp Die Set Industrial

Reliable, ratchet controlled, ensures consistent and accurate crimp.

Item		£.5	
No.	Set includes: Tool Frame &	lbs.	Pkg.
43191	43129, 43127, 43147	5.0	1



43192 4 Piece PortaCrimp Die Set Data Com Telco

Reliable, ratchet controlled, ensures consistent and accurate crimp.

	* *		
Set includes: Tool Frame &	lbs.	Pkg.	
43144, 43136, 43132	5.0	1	
	and an and the state and an and	when well all places measures	

39



Toll Free: (800) 494-6104

PortaCrimp Dies

One piece die, held together to prevent mix up & loss. Easily interchangeable crimp dies are kept together with a special pin to simplify handling. Reliable crimping performance is consistent and accurate with a parallel action stroke, good to 50,000 cycles.





43128 PortaCrimp Die Set For Green & Yellow Insulated **Terminals & Splices**

Item			£.\$	Constant P
No.	Crimps	AWG	lbs.	Pkg.
43128	4-6 & 0.1-0.4mm ²	26-22 & 12-10	1.2	1



43129 PortaCrimp Die Set For Red & Blue Insulated Terminals & Splices Die set for 22-14 AWG (0.5 - 2.5mm).

Item			÷.+		
No.	Crimps	AWG	lbs.	Pkg.	
43129	1.5-2.5 & 0.5-1.5mm ²	22-14	1.2	1	



43142 PortaCrimp Die Set For Non-Insulated Terminals,

Lugs & Splices

Item			53	
No.	Crimps	AWG	lbs.	Pkg.
43142	4-6 & 0.5-2.5mm ²	12-10 & 22-14	1.2	1



43137 PortaCrimp Die Set For Non-Insulated Terminals,

Lugs & Splices Item 1-2 Pkg. No. Crimps Awg bs. 2.5/1.5/0.75mm² 43137 14/16/20 1.2 1



43139 PortaCrimp Die Set For Non-Insulated Terminals,

Lugs & Splices

Item				
No.	Crimps	AWG	lbs.	Pkg.
43139	10/6/4mm ²	8/10/12	1.2	1





43127	PortaCrimp	Wire Ferrules - Insulated & Non-Insulated	
Die set f	or 24-8 AWG	(0.25-10mm).	

Item				
No.	Crimps	AWG	lbs.	Pkg.
43127	10/6/4/2.5/1-1.5/.2575mm ²	8-24	1.2	1





43153	PortaCrimp Wire Ferrules - Insulated & Non-Insulated	
Die set	for 6-4 AWG (16-25mm).	

Item			÷.+	
No.	Crimps	AWG	lbs.	Pkg.
43153	25 & 16mm ²	6 & 4	1.2	1



43154 PortaCrimp Wire Ferrules - Insulated & Non-Insulated Die set for 2-1/0 AWG (35-50mm).

Item			÷.+		
No.	Crimps	AWG	lbs.	Pkg.	
43154	50 & 35mm ²	1/0 & 2	1.2	1 -	



43146 PortaCrimp Open Barrel, Non-Insulated Standard Commercial Terminals & Lugs - .250"(6.3mm) Push On Terminals

Item			÷.*	(1999)	
No.	Crimp	AWG	lbs.	Pkg.	
43146	4-6/1.5-2.5/0.5-1.0mm ²	22-10	1.2	1	

www.wihatools.com





One piece die, held together to prevent mix up & loss. Easily interchangeable crimp dies are kept together with a special pin to simplify handling. Reliable crimping performance is consistent & accurate with a parallel action stroke, good to 50,000 cycles.



43150 PortaCrimp Open Barrel Non-Insulated Push On Terminals DIN 46247-1 .110" (2.8mm) Tab

Item			5-2	(and a second se	
No.	Crimps	AWG	lbs.	Pkg.	
43150	0.5-1.0/0.25-0.5/0.1-0.25mm ²	26-18	1.2	1	



43151 PortaCrimp Open Barrel Non-Insulated Push On Terminals DIN 46247-2 .187" (4.8mm) Tab

Item			÷.+		
No.	Crimps	AWG	lbs.	Pkg.	
43151	1.5-2.5 & 0.5-1.5mm ²	22-14	1.2	1	



43143 PortaCrimp Weather Pack Open Barrel Terminals

item					
No.	Crimps	AWG	lbs.	Pkg.	
43143	4.0-1.0mm ²	12-20	1.2	1	



43141 PortaCrimp Fiber Optic Die set for SMA, SMB, SFR, ST, SC fiber optic connectors (.178"/.213"/.151"/.128" hex)

Item			£-7	
No.	Crimps		lbs.	Pkg.
43141	4.52/5.41/3.84/3.25mm	(.178/.213/.151/.128")	1.2	1

530-318 Hot H 5 Sweet 107 0 0 0 0 107 0 0 107 0 107 0 10

43136 PortaCrimp Coaxial Network & Communications Die set for RG58, RG59, RG62AU BNC/TNC Coaxial Connectors (.213"/.255"/.068" hex).

Item	Crimps	5-2	
No.	1.69/5.41/6.48mm	lbs.	Pkg.
43136	(.213/.255/.068"hex)	1.2	1



43138 PortaCrimp Coaxial Network & Communications, CATV, HDTV, Video Die set for RG6, Belden 1694A, Twinax BNC, CATV F Coaxial Connectors (.360"/.324" Hex).

Item			5-2	
No.	Crimps		lbs.	Pkg.
43138	9.14 & 8.23mm	(.360/.324")	1.2	1



43140 PortaCrimp Coaxial Network & Communications Die set for RG174, RG179 BNC/TNC Coaxil Connectors

(.178"/.1	28"/.068" Hex, .028"(0.7mm)Sq.			
Item	Crimps	5-3	10000	
No.	4.52/3.25/1.69mm hex 0.7mm sq.	lbs.	Pkg.	
43140	(.178"/.128"/.068" hex028" sq.)	1.2	1	



43144 PortaCrimp Datacom/Telecom Modular Plug Die set for 8-position 8-contact (BJ45).

ltem		÷.*	
No.	RJ45	lbs.	Pkg.
43144		1.2	1



IC



43132 PortaCrimp Datacom/Telecom Modular Plug

Die set for 6-position 6-contact (RJ11).

Item		£.5	Ciscular, P	
No.	RJ11	lbs.	Pkg.	
43132		1.2	1	-



43147 PortaCrimp Power Contacts

Item				
No.	Crimps	AWG	lbs.	Pkg.
43147	4 / .14-1 / 2.5 / 1.5mm	26-12	1.2	1



43148 PortaCrimp Power Contacts

ntem			
No.	Crimps	AWG	
43148	6 & 10mm	10-8	



2

lbs.

1.2

Pkg.

1

43158 PortaCrimp Die set for heat shrink connectors: 0.5-1.5mm2 red & 1.5-2.5mm2 blue. Item Crimps

No.	0.5-1.5mm ² (22-16AWG) red	lbs.	Pkg.	
43158	1.5-25mm ² (16-14 AWG) blue	1.2	1	



43162 PortaCrimp Die set for heat shrink connectors: 4-6mm² yellow & 0.32-0.75mm² green.

Item	Crimps	÷.+	Concession of the local division of the loca
No.	4-6mm ² (12-10AWG) yellow	lbs.	Pkg.
43162	0.32-0.75mm ² (22-18AWG) green	1.2	1





43652 Crimping Tool Frame Parallel action ratchet crimp tool designed to provide the best crimp without compromise on modular plug terminals. Ratchet action to ensure full crimp cycle with safety release.

#43652			🖅 lbs. 🛑 Pkg.	
	200	7.87	1	



43654 Tool Die D-RJ11 Item no. Ibs. Pkg. 43654 1.0 1 Crimps: 6/6, 6/4 RJ11



43657 Crimping Tool Die D-RJ45U (universal) Item no. Ibs. Pkg. 43657 1.0 1 Crimps: 8/8, 8/6, 8/4, Universal RJ45 (Primary strain relief punch only)



43655 Tool Die D-RJ22 Item no. Ibs. Pkg. 43655 1.0 1 Crimps: 4/4, 4/2 RJ22



43658 Crimping Tool Die D-MMJ (DEC) Pkg. lbs. Item no. 43658 1.0 1 Crimps: 6 pos. DEC/6



43656 Tool Die D-RJ45 Item no. Ibs. Pkg. 43656 1.0 1 Crimps: 8/8, 8/6, 8/4 RJ45 (Primary & secondary strain relief punches)



43659 Tool Die D-10POS Pkg. Item no. lbs. 43659 1.0 1 Crimps: 10 pos.

www.wihatools.com



Premium

43632 Non-Insulated Crimping Tool For Non-insulated terminals, lugs, wire splices and solid/standard wires ranging from 0.75 - 6.0mm². Ratchet action to ensure full crimp cycle with safety release. Factory set for precise crimping to guarantee performance.

#43632	mm	Inch	AWG	-	➡ lbs.	Pkg.	
	255	10.0	22 - 10 (0.75-6.0mm ²	²)	1.2	1	

43622 UnInsulated Ergonomic Open Barrel Crimping Tool Precision ratchet crimp tool designed to provide consistent & reliable crimp connections on uninsulated open barrel connectors terminals on wires ranging from 0.5 - 6.0mm². Ratchet action to ensure full crimp

10.0 22 - 10 (0.5-6.0mm²)

cycle with safety release. Factory set for precise crimping to guarantee

lbs.

1.2

Pkg.

1

50,000 Cycle Rated

performance. #43622 m

50,000 Cycle Rated

mm Inch AWG

255



0

Die Profile

5 die nests side entry

crimp

43611	Insula	ted &	UnInsulated Ergonom	ic End	Splices/Ferrules
Crimping	Tool	Precisi	on ratchet crimp tool de	signed	to provide
consisten	t & relia	ble cri	mp connections on wire	s rangi	ng from 0.5 -
6.0mm².	Ratche	t actior	n to ensure full crimp cy	cle with	safety release.
Factory s	et for pi	recise	crimping to guarantee p	erforma	ince.
#43611	mm	Inch	AWG	lbs.	Pkg.
	212	8.35	20 - 10 (0.5-6.0mm ²)	1.3	1

50,000 Cycle Rated



43619	Insula	ted &	Uninsulate	ed Ergonomi	c End	Splices/Ferrules
Crimping	Tool	Precisi	on ratchet	crimp tool de	signed	to provide
consistent	t & relia	ble cri	mp connec	tions on end	splices	/ferrules
terminals	on wire	s rang	ing from 4.	0 - 10.0mm².	Ratch	et action to ensure
0-0-0-0-0-0-0-0-0-0-0-0-0-0-0-0-0-0-0-			•	e. Factory set	t for pre	ecise crimping to
guarantee	perfor	mance	•			
#43619	mm	Inch	AWG		lbs.	Pkg.

#43019	111111	mon	AWG	105.	FKg.	
	255	10.0	12 - 8 (4.0-10.0mm ²)	1.2	1	
50 000 Cvc	le Bater	4				

50,000 Cycle Rated



43620	Insula	ted &	Uninsulated Ergonom	ic End	Splices/Ferrules
Crimping	Tool	Precisi	on ratchet crimp tool de	signed	to provide
consistent	& relia	ble cri	mp connections on end	splices	/ferrules
terminals	on wire	s rang	ing from 10.0 - 25.0mm	² . Ratc	het action to
ensure ful	l crimp	cycle	with safety release. Fac	ctory se	t for precise
crimping t	o guara	antee p	erformance.		
#43620	mm	Inch	AWG	lbs.	Pkg.
	255	10.0	6 - 4 (10.0-25.0mm ²)	1.2	1

50,000 Cycle Rated



Non-Insulated Crimping Tool

Self adjust-

crimp

ing side entry Die Profile



Toll F<mark>ree: (800) 494-6104</mark>

Ergonomic End Splices/Ferrules Crimping Tool







Ergonomic Coaxial Crimping Tool



Ergonomic Coaxial Crimping Tool







43621	Insula	ted &	UnInsulate	d Ergono	mic End	Splices/Fe	rrules
Crimpin	g Tool	Precisi	on ratchet c	rimp tool	designed	to provide	
consiste	nt & relia	ble cri	mp connect	ions on er	nd splices	/ferrules	
terminals	s on wire	s rang	ing from 35	.0 - 50.0m	nm ² . Ratc	het action t	0
ensure f	ull crimp	cycle	with safety r	elease. F	actory se	t for precis	е
crimping	to guara	antee p	performance				
#43621	mm	Inch	AWG		lbs.	Pkg.	

255 10.0 2 - 1/0 (35.0-50.0mm²) 1.2 1 50,000 Cycle Rated

43653	Insula	ted & I	Jninsulate	d Ergonom	nic End	Splices/Ferrules
Crimpin	g Tool	Precisi	on ratchet	crimp tool d	esigned	to provide
consister	nt & relia	ble cri	mp connec	tions on end	d splices	/ferrules
terminals	on wire	s rangi	ng from 0.	5 - 6.0mm².	Ratcher	t action to ensure
full crimp guarante	1000			. Factory se	et for pre	cise crimping to
#40000		Inch	ANALO		lba	Dire

#43653	mm	Inch	AWG	lbs.	Pkg.	
	220	8.66	22 - 10 (0.5-6.0mm ²)	1.0	1	
50 000 Cvc	le Rate	d				

50,000 Cycle Rated

43614	Ergon	omic (Coaxial BNC, TNC C	rimping T	ool
Precision	ratchet	crimp	tool designed to prov	ide consis/	tent & reliable
crimp con	nection	is on B	NC, TNC coaxial cor	nnectors R	G58, RG59, RG62,
RG71, Th	innet.	Ratche	et action to ensure ful	I crimp cyc	cle with safety
release. F	actory	set for	precise crimping to g	guarantee	performance.
#43614	mm	Inch	Hex Crimp Dim.	lbs.	Pkg.

	0.00	6.48/5.41/1.69mm		
		(.255"/.213"/.068"hex)		

50,000 Cycle Rated

43613	Ergon	omic (Coaxial SMA, SMB, S	MC Crim	nping Tool
Precision	ratchet	crimp	tool designed to provid	le consis	stent & reliable
crimp con	nection	is on S	MA, SMB, SMC coaxia	al conne	ctors RG174,
RG179 A	F. Rat	chet a	ction to ensure full crim	p cycle	with safety
			r precise crimping to g		· · · · · · · · · · · · · · · · · · ·
#43613	mm	Inch	Hex Crimp Dim.	lbs.	Pkg.
	212	8.35	3.25/4.52/1.69mm	1.1	1
			(.128"/.178"/.068"hex)	

50,000 Cycle Rated

	•		oaxial BNC, TNC Crir			
Precision	ratchet	crimp t	ool designed to provide	e consis	stent & relia	ble
crimp con	nection	s on Bl	NC, TNC coaxial conne	ectors R	G58, RG8,	RG11
2.54 (PC0) & S10 (S10) S10 (S10) (S2, 1)			het action to ensure ful	0.0410.03000.000		
release.	Factory	set for	precise crimping to gu	arantee	performance	ce.
#43628	mm	Inch	Hex Crimp Dim.	lbs.	Pkg.	
" TOOLO	10002000000	10.29	5.41/10.9/2.54/1.69mm	n 1.2	1	
. 10010	261	10.20	0.41/10.0/2.04/1.00111			

50,000 Cycle Rated





43687	Ergon	omic C	oaxial Twinax CAT	/, F Crim	ping Tool	
Precision	ratchet	crimp	tool designed to provi	de consis	stent & relia	able
crimp co	nnection	s on T	winax CATV, F coaxia	al connec	tors RG6,	RG6
Quad, 16	895, Twi	nax. R	atchet action ensures	full crim	p cycle with	n safety
release.	Factory	set for	precise crimping to g	juarantee	performar	nce.
#43687	mm	Inch	Hex Crimp Dim.	lbs.	Pkg.	
	261	10.28	8.23/9.14/1.73mm	1.2	1	

(.360/.324/.068"hex)

50,000 Cycle Rated



Crimp Profile High Density Type





End Splices/Ferrules Crimping Tool



000



43615	Ergono	omic D	Sub UnInsulated/Ope	n Barr	el Crimping Tool
Precision	ratchet	crimp t	ool designed to provide	consis	tent & reliable
crimp con	nections	s on Ur	Insulated/Open Barrel,	D Sub	wires ranging
from 0.05	- 0.5mr	n². Rat	tchet action to ensure fu	II crim	o cycle with safety
release. F	=actory	set for	precise crimping to gua	rantee	performance.
#43615	mm	Inch	AWG	lbs.	Pkg.
	212	8.35	30 - 20 (0.08-0.5mm ²)	1.1	1

50,000 Cycle Rated

43617	Ergono	omic D	Sub UnInsulated/Oper	Barre	el Crimping Tool
Precision I	ratchet	crimp t	ool designed to provide	consist	tent & reliable
crimp coni	nections	s on Ur	Insulated/Open Barrel, I	D Sub	wires ranging
from 0.08	- 0.5mr	n². Rat	tchet action to ensure ful	I crimp	cycle with safety
release. F	actory	set for	precise crimping to guar	antee	performance.
#43617	mm	Inch	AWG	lbs.	Pkg.
	212	8.35	28 - 20 (0.08-0.5mm ²)	1.1	1

50,000 Cycle Rated

43647 Insulated & UnInsulated End Splices/Ferrules Crimping

Tool Precision ratchet crimp tool designed to provide consistent & reliable crimp connections on end splices/ferrules terminals on wires ranging from 0.5 - 6.0mm². Front entry for easy access within confined spaces. Ratchet action to ensure full crimp cycle with safety release. Factory set for precise crimping to guarantee performance. Two component comfort grip handle.

#43647	mm	Inch	AWG	lbs.	Pkg.	
	197	7.75	22 - 10 (0.5-6.0mm ²)	.82	1	
FO 000 0	I. Date	4	the second s			

50,000 Cycle Rated

326 Crimping Pliers DIN ISO 5743

Semi-circular profiles for secure connection between end sleeve and conductor. Long life is achieved through additional induction hardening to 64 HRC. CV 60 special tool steel hardened & tempered. Soft vinyl grips.

Item					-	<u>.</u>	
No.		mm	Inch	mm2	Pkg.	wt.	
32604	Z14560001	145	5.75	0.25-2.5	1	.29	
32605	Z18060001	180	7.0	0.25-16	1	.57	

(See other soft vinyl grip pliers & cutters on pages 16-22)



Toll Free: (800) 494-6104

Automatic Stripping Tool



Interchangeable stripping blade cassettes



Cuts & strips up to 10mm²/8 AWG - Strips PVC, THHW, TEFLON insulations



Ergonomic design with non-slip two component handles



Easy/snag free wire removal from tool - jaws stay open after strip



Cables: Conduit wire, Flex mains cable, Equipment wire,

Straight Blade

34-8 AWG



Flat modplug cable etc.

Self Adjusting Cut & Strip Tool



Hà MG 34-8 AWG



Replace	able Cassette - "	V" Blade	
	PIFE 28-12 AWG		VBC for PTFE
"V" Blade Stripping Range 0.1 - 4mm ²		28-12 AWG	

44212 Self Adjusting Cutting & Stripping Tool

Easily interchangeable stripping cassettes enables a wide range of insulations from PVC to PTFE. Light weight soft grip handle qualified for high volume production and portable/field usage.

#44212	mm	Inch	AWG	Strip Dim.	lbs.	Pkg.	
	191	7.5	34 - 8	0.02-10mm ²	.30	1	

44214 Straight Blade Cassette, PVC Insulations

Fine adjustability ensures that thin insulations can be stripped without damage to conductors. At the end of the stripping function, the stripping blades open and remain open during the return phase of the strip cycle facilitating easy/snag free wire removal from the tool.

#44214	AWG	Strip Range	lbs.	Pkg.	
	34 - 8	0.02-10mm ²	.02	1	



Replaceable Cassette, 4-16mm Stripping Range

Fine adjustability ensures that thin insulations can be stripped without damage to conductors. At the end of the stripping function, the stripping blades open and remain open during the return phase of the strip cycle facilitating easy/snag free wire removal from the tool.

#44269	AWG	Strip Range	lbs.	Pkg.	
	10 - 5	4-16mm ²	.02	1	

44213 Replaceable VBC or PTFE Cassette, "V" Blade

Fine adjustability ensures that thin insulations can be stripped without damage to conductors. At the end of the stripping function, the stripping blades open and remain open during the return phase of the strip cycle facilitating easy/snag free wire removal from the tool.

#44213	AWG	Strip Range	lbs.	Pkg.	
	28 - 12	0.1-4mm ²	.02	1	



Itom No.	Paga	Item No.	Paga	Item No.	Page	Item No.	Paga	Item No.	Page	Item No.	Page
Item No. F					CARGE AN INC.						2011
10250			15	32706	31	32889	8	43127	40	44269	46
29240		32639	15	32708	31	32891	8	43128	40	45810	36
29250		32642	15	32710	31	32969	27	43129	40	45811	36
	24	32645	13	32711	31	32917	10	43132	42	45812	36
	24	32646	15	32712	31	32923	10	43136	41	45813	37
	24	32648	16	32714	32	32926	10	43137	40	45814	37
	24	32649	15	32716	32	32927	10	43138	41	45820	37
	24	32652	15	32718	32	32929	10	43139	40	45821	37
	25	32653	17	32720	32	32930	10	43140	41	45822	37
	24	32654	18	32721	32	32933	10	43141	41	45823	38
	25		17	32722	33	32945	10	43142	40	45824	38
	25	32656	18	32724	33	32947	10	43143	41	45890	38
	25	32657	16	32726	33	32970	22	43144	41	56801	29
		32658	16	32728	33	32971	22	43146	40	56812	28
30921 2	25	32659	16	32732	34	32972	22	43147	42	56813	29
30923 2	26	32660	14	32734	34	32974	22	43148	42	56815	28
30925 2	26	32661	14	32742	34	32975	22	43149	39	56818	28
30926 2	26	32662	18	32744	34	32976	22	43150	41	56825	28
30927 2	26	32663	14	32746	34	32978	22	43151	41	56830	29
	26	32664	14	32748	35	32979	22	43153	40	56833	29
30929 2	26	32665	14	32750	35	32980	22	43154	40	56871 2	25,29
30931 2	26	32666	18	32752	35	32981	11	43158	42	57872	15
30933 2	26	32667	14	32790	35	32983	11	43162	42	76208	9
30937 2	26	32668	14	32791	35	32984	11	43190	39	76210	9
30943 2	26	32669	14	32793	33	32985	11	43191	39	76212	9
30947 2	24	32670	14	32804	6	32986	11	43192	39	76215	9
		32671	16	32806	6	32987	11		43		9
		32672	16	32807	6	32988	11		23	91201	38
		32674	16	32808	6	32995	22		44		38
		32676	16	32810	6	32996	22		44		8
		32678	16	32814	4	34608	20		45	91256	7
		32680	16	32816	4	34609	20		45		
		32681	18	32818	4	34610	20		23		
		32682	18	32820	4	34611	20		43		
32604 15	Sector 1		18	32821	4		20	43620	43		
32605 15		32684		32826	5				44		
32606 1		32685		32828		34614		43622			
32608 1			18		5	34615			23		
32609 1			18	32832		34616			44		
32610 1			18	32834		34617			43		
32611 1			18	32835		34618			23		
32612 1		32690		32836		34619			45		
32615 1			18	32838		34620			42		
32616 1			18	32841			21		44		
32618 1		32693		32850		34622			42		
32621 1		32694		32852		34623			42		
32623 1		32695		32854		34624			42		
32625 1		32696		32859		34625			42		
32626 1 32627 1		32697		32860		34626			42		
			16	32861		34627			42		
32628 1 32629 1		32702 32703		32870		34651			45		
32629 1		32703 32704		32871 32872		34652		44212 44213			
						34653					
32633 1	<u> </u>	32705		32873	1	34654	21	44214	+0		





99060.wo - Product Guide



Supervised Supervised

99004.wo - Shop Tools Catalog



99934.wo - Hex Tools Catalog



99006.wo - Tech Tools Catalog



99919.wo - Insulated Catalog



99002.wo - Screwdrivers Catalog



99945.wo - ESD Catalog







99914.wo - TORX Catalog