


Duplex Multimode 62.5/125 Fiber Patch Cable (MTRJ/SC), 11M (36 ft.)

MODEL NUMBER: N310-11M



Highlights

- Premium PVC 62.5/125µm multimode patch cables
- Attenuation loss meets or exceeds the latest industry standards

Package Includes

 11-meter (35ft) Duplex MMF Cable MTRJ/SC 62.5/125 Fiber

Features

- Manufactured from 62.5/125 duplex (zipcord) fiber
- PVC jacket
- Length: 11-meters (35ft) Connectors: MTRJ to 2 SC
- Insertion loss testing performed on every connector (0.2db typical) and provided with cable
- Beveled edge on ends of glass makes insertion of plug a breeze
- Fiber made from glass (not a polymer)
- Color coded shrouds identify transmit and receive
- Fiber optic distributed data interface (FDDI) rated
- OFNR (riser rated)

Specifications

| OVERVIEW | | |
|-----------------------|--------------|--|
| UPC Code | 037332135087 | |
| Technology | Multimode | |
| Optical Mode | OM1 | |
| PHYSICAL | | |
| Cable Jacket Color | Orange | |
| Connector Color | White; Black | |
| Cable Jacket Material | LSZH | |
| Cable Jacket Rating | OFNR | |



| Clad Diameter (microns) | 125 | |
|---------------------------------|-------------------------------|--|
| Core Diameter (microns) | 62.5 | |
| Number of Fibers | 2 | |
| Cable Length (ft.) | 36.1 | |
| Cable Length (m) | 11.01 | |
| Cable Length (in.) | 433.1 | |
| Minimum Bend Radius | 20MM (Dynamic); 10MM (Static) | |
| Shipping Dimensions (hwd / in.) | 10.00 x 7.00 x 0.50 | |
| Shipping Dimensions (hwd / cm) | 25.40 x 17.78 x 1.27 | |
| Shipping Weight (lbs.) | 0.14 | |
| Shipping Weight (kg) | 0.06 | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -4 to 140 °F (-20 to 60 °C) | |
| Storage Temperature Range | -4 to 140 °F (-20 to 60 °C) | |
| Operating Humidity Range | 5% to 85% RH, Non-Condensing | |
| Storage Humidity Range | 35% to 65% RH, Non-Condensing | |
| Clorage Harmany Hange | CONTROL CONTROL | |
| COMMUNICATIONS | | |
| Network Compatibility | 1 Gbps (Gigabit); 10 Gbps | |
| Attenuation @ 850NM | 3.0dB/Km | |
| Insertion Loss | MTRJ0.50dB; SC0.20dB | |
| CONNECTIONS | | |
| Side A - Connector 1 | MTRJ DUPLEX (MALE) | |
| Side B - Connector 1 | SC DUPLEX (MALE) | |
| Endface Polish | PC | |
| FEATURES & SPECIFICATIONS | | |
| Push/Pull Tabs | No | |
| Breakout | No | |
| Trunk | No | |
| STANDARDS & COMPLIANCE | | |
| Product Compliance | RoHS; REACH | |
| WARRANTY & SUPPORT | | |



| Product Warranty Period (Worldwide) | Lifetime limited warranty |
|-------------------------------------|---------------------------|
|-------------------------------------|---------------------------|



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.